911 N. Midkiff Midland, Texas 79701 (432) 697-3420-Phone (432) 697-3400-Fax

Dakota Resources, Inc.


March 20, 2006

BLM Carlsbad Field Office 620 E. Greene Street Carlsbad, NM 88220

RE: TRIGG FEDERAL #1

To Whom It May Concern:

30-015-25006



Drilling pit will not be opened

- 1. Cover contaminated area w/ 12 mil. reinforced plastic.
- 2. Cover plastic w/ 6" caliche.
- 3. Cover caliche w/ 30" of top soil.
- 4. Reseed per BLM recommendation.

During the time of the cleanup of the old pit, we will also reduce the size of the caliche pad and reseed it to meet BLM specs.

Work will begin in approximately 30 days and will be completed within 90 days. We will notify the BLM prior to the actual start date.

Sincerely,

Rick Maddox Production Superintendent

OCD approval conditional. Well must meet BLM Requirements and obtain Their approval.







District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form © 144
June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Officer

For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Pit or Below-Gra	de Tank Registration or Closus	re lot to
Is pit or below-grade tank	k covered by a "general plan"? Yes 🗌 No	
Operator: Dakota Resources Telephone Address: 911 N. Miskiss Mislar Facility or well name: Triesa Fed #1 API#: 3	r below-grade tank \square Closure of a pit or below-grade: $(432)697-342$ Rail address: \underline{Cic} \underline{C}	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
County: FDDV Latitude	Longitude	NAD: 1927 🗌 1983 🗍
Surface Owner: Federal 🔀 State 🗌 Private 🔲 Indian 🗍		
<u>Pit</u>	Below-grade tank	
Type: Drilling X Production Disposal	Volume:bbl Type of fluid:	
Workover	Construction material:	
Lined M Unlined	Double-walled, with leak detection? Yes 🔲 If not, explain why not.	
Liner type: Synthetic Thicknessmil Clay		
Pit Volumebbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excave Additional Comments:	Yes I f yes, show depth below ground surface	description of remedial action taken including
I hereby certify that the information above is true and complete to the behas been/will be constructed or closed according to NMOCD guideling. Date: 3-31-06 Printed Name/Title Rick Maddox Supt. Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	s not relieve the operator of liability should the content	native OCD-approved plan
Approval: Printed Name/Title	Signature	Date: