CONDITIONS OF APPROVAL, IF ANY:

	St	ate of New Mexico and Natural Resource SERVATION DIV P.O. Box 2088				
<u>DISTRICT I</u>	Energy, Minerals a	and Natural Resource ্ত	i) Jephanien		20.0	NOE C4507
P.O. Box 1980, Hobbs NM 88240	OIL CON	SERVATION DIV	isin a	WELL API N 5. Indicate Ty		005-61527
DISTRICT II P.O. Drawer DD, Artesia NM 88210	OIL OOM	P.O. Box 2088	CION.	State	FEE .	X
DISTRICT III		ew Mexico 87504-2	JAUG 2003 3	~ \	& Gas Lease No.	<u> </u>
1000 Rio Brazos Rd., Aztec NM 87410		:	RECEIVED	92		
SUNDRY NOT (DO NOT USE THIS FORM	ICES AND REPORTS O	NIMELLE		0		
	I FOR PROPOSALS TO I RESERVOIR. USE " APP			7. Lease Nar	me or Unit Agreement	Name
•	01) FOR SUCH PROP	1	ر کرک	/	RIC	,
1. Type of Well:		<u> </u>	3/297874			
OIL GAS			-1585A0			
METT METT X	OTHER					
2. Name of Operator	. Detrolour Com			8. Well No		
3. Address of Operator	Petroleum Corp	oration		9. Pool Name	e or Wildcat	7
}	outh 4th., Artesi	a, NM 88210			PECOS SLC	PE ABO
4. Well Location				, , , , , , , , , , , , , , , , , , , ,		
Unit Letter : 660	Feet From The	NORTH Line an	d 660	Feet From The	EAS	T Line
24	T00 -	D055		AVES		
Section 31 Township	T6S Rang	R25E NMPN		4VES		COUNTY
10. Ele	vation (Show wheti	her DF, RKB, RT, GR	, etc.)			
	**. · · · · · · · · · · · · · · · · · ·			<u> </u>		
11. Check Appropriate	Box to Indicate N	ature of Notice, R	eport, or Other D	ata		
					•	,
NOTICE OF INTENTI	ON TO:		SUBSEQUE	ENT REPORT O	OF:	
	PLUG AND ABANDON	REMEDI	AL WORK	ALTERING		
TEMPORARII V ARANDON	OLIANIOE BY AND	<u> </u>	NCE DON LINC ODNE	DILIC AN	D ABANDONMENT	
	CHANGE PLANS		NCE DRILLING OPNS.	FLOGAN	DABANDONNENT	
PULL OR ALTER CASING		CASING	TEST AND CEMENT JOB			
OTHER		OTHER		•		
						
12. Describe Proposed or Complet date of starting any proposed wo			talis, and give pertine	enet aates, includ	ung esumatea	
1. Notify NMOCD at least 24 h	hours before start		e tor new direction:	s it anv abnorm	alities are noti	ced
during plugging operations. Mil						
BOP. POH w/ tubing.	no moo a an oaro	ty oquipmont Loud	·	, 2,0,102, 11410	.,	2 4 140
2. RU wireline truck & RIH w/ 4	1 1/2" gauge ring to	3500' to make sur	caeina ie claar th	en RIH w/ 4-1/2	O" CIRP & set i	alua @ acon
RIH w/ tubing to top of CIBP &						
3. RU wireline & RIH w/ perfora		•	•	-		
behind casing to cover the Glo		-				· ·
holes @ 100'; RIH w/ packer or	•	ueeze 50 sx cemer	it behind casing to	surface - POH	w/ tubing & pa	cker.
Spot 5 sx of cement to surface		,				
4. ND BOP & remove wellhead	i; install dry-hole ma	arker & clean locati	on.			
		A				
See Ai	Hached					
See 11	,,,,,,,	15				
		*				
Λ	\wedge	£				
I hereby certify that the information above a true ar	nd complete to the best of my i	spowledge and belief.				
SIGNATURE (NO. 4)	(Small	TITLE	Reaulator	y Techician	DATE	8/12/03
TYPE OR PRINT NAME DONNA	CACK		-37		TELEPHONE NO.	505-748-1471
					ICLEPHONE NO.	202-140-14/1
(This space for State Use) APPROVED BY		TITLE		DATE	= 0.00000000000000000000000000000000000	

SUNDRY NUTTO (DO NOT USE THIS FORM FOR PROPOS DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.) 1. Type of Well: Oil Well Gas Well X	CES AND REPURISON W ALS TO DRILL OR TO DEEPEN (ATION FOR PERMIT" (FORM C-)	OR PLUG BACK TO A	Ric	Omi vikideliham jarik	
2. Name of Operator	Other		8. Well No.	100 OFCIALES	
Yates Petroleum Corpo	7	10.			
3. Address of Operator	9. Pool name or	Wildent			
105 S. 4th Street Artes	a, NM 88210		Pecos Slope /	4bo 6086282728230	
4. Well Location Unit Letter A: 660	feet from the North	line and <u>660</u> 1	feet from the <u>Eas</u>		
Section 31			NMPM Cha	ves County	
		1838' GR			
	ppropriate Box to Indica				
NOTICE OF IN	ENTION TO:	SOB	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	X REMEDIAL WOR	K 🗆	ALTERING CASING	
TEMPORARILY ABANDON	_	COMMENCE DR		PLUG AND ABANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AI	ND		
OTHER:		OTHER:			
Describe proposed or completed or starting any proposed work). SEE I recompilation.					
Yate Petroleum Corporation p. 1. Notify the NMOCD at least water. 2. Set a 4-1/2" gauge ring to 3. Circulate the hole with 10.0 pt. 3. Perforate with 4 holes at 13 the base of the 8-5/8" casing to the surface. Spot 5 sx ceme. 4. ND the BOP and remove the	24 hrs before starting the asserting the assertion of the start of the	e work. Load the tube casing is clear then RI gel in the mud and s persx cement behind it 100' and squeeze v up the casing. — WO	oing and the casion with a 4-1/2" Copot 25 sx cemen the casing to cowith 50 sx cemen at 24 Mes - 74	CIBP and set at 3500'. It on top of the CIBP. It on the Glorieta and it behind the casing	
HARR 100' of continuside: Out of Cos @ 1000' AlAca 100' of	to do at nec		TAS	85 Q	
I hereby certify that the information	above is true and complete to	o the best of my knowled 5 CSG. 206-306-	lge and belief.	uter Ter	
SIGNATURE	TITLE Reg	ulatory Compliance	Supervisor_DATE	June 5, 2003	
Type or print name Ting Huerto	200	111	Telephone No	. 505-748-1471	
(This space for State use) APPPROVED BY	X	LE SULP PS	to a	JUN 1 1 2003	
Conditions of approval, if any:					