Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Oil Cons. N.M. DIV-Dist. 2 1301 W. Grand Avenue Artesia, 2ND 88210

FORM APPROVED OMB No. 1004-0135

ine United

Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or re enter and and a supplied to the supplie				5. Lease Serial No. NM-26069		
abandoned well. Us	pposals. AUG 200	assis. All Luca		6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side				7. If Unit or CA/Agreement, Name and/or No.		
Type of Well Oil Well X Gas W	(68<99#c	8. Well		0.		
2. Name of Operator				Margene AWM Federal #2		
Yates Petroleum Corporation				9. API Well No.		
3a. Address 3b. Phone No. (include area code)				30-005-63488		
105 S. 4th Str., Artesia, NM 88210 505-748-1471 4. Location of Well (Footage, Sec.,T.,R.,M., OR Survey Description)				10. Field and Pool, or Exploratory Area Pecos Slope Abo		
				11. County or Parish, State		
1980'FSL & 660'FEL (Unit I, NESE) of Section 20-T9S-R26E				Chaves County, New Mexico		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACTION						
	Acidíze	Deepen	Production (S	Start/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity	
X	Casing Repair	New Construction	X Recomplete		Other	
Subsequent Report	Change Plans	Plug and Abandon	Temporarily a	Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dispos	osal		
testing has been completed. Final Abandonment Notices shall be filed cmy after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 7/30/03 Set CIBP at 5720' and cap with 35' cement. Perforate Wolfcamp 5300'-5310' (40). 7/31/03 Acidize Wolfcamp with 1000g 15% IC HCL and balls. 8/4/03 Set CIBP at 5250' and cap with 35' cement. Perforate Abo 4412'-4415', 4452'-4460', 4516'-4522', 4546'-4550', 4566'-4570', 4588'-4592', 4622'-4630', 4652'-4656', 4693'-4697' for a total of 55 holes. 8/6/03 Frac Abo with 62,000g 55Q CO2 foamed 35# x-linked 7% KCL water carrying 160,000# 16/30 Brady sand + 2000g 7-1/2% HCL ahead of pad. ACCEPTED FOR RECORD ARMANDO A. LOPEZ PETROLEUM ENGINEER						
14. I hereby certify that the foregoing is true a	nd correct					
Name (Printed/Typed) Tina Hue	Title Regulatory Compliance Supervisor					
Signature 1 Date August 13, 2003						
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by						
Approved by Title Date Conditions of approval, if any, are attached. Approval of this notice does not warrant or						
certify that the applicant holds legal or equita	able title to those rights in the subje					