

Green Wooley Booger Fed "5" #1

Wildcat; Wolfcamp

Lea County, NM

API: 30-015-31498

Current Wellbore

2330' FSL

860' FWL

Sec 5, T19S, R24E

RECEIVED

JUN 23 2006

UCC-ARTCOIA

KB: 3786'

GL: 3768'

Bit Size: 12-1/4"

8-5/8" 32# K55 LTC 0' - 1336'
Cmt w/

200 sx 10% Prem +10% CAL + 1%
CaCl2 + .25# Flocele
14.6 ppg, 1.5 ft3/sx

405 sx Halliburton lite + 4.48# salt +
2% CaCl2 + .25# flocele
12.7#, 1.98 ft3/sx

200 sx Prem Plus + 2% CaCl2
14.8#, 1.34 ft3/sx

Circ 150 sx

2-3/8" SN @ 4905'

MA/Pin Collar @ 4939'

CIBP@ 5000'

CIBP@ 6146'

CIBP@ 6460'

Bit Size: 7-7/8"

5-1/2" 17# N80 LTC 0' - 8610'
Cmt w/

Stage 1

535 sx 50/50 Poz + 5% Lap-1 +
2% CFR 3 + 5# GLL +
.25# D-Air-3000

14.4#, 1.24 Ft3/sx

Stage 2

1240 sx 50/50poz + 5% Lap-1 +
2% CFR 3 + 5# GLL +
.25# D-Air- 3000

14.4#, 1.24 Ft3/sx

SHL:

N: 613000

S: 413072

Rig: Patterson 41
Cmt: Halliburton
Mud: Horizon
Wellhead:

Tubing

144 2-3/8" tubing
1 2-3/8" x 5-1/2" TAC @ 4673'
7 2-3/8" tubing
1 2-3/8" SN @ 4905'
1 MA/Pin Collar @ 4939'

Rods

1 1-1/4" 26' PR-16' Liner
1 7/8" x 6' Pony Rods
70 7/8" x 25' GRD Sucker Rods (Norris)
120 3/4" x 25' GRD Sucker Rods (Norris)
4 1-1/2" x 25' Sinker Bars
1 2" x 1-1/4" x 20' Pump (Don-Nan)

2-3/8" x 5-1/2" TAC @ 4673'

Perfs:

4776' - 79' (2 spf)
4782' - 84' (2 spf)
4792' - 94' (2 spf)
4798' - 00' (2spf)
4804' - 06' (2 spf)
4820' - 24' (2 spf)

4852' - 55' (2 spf)
4878' - 82' (2 spf)
4904' - 06' (2 spf)
4913' - 19' (2spf)

5025' - 35' (2spf)

6196' - 6202'
6236' - 6246'
6316' - 6354'

6382' - 6394'
6418' - 6430'

6496' - 6503'
6510' - 6526'
6450' - 6576'
6608' - 6620'
6628' - 6640'

DV Tool @ 6810'

CIBP w/ 20' cmt @ 8070'

Perfs:

8134' - 8142'

CIBP w/ 20' cmt @ 8240'

Perfs:

8258' - 8270'

TD @ 8610'

YPO: 11/17/05

Handwritten note: *See memo to all surrounding areas*