DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

BLANTHOSWEI	FIELDOFFICE
· ·	Expires: March 31, 2007

Lease	Sea	ial	No.	
	-	~	~ ~	_

BUREAU OF LAND MANAGEMENT			5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS			LC 068712		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE- Other instructions or	n reverse side.	7. If Unit or C.	A/Agreement, Name and/or No.		
1. Type of Well		_			
Oil Well Gas Well Other		8. Well Name and No.			
2. Name of Operator MURCHISON OIL & GAS, INC.			BOBCAT FED COM #1 9. API Well No.		
3a. Address 3b. Phone No. (include area code)			30-015-34993		
1100 MIRA VISTA BLVD., PLANO, TX. 75093-4698 972-931-0700 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area EMPIRE; MORROW, SOUTH		
			11. County or Parish, State		
SURFACE: 107' FSL & 704' FWL SEC. 11, T17S, R28E BOTTOM HOLE: 810' FSL & 810' FWL			EDDY CO., NM.		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE	NATURE OF NOTICE, I	REPORT, OR O	OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	<u></u>			
Acidize Deepen	Production (St	tart/Resume)	Water Shut-Off		
Notice of Intent Alter Casing Fracture T.			Well Integrity		
Subsequent Report Casing Repair New Cons	truction Recomplete		Other RUN 5-1/2" CSG		
Change Plans Plug and A	Abandon Temporarily A	bandon	& CEMENT		
Final Abandonment Notice Convert to Injection Plug Back	Water Disposal	1			
following completion of the involved operations. If the operation results in a multesting has been completed. Final Abandonment Notices shall be filed only after determined that the site is ready for final inspection.) Drill a 6-1/2" hole to a total depth of 10,441'. Run 5-1/2" casing as fo 1 Float Shoe 2 Jts 5-1/2" 17 #/FT P-110 LT& 1 Float Collar 58 Jts 5-1/2" 17 #/FT P-110 LT& 187 Jts 5-1/2" 17 #/FT P-110 LT& 187 Jts 5-1/2" 17 #/FT P-110 LT& 4 Jts 5-1/2" 17 #/FT P-110 LT& Set casing @ 10441'. Cemented with 1170 SXS Cemerete + 1% D153 SXS TX1 Lite + .3% D167 + .2% D65 + 1.4 GPSX D600 + .2% D6000 production head. Test to 5000 PSI. Held OK. Release rig @ 10:00 at	all requirements, including reclar llows: 2C 82' 1' 2C 2477' 2C 7709' 2C 171' 10441' + .05 GPSX D604 + .03 GPS G. Circulate 146 SXS to pits.	mation, have been o	PSX D801 and tail with 600 et slips. Cut casing and install		
14. Thereby certify that the foregoing is true and correct	1		23.24. ↑ ↑ 00 × 00 × 00 × 00 × 00 × 00 × 00 ×		
Name (Printed/Typed) MIGHAEL S. DAUGHERTY	Title VICE PRESIDENT	OPERATIONS	REC CD		
Signature Many /////	Date	09/28/2006	Ed State of the st		
THIS SPACE FOR FEDERAL	OR STATE OFFICE	EUSE	% ZI 9194		
			PECORD		
Approved by Conditions of approval, if any, are attached. Approval of this notice does not warra certify that the applicant holds legal or equitable title to those rights in the subject lewhich would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any States any false, fictitious or fraudulent statements or representations as to anymatte (Instructions on page 2) Accepted for record - NMOCD	office Office operson knowingly and willfull	y to make to any o	6 2006 department or agency of the United CK WRIGHT MENGINEER		