

1241

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK  
 DRILL  DEEPEN

b. TYPE OF WELL  
 OIL WELL  GAS WELL  OTHER  SINGLE ZONE  MULTIPLE ZONE

2. NAME OF OPERATOR  
 LCX ENERGY, LLC. LARRY GILLETTE 432-848-0218 218885

5. LEASE DESIGNATION AND SERIAL NO.  
 NM-108938

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
 -----

7. UNIT AGREEMENT NAME  
 -----

8. FARM OR LEASE NAME, WELL NO. 35858  
 1823 FEDERAL COM. # 181

9. AP WELL NO.  
 30-015-35227

10. FIELD AND POOL, O. WILDCAT  
 WILDCAT-WOLFCAMP

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA  
 SECTION 18 T18S-R23E

12. COUNTY OR PARISH 13. STATE  
 EDDY CO. NEW MEXICO

3. ADDRESS AND TELEPHONE NO.  
 101 NORTH MARIENFELD SUITE 200 MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)  
 At surface  
 660' FSL & 1880' FEL SECTION 18 T18S-R23E EDDY CO. NM  
 At proposed prod. zone 660' FNL & 1880' FEL SECTION 18 T18S-R23E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*  
 Approximately 6 miles South of Hope New Mexico

15. DISTANCE FROM PROPOSED\* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drig. unit line, if any)  
 660'

16. NO. OF ACRES IN LEASE  
 160

17. NO. OF ACRES ASSIGNED TO THIS WELL  
 320

18. DISTANCE FROM PROPOSED LOCATION\* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.  
 NA

19. PROPOSED DEPTH  
 MD-8755' TVD-4960'

20. ROTARY OR CABLE TOOLS  
 ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)  
 4034' GR.

22. APPROX. DATE WORK WILL START\*  
 WHEN APPROVED

23. PROPOSED CASING AND CEMENTING PROGRAM


SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
26"	20" conductor	NA	40'	Redi-mix to surface
17 1/2"	H-40 13 3/8"	48#	350'	400 Sx. circulate cement to surface
12 1/2"	J-55 9 5/8"	36#	1200'	475 Sx. " " " "
8 3/4 or 7 7/8"	N-80 5 1/2"	17#	8755 MD	600 Sx. Est top of cement 1000'

ROSWELL CONTROLLED WATER BASIN

SEE ATTACHED SHEET FOR DETAIL

APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS  
AND SPECIAL STIPULATIONS  
ATTACHED

If earthen pits are used in association with the drilling of this well, an OCD pit permit must be obtained prior to pit construction.



IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED Joe T. Jamieson TITLE Agent DATE 08/08/06

PERMIT NO. \_\_\_\_\_ APPROVAL DATE \_\_\_\_\_

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. CONDITIONS OF APPROVAL, IF ANY:

/s/ James Stovall ACTING FIELD MANAGER

NOV 03 2006

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ APPROVAL FOR 1 YEAR

\*See Instructions On Reverse Side

STATEMENT ACCEPTING RESPONSIBILITY FOR OPERATIONS

OPERATOR NAME: LCX ENERGY, LLC.  
ADDRESS: 110 NORTH MARIENFELD  
SUITE 200  
CITY, STATE, & ZIP: MIDLAND, TEXAS 79701

The above operator accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted on the leased land or portion thereof, as described below.

Lease No: NM-108938  
Well name: 1823 FEDERAL COM. # 181  
Legal Description of land: NE/4 of SECTION 18 T18S-R23E EDDY CO. NM  
Bond coverage: ~~\$-50,000.00~~ BLANKET STATEWIDE  
B.L.M. Bond File No.: ~~RLB0008129~~ NMAL00094

Authorized Signature

Joe T. Janica

Title: AGENT

Date: 08/18/06

DISTRICT I  
1625 N. French Dr., Hobbs, NM 88240

State of New Mexico  
Energy, Minerals & Natural Resources Department

Form C-102  
Revised October 12, 2005  
Submit to Appropriate District Office  
State Lease - 4 Copies  
Fee Lease - 3 Copies

DISTRICT II  
1301 W. Grand Avenue, Artesia, NM 88210

OIL CONSERVATION DIVISION  
1220 South St. Frances Dr.  
Santa Fe, NM 87505

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code 96086	Pool Name WILDCAT-WOLFCAMP
Property Code	Property Name 1823 FED COM	Well Number 181
OGRID No. 218885	Operator Name LCX ENERGY, LLC	Elevation 4034'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
0	18	18 S	23 E		1880'	EAST	660	SOUTH	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	18	18 S	23 E		1880	EAST	660	NORTH	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
320			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

**NOTE:**  
1) Plane Coordinates shown hereon are Transverse Mercator Grid and Conform to the "New Mexico Coordinate System", New Mexico East Zone, North American Datum of 1983. Distances shown hereon are mean horizontal surface values.

The diagram shows a grid with a dashed line for the 'PROJECT AREA' and a solid line for the 'PRODUCING AREA'. The producing area is a rectangle with corners at (4038.1, 1880), (4032.1, 1880), (4031.4, 660), and (4036.7, 660). The project area is a larger rectangle with corners at (4038.1, 1880), (4032.1, 1880), (4031.4, 660), and (4036.7, 660). The diagram also shows sections NE/4 Federal NM-108938 and SE/4 State VA-2593. A well location is marked with 'BL' at the top-left corner of the producing area and 'SL' at the bottom-left corner. Distances of 660' and 1880' are indicated along the axes.

**OPERATOR CERTIFICATION**  
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*Joe T. Janica*  
Signature Date 08/08/06  
Joe T. Janica  
Printed Name  
Agent

---

**SURVEYOR CERTIFICATION**  
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my belief.


June 22, 2006  
Date of Survey JSR  
Signature & Seal of Professional Surveyor  
*[Signature]*  
W.O. Num. 2006-0730  
Certificate No. EMACON McDONALD 12185

SECTION 18, TOWNSHIP 18 SOUTH, RANGE 23 EAST, N.M.P.M.

EDDY COUNTY

NEW MEXICO

L-2006-0730



DRIVING DIRECTIONS

Beginning at the intersection of US Highway 82 with County Road 12 (Armstrong Road) located in the West side of the town of Hope, New Mexico, proceed South on County Road 12 (Armstrong Road) for approximately 5.8 miles to an existing lease road extending East. Turn left and go East approximately 170 feet to an existing 2-track road extending North. Turn left and go North approximately 1.1 miles to a point from which the well location bears East 3,450 feet.

**LCX ENERGY, LLC**

**1823 FED COM #181**

Located 660' FSL & 1880' FEL, Section 18  
Township 18 S, Range 23 E, N.M.P.M.  
Eddy County, New Mexico



110 W. LOUISIANA, STE. 110  
MIDLAND TEXAS, 79701  
(432) 687-0865 - (432) 687-0868 FAX

Drawn By: JSR	Date: June 1, 2006
Scale: 1"=100'	Field Book:
Revision Date:	Quadrangle: Antelope Sink, N.M.
W.O. No: 2006-0730	Dwg. No.: L-2006-0730

APPLICATION TO DRILL

LCX ENERGY, LLC.  
 1823 FEDERAL COM. #181  
 UNIT "O" SECTION 18  
 T18S-R23E EDDY CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

1. Location of well: Surface 660' FSL & 1880' FEL SECTION 18 T18S-R23E
2. Ground Elevation above Sea Level: 4034' GR.
3. Geological age of surface formation: Quaternary Deposits:
4. Drilling tools and associated equipment: Conventional rotary drilling rig using drilling mud as a circulating medium to remove solids from hole.
5. Proposed drilling depth: MD-8755±' TVD-4960'±

6. Estimated tops of geological markers:

San Andres	575'	Abo	3875'
Glorietta	1715'	Wolfcamp	4700'
Tubb	3200'		

7. Possible mineral bearing formations:

Abo	Gas
Wolfcamp	Gas

8. Casing Program:

Hole Size	Interval	OD of Casing	Weight	Thread	Collar	Grade
26"	0-40'	20"	NA	NA	NA	Conductor
17½"	0-350'	13 3/8"	48#	8-R	ST&C	H-40
12½"	0-1200'	9 5/8"	36#	8-R	ST&C	J-55
8 3/4' & 7 7/8"	0-8755'±	5½"	17#	8-R Butt.	LT&C	N-80

APPLICATION TO DRILL

LCX ENERGY, LLC.  
 1823 FEDERAL COM. #181  
 UNIT "O" SECTION 18  
 T18S-R23E EDDY CO. NM

9. CASING CEMENTING & SETTING DEPTH:

20"	Conductor	Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
13 3/8"	Surface	Set 350' of 13 3/8" 48# H-40 ST&C casing. Cement with 400 Sx. of Class "C" cement + additives, circulate cement to surface.
9 5/8"	Intermediate	Set 1200' of 9 5/8" 36# J-55 ST&C casing. Cement with 475 Sx. of Class "C" cement + additives, circulate cement to surface.
5 1/2"	Production	Set 8755' ± 5 1/2" 17# N-80 LT&C casing. Cement with 600 Sx. of Class "C" Premium Plus cement + additives, estimate top of cement 1000' from surface.

10. PRESSURE CONTROL EQUIPMENT: Exhibit "E" shows a 900 series 3000 PSI working pressure B.O.P. consisting of an annular bag type preventor, middle blind rams, and bottom pipe rams. The B.O.P. will be nipped up on the 13 3/8" casing and tested to API specifications. The B.O.P. will be operated at least once each 24 Hr. period and the blind rams will be operated when the drill pipe is out of on trips. Full opening stabbing valve and upper kelly cock will be available in case if needed. Exhibit "E-1" shows a hydraulically operated closing unit and a 3" 3000 PSI choke manifold with adjustable chokes. No abnormal pressures or temperatures are expected while drilling this well. No problems in offset wells.

11. PROPOSED MUD CIRCULATING SYSTEM:

DEPTH	MUD WT.	VISC.	FLUID LOSS	TYPE MUD SYSTEM
40-350'	8.4-8.7	29-34	NC	Fresh water use paper to control seepage.
350-1200'	8.4-8.7	30-38	NC	Fresh water use paper to control seepage.
1200-5000' ±	9.0-9.2	29-34	NC	Cut brine circulate outer reserve
5000-8755'	9.0-9.3	29-38	* 15 cc or less	Cut brine use high viscosity sweeps to clean hole

\* Water loss may have to be controlled to log well and run casing.

Sufficient mud materials will be kept on location at all times in order to combat lost circulation, or unexpected kicks. In order to run DST's, open hole logs, and casing, viscosity, and water loss may have to be adjusted to meet these needs.

APPLICATION TO DRILL

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

12. LOGGING, CORING, AND TESTING PROGRAM:

- A. Open hole logs: Log vertical hole with Dual Induction, SNP, MSFL, LDT, Gamma Ray, Caliper from TVD back to the 9 5/8" casing shoe.
- B. Cased hole log Gamma Ray, Neutron from 9 5/8" casing shoe back to surface.
- C. Rig up mud logger on hole at 3700'±.
- D. No cores or DST's are planned at this time.

13. POTENTIAL HAZARDS:

No abnormal pressures or temperatures are expected. There is no known presence of H<sup>2</sup>S in this area. If H<sup>2</sup>S is encountered the operator will comply with the provisions of Onshore Oil and Gas Order No. 6. No lost circulation is expected to occur. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Estimated BHP 3500 PSI, and Estimated BHT 165°.

14. ANTICIPATED STARTING DATE AND DURATION OF OPERATION:

Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as soon after BLM approval and as soon as a rig will be available. Move in operation and drilling is expected to take 40 days. If production casing is run then an additional 30 days will be needed to complete well and construct surface facilities and/or lay flowlines in order to place well on production.

15. OTHER FACETS OF OPERATIONS:

After running casing, cased hole Gamma Ray, Neutron Collar logs will be run from TD back to all possible productive zones. The Wolfcamp formation will be perforated and stimulated in order to establish production. The well will be swab tested and potentialized as a gas well.

**Horizontal Drilling Procedure  
Abo Wildcat Horizontals  
(Eddy Co., NM)**

1. Drill 26" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
2. Drill 17-1/2" hole to 350'.
3. Drill 12-1/4" hole to 1200'. Run and set 1200' of 9-5/8" 36# J-55 ST&C casing. Cement with 375 sx of 35/65 Poz/C + 5% NaCl + 6% Bentonite, tail in with 100 sx. of Class "C" cement + 2% CaCl, circulate cement to surface.
4. Drill 7-7/8" or 8-3/4" hole to approx. 5000'. Set cement kick-off plug from TD to approx. 4400 ft with 150 sx H + 0.5% dispersant.
5. Dress cement top to desired kick-off point. Drill 7-7/8" curve and land lateral in pay zone (approx. 4900 ft TVD). Pickup lateral drilling assembly with an 8-3/4" or 7-7/8" bit and drill a +/-4000' lateral to 660' from lease line (approx. 4000 ft vertical section).
6. Run and set 5-1/2" 17# N80 or stronger production casing. Cement 5-1/2" with acid soluble cement through the lateral and 400 sx 50/50 Poz/C + 10% gel and tail in with 200 sx C + 200% CaCO<sub>3</sub> (acid soluble cement) + fluid loss additive + retarder (as required), attempting to bring top of cement to 1,000'.

**Contingency Strings:**

If lost circulation occurs in the surface hole:

- 2a. Run and set 350' of 13-3/8" 48# H-40 ST&C casing. Cement with 200 sx 35/65 Poz/C + 6% gel and tail in with 200 sx of Class "C" cement + 2% CaCl, circulate cement to surface.

If hole conditions dictate running a 7" contingency string in the 8-3/4" hole :

- 4a. Run approx. 5100 ft 7" 26# J55 or stronger casing to TD. Cement with 700 sx class 'C' cement + add's attempting bringing TOC to approx. 1,000 ft. This may be done in the vertical pilot hole or at the end of the 8-3/4" curve section.
- 4b. Run whipstock and cut a window in the 7" casing (or drill out with 6-1/8" BHA if 7" set at end of curve). Drill to TD.
- 5a. Step 5 will be omitted.
- 6a. Run and set approximately 4400 ft 4-1/2" 11.6# N/L80 liner from TD to approximately 200' above the window/7" casing shoe. Cement with approx. 110 sx C + 200% CaCO<sub>3</sub> (acid soluble cement) + add's attempting to bring TOC above liner top.

FRESH WATER WILL BE USED TO DRILL THE 350' HOLE AND THE 1200' HOLE.

THERE IS NO KNOWN PRESENCE OF ANY H<sub>2</sub>S IN THIS AREA. OTHER WELLS DRILLED HAVE NOT ENCOUNTERED ANY HYDROGEN SULFIDE WHILE DRILLING.



SURFACE USE PLAN

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

1. EXISTING ROADS & PROPOSED ROADS: Area maps; Exhibit "B" is a reproduction of a County General Hi-way Map. Exhibit "C" is a reproduction of a USGS Topographic Map, showing existing and proposed roads. All existing roads will be maintained in a condition equal to or better than current conditions. Any new roads will be constructed to BLM specifications.

A. Exhibit "A" shows the proposed well site as staked.

B. From Artesia New Mexico take U.S. Hi-way 82 West 34 miles to Hope New Mexico to the junction with State Road , turn Left (South) go 5 miles, turn Left East follow newly constructed road 3300' to location.

C. Exhibit "C" is a topographic map showing existing roads and proposed roads.

2. PLANNED ACCESS ROADS: Approximately 3300' of new road will be constructed.

A. The access roads will be crowned and ditched to a 12' wide travel surface with a 40' Right-of-Way.

B. Gradient of all roads will be less than 5.00%.

C. If turn-outs are necessary they will be constructed.

D. If needed roads will be surfaced with a minimum of 4" of caliche. This material will be obtained from a local source.

E. Center-line for new roads will be flagged. Earth-work will be will be done as field conditions require.

F. Culverts will be placed in the access road if they are necessary. The roads will be constructed to utilize low water crossings for drainage as required by topography.

3. LOCATIONS OF EXISTING WELLS IN A ONE MILE RADIUS. EXHIBIT "A-1"

A. Water wells - One 1.7 miles Northeast of location.

B. Disposal wells - None known

C. Drilling wells - None known

D. Producing wells - As shown on Exhibit "A-1"

E. Abandoned wells - As shown on Exhibit "A-1"

SURFACE USE PLAN

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

4. If on completion this well is a producer the operator will lay pipelines and construct powerlines along existing road R-O-W's or other existing R-O-W's. Exhibit "C" shows proposed routes of roads, flowlines and powerlines.

5. LOCATION AND TYPE OF WATER SUPPLY:

Water will be purchased locally from a commercial source and trucked over the access roads or piped to location in flexible lines laid on top of the ground.

6. SOURCE OF CONSTRUCTION MATERIAL:

If possible construction material will be obtained from the excavation of drill site, if additional material is needed it will be obtained from a local source and transported over the access roads as shown on Exhibit "C".

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the reserve pits.
- B. All trash, junk and other waste material will be contained in trash cages or trash bins to prevent scattering. When the job is completed all contents will be removed and disposed of in a approved sanitary land fill:
- C. Salts remaining after completion of well will be picked up by the supplier, including broken sacks.
- D. Waste water from living quarters will be drained into holes with a minimum of 10'. These holes will be covered during drilling and will be back filled when the well is completed. A Porto-John will be provided for the rig crews. This equipment will be properly maintained during the drilling and completion operations and will be removed when all operations are complete.
- E. Remaining drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry enough to be broken out for further drying. If the drilling fluids do not evaporate in a reasonable time they will be hauled off by transports to a state approved disposal site. Later pits will be broken out to speed drying. Water produced during completion will be put in reserve pits. Oil and condensate produced will be put in storage tanks and sold.

8. ANCILLARY FACILITIES:

- A. No camps or air strips will be constructed on location.

SURFACE USE PLAN

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

9. WELL SITE LAYOUT:

- A. Exhibit "D" shows the proposed well site layout.
- B. This Exhibit shows the location of reserve pit, sump pits, and living facilities.
- C. Mud pits in the active circulating system will be steel pits and the reserve pits will be unlined unless subsurface conditions encountered during pit construction indicate that a plastic liner is required to contain lateral migration.
- D. If needed the reserve pits will be lined with polyethelene. The pit liner will be no less than 6 mils thick and the liner will be extended at least 3 feet over the top of the dikes and secured in place to keep edge of liner in place.
- E. The reserve pit will be fenced on three sides and fenced with four strands of barbed wire during drilling and completion phases. The 4th side will be fenced after drilling operations are complete and the drilling rig has moved out. If the well is a producer the mud pits will remain fenced in until the mud has dried up enough to break out the pits and reclaimed according to BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE:

Rehabilitation of the location and reserve pits will be allowed to dry properly, fluids may be moved and disposed of in accordance with article 7-E as previously noted. The pit area will then be leveled and contoured to conform to the original and surrounding area. Drainage systems, if any will be reshaped to the original configuration with provisions made to alleviate future erosion. In case of the well completed as a producer the drilling pad will be necessary to construct production facilities. After the area has been shaped and contoured top soil from the spoil pile will be placed over the disturbed area to the extent possible so that revegetation procedures can be accomplished to comply with the BLM specifications.

If the well is a dry hole the pad and road area will be contoured to match the existing terrain. Top soil will be spread to the extent possible and revegetation will be carried out according to the BLM specifications.

Should the well be a producer the previously noted procedures will apply to those areas which are not required for production facilities.

SURFACE USE PLAN

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

11. OTHER INFORMATION:

- A. The project area is located on open rolling plain, relatively flat with drainage to the Northeast. Soils are tan-brown to grey, loamy sand silty with minor amounts of caliche. Vegetation consists of various native grasses, loco weed, broom snakeweed, yucca, prickly pear, cholla, and scorpion weed.
- B. The surface location is on State of New Mexico land. This land is used for grazing of livestock.
- C. An archaeological survey will be conducted on the access roads and drilling pad, the results will be filed with The Bureau of Land Management in the Carlsbad Field Office.
- D. There are no dwellings in the near vicinity of the location.

12. OPERATORS REPRESENTATIVE:

Before Construction:

TIERRA EXPLORATION, INC  
P.O. BOX 2188  
HOBBS, NEW MEXICO 88241  
JOE T. JANICA  
OFFICE PHONE 505-391-8503  
CELL PHONE 505-390-1598

During and after construction:


LCX ENERGY, LLC.  
110 NORTH MARIENFELD  
SUITE 200  
MIDLAND, TEXAS 79701  
FRANK NIX 432-682-8553


13. CERTIFICATION: I hereby certify that I or persons under my direct supervision have inspected the proposed drill site and access route, that I am familiar with the conditions which currently exist, that the statements made in this plan are to the best of my knowledge are true, and correct, and that the work associated with the operations proposed herein will be performed by LCX ENERGY, LLC. it's contractors/subcontractors is in the conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false statement.

NAME : Joe T. Janica

DATE : 08/08/06

TITLE : Agent






- ☞ Wind Direction Indicators (wind sock or streamers)
- △ H2S Monitors (alarms at bell nipple and shale shaker)
- Briefing Areas
- Remote BOP Closing Unit
- Sign and Condition Flags

EXHIBIT "D"  
RIG LAY OUT PLAT


LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM



**ARRANGEMENT SRRA**

SERIES 900 3000 PSI WP

EXHIBIT "E"  
 SKETCH OF B.O.P. TO BE USED ON  
  
 LCX ENERGY, LLC.  
 1823 FEDERAL COM. #181  
 UNIT "O" SECTION 18  
 T18S-R23E EDDY CO. NM



Typical choke manifold assembly for 3M WP system




EXHIBIT "E-1"  
CHOKE MANIFOLD & CLOSING UNIT

LCX ENERGY, LLC.  
1823 FEDERAL COM. #181  
UNIT "O" SECTION 18  
T18S-R23E EDDY CO. NM

SPECIAL DRILLING STIPULATIONS

THE FOLLOWING DATA IS REQUIRED ON THE WELL SIGN

Operator's Name: LCX Energy, LLC. Well Name & #: 1823 Fed. Com. #181  
Location 660 F S L & 1880 F E L; Sec. 18, T. 18 S., R. 23 E.  
Lease #: NM-108938 County: Eddy State: New Mexico  
Bottom Hole: 660 FNL & 1880 FEL, Section 18, T. 18 S., R. 23 E.

The Special stipulations check marked below are applicable to the above described well and approval of this application to drill is conditioned upon compliance with such stipulations in addition to the General Requirements. The permittee should be familiar with the General Requirements, a copy of which is available from a Bureau of Land Management office. EACH PERMITTEE HAS THE RIGHT OF ADMINISTRATIVE APPEAL TO THESE STIPULATIONS PURSUANT TO TITLE 43 CFR 3165.3 AND 3165.4.

This permit is valid for a period of one year from the date of approval or until lease expiration or termination whichever is shorter.

I. SPECIAL ENVIRONMENT REQUIREMENTS

- Lesser Prairie Chicken (stips attached)
- San Simon Swale (stips attached)
- Flood plain (stips attached)
- Other **See attached Aplomado Falcon Habitat Stipulations**

II. ON LEASE - SURFACE REQUIREMENTS PRIOR TO DRILLING

- The BLM will monitor construction of this drill site. Notify the  Carlsbad Field Office at (505) 234-5972  Hobbs Office (505) 393-3612, at least 3 working days prior to commencing construction.
- Roads and the drill pad for this well must be surfaced with 6 inches of compacted caliche upon completion of well and it is determined to be a producer.
- All topsoil and vegetation encountered during the construction of the drill site area will be stockpiled and made available for resurfacing of the disturbed area after completion of the drilling operation. Topsoil on the subject location is approximately \_\_\_\_\_ inches in depth. Approximately \_\_\_\_\_ cubic yards of topsoil material will be stockpiled for reclamation.
- Other.

III. WELL COMPLETION REQUIREMENTS

- A Communitization Agreement covering the acreage dedicated to the well must be filed for approval with the BLM. The effective date of the agreement must be prior to any sales.
- Surface Restoration: If the well is a producer, the reserve pit(s) will be backfilled when dry, and cut-and-fill slopes will be reduced to a slope of 3:1 or less. All areas of the pad not necessary for production must be re-contoured to resemble the original contours of the surrounding terrain, and topsoil must be re-distributed and re-seeded with a drill equipped with a depth indicator (set at depth of 1/2 inch) with the following seed mixture, in pounds of Pure Live Seed (PLS), per acre. If broadcasting, the seeding rate must be doubled.
  - A. Seed Mixture 1 (Loamy Sites)
    - Side Oats Grama (*Bouteloua curtipendula*) 5.0
    - Sand Dropseed (*Sporobolus cryptandrus*) 1.0
    - Plains lovegrass (*Eragrostis intermedia*) 0.5
  - B. Seed Mixture 2 (Sandy Sites)
    - Sand Dropseed (*Sporobolus crptandrus*) 1.0
    - Sand Lovegrass (*Eragostis trichodes*) 1.0
    - Plains Bristlegrass (*Setaria magrostachya*) 2.0
  - C. Seed Mixture 3 (Shallow Sites)
    - Side oats Grama (*Bouteloua curtipendula*) 5.0
    - Green Spangletop (*Leptochloa dubia*) 2.0
    - Plains Bristlegrass (*Setaria magrostachya*) 1.0
  - D. Seed Mixture 4 (Gypsum Sites)
    - Alkali Sacaton (*Sporobolus airoides*) 1.0
    - Four-Wing Saltbush (*Atriplex canescens*) 5.0

OTHER SEE ATTACHED SEED MIXTURE

Seeding should be done either late in the fall (September 15 - November 15, before freeze up, or early as possible the following spring to take advantage of available ground moisture.

- Other



#### RESERVE PIT CONSTRUCTION STANDARDS

The reserve pit shall be constructed entirely in cut material and lined with 6-mil plastic. Mineral material extracted from within the boundary of the APD during construction of the well pad and reserve pits and be used for the construction of this well pad and its immediate access road only, as long as that portion of the access road it is use on remains on-lease. Removal of any additional material from this location for construction or improvement of other well pads and other access or lease roads must first be purchased from BLM.

Reclamation: Reclamation of this type of deep pit will consist of pushing the pit walls into the pit when sufficiently dry to support track equipment. The pit liner is NOT TO BE RUPTURED to facilitate drying; a ten month period after completion of the well is allowed for drying of the pit contents.

The pit area must be contoured to the natural terrain with all contaminated drilling mud buried with at least 3 feet of clean soil. The reclaimed area will then be seeded as specified in this permit.

#### OPTIONAL PIT CONSTRUCTION STANDARDS

The reserve pit may be constructed in predominantly fill material if:

- (1) Lined as specified above and
- (2) A temporary or emergency pit may be constructed immediately adjacent to the reserve pit as long as the pit remains within the APD boundary. Mineral material removed from this pit may be used for the construction of this well pad only and its immediate access road, as long as that portion of the access road the material is used on remains on-lease. Removal of any material from the APD boundary for use on other well locations or roads must first be purchased from BLM.

Reclamation of the reserve pit consists of bulldozing all reserve pit contents and contaminants into the borrow pit and covering with a minimum of 3 feet of clean soil material. The entire area must be re-contoured, all trash removed, and reseeded as specified in this permit.

#### CULTURAL

Whether or not an archaeological survey has been completed and notwithstanding that operations are being conducted as approved, the lessee/operator/grantee shall notify the BLM immediately if previously unidentified cultural resources are observed during surface disturbing operations. From the time of the observation, the lessee/operator/grantee shall avoid operations that will result in disturbance to these cultural resources until directed to process by BLM.

#### TRASH PIT STIPS

All trash, junk, and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

## CONDITIONS OF APPROVAL - DRILLING

Operator's Name: LCX Energy LLC  
Well Name & No. 1823 Federal Com #181  
Surface Location: 660' FSL, 1880' FEL, Section 18, T. 18 S., R. 23 E., Eddy County, New Mexico  
Bottom Location: 660' FNL, 1880' FEL, Section 18, T. 18 S., R. 23 E., Eddy County, New Mexico  
Lease: NM-108938

### I. DRILLING OPERATIONS REQUIREMENTS:

1. The Bureau of Land Management (BLM) is to be notified at the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (505) 361-2822 for wells in Eddy County in sufficient time for a representative to witness:

A. Well spud

B. Cementing casing: 13-3/8\* inch 9-5/8 inch 5-1/2 inch

\* 13-3/8 inch surface casing will be set at 350 feet if lost circulation is encountered while drilling the surface hole.

C. BOP tests

2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.

3. Submit a Sundry Notice (Form 3160-5, one original and five copies) for each casing string, describing the casing and cementing operations. Include pertinent information such as; spud date, hole size, casing ( size, weight, grade and thread type), cement (type, quantity and top), water zones and problems or hazards encountered. The Sundry shall be submitted within 15 days of completion of each casing string. The reports may be combined into the same Sundry if they fall within the same 15-day time frame.

4. The API No. assigned to the well by NMOCD shall be included on the subsequent report of setting the first casing string.

5. A Communitization Agreement covering the acreage dedicated to this well must be filed for approval with the BLM. The effective date of the agreement shall be prior to any sales.

### II. CASING:

1. The 9-5/8 inch surface casing shall be set at approximately 1200 feet and cement circulated to the surface. If cement does not circulate to the surface the appropriate BLM office shall be notified and a temperature survey or cement bond log shall be run to verify the top of the cement. Remedial cementing shall be completed prior to drilling out that string.

2. The minimum required fill of cement behind the 5-1/2 inch production casing is to reach at least 500 feet above the top of the uppermost hydrocarbon productive interval.

### III. PRESSURE CONTROL:

1. All BOP systems and related equipment shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2. The BOP and related equipment shall be installed and operational before drilling below the 9-5/8 inch casing shoe and shall be tested as described in Onshore Order No. 2. Any equipment failing to test satisfactorily shall be repaired or replaced.

2. Minimum working pressure of the blowout preventer and related equipment (BOPE) shall be 2000 psi.

3. The appropriate BLM office shall be notified in sufficient time for a representative to witness the tests.

- The tests shall be done by an independent service company.
- The results of the test shall be reported to the appropriate BLM office.
- Testing fluid must be water or an appropriate clear liquid suitable for sub-freezing temperatures. Use of drilling mud for testing is not permitted since it can mask small leaks.
- Testing must be done in a safe workman-like manner. Hard line connections shall be required.

#### **IV. DRILLING MUD:**

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented. Monitoring equipment shall consist of the following:

- Recording pit level indicator to indicate volume gains and losses.
- Mud measuring device for accurately determining the mud volumes necessary to fill the hole during trips.
- Flow-sensor on the flow-line to warn of abnormal mud returns from the well.

8/29/06

acs

8/29/2006

acs