Form 3160-5 (April 2004)

OCD-ARTESIA UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED
OM B No. 1004-0137
Expires: March 31, 2007

5.	Lease Serial No.	

NMI.	C	6170)5B

6. If Indian. Allottee or Tribe Name

SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well Oil Well	Gas Well Other			8. Well Nar	ne and No.	
2. Name of Operator BEPCO, L. F	•			9. API We		
3a Address P. O. Box 2760 Midland, TX	3b. Phone ** ** ** ** ** ** ** ** ** ** ** ** **		30-015-35162 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) NENW, 1140' FNL & 2310' FWL, Sec 25, T24S, R30E Lat N 32.193056 deg, Lon W 103.83556 deg				Poker Lake (Delaware), SW 11. County or Parish, State Eddy County, New Mexico		
12. CHECK A	PPROPRIATE BOX(ES) T	O INDICATE NATUR	RE OF NOTICE, R	EPORT, OF	OTHER DATA	
TYPE OF SUBMISSION		TYI	PE OF ACTION			
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Sta Reclamation Recomplete Temporarily Ab Water Disposal	ŕ	Water Shut-Off Well Integrity ✓ Other Drilling Sundry	
•	, , ,	. •	•	• • •	ork and approximate duration thereof. ns of all pertinent markers and zones.	

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Spudded well on 10/14/06. Drilled 12-1/4" hole to 975'. Ran 25 jts 8-5/8", 32#, J-55, LTC csg set at 965'. Cemented with 320 sx 35/65 Poz + 6% D20 + 3% S1 + 0.2% D46 + 0.125 pps D130 (wt 12.6, yld 1.96) lead and 200 sx Class C + 2% S1 + 1/8 pps D130 (wt 14.8, yld 1.34) tail. WOC 26 hrs. Tested csg to 1000 psi - held ok, Drilled 7-7/8" hole to 8202'. Ran 159 its 5-1/2", 15.50#, J-55, LTC and 51 its 5-1/2", 17#, J-55, LTC set at 8202'. Cemented w/ 565 sx Litecrete + 2% D153 + 0.05% D604AM + 0.03% M45 + 2 pps D24 + 0.04 D801 (wt 10.2, yld 2.4) lead and 300 sx Litecrete + 2% D153 + 0.05% D604AM + 0.03% M45 + 2 pps D24 + 0.04 D801 (wt 10.5, yld 2.07) tail. Displace w/ acetic acid + 2% KCL. TOC by temperature survey 4100'. Rig released on 11/5/06.



14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)						
Annette Childers	Title Administrative Assistant					
Signature Connette Childers	Date 11-14-00					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by	Title ACCEPTED FOR RECORD					
Conditions of approval, if any, are attached. Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject lewhich would entitle the applicant to conduct operations thereon.	nt or ase Office					
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any States any false, fictitious or fraudulent statements or representations as to any matter	person knowingly and willfull to make to any department or agency of the United r within its jurisdiction.					
(Instructions on page 2)	EREDERICK WRIGHT					

PRECISION PRESSURE DATA, INC.

TEMPERATURE SURVEY REPORT

Company _	BASS ENTERPRISE	ES	Lease	POKER LAKE UNIT	Well#	102	
Field			County	EDDY	State	NEW MEXICO	
Survey Date	11/6/06		Time	5:49	Company Rep.	ROGER PRUITT	
·		Top of Cem	ent	4100			
		Total Depth					
				8000			
		Zero @		GL			
		Plug Down (@	11/6/06 @ 03:15			
		Casing Size		5 1/2			
		Hole Size		7 7/8			
		Sacks of Ce	ment	865			
		Ran By		C. HOMER			
		Calculated B	y	D. WEST			•

TEMPERATURE SURVEY REPORT

