Form 3160-5 (April 2004)

#### OCD-ARTESIA UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

5.	Lease Serial No.	

SUNDRY NOTICES AND I	REPORTS ON WELLS
Do not use this form for proposa abandoned well. Use Form 3160 -	Is to drill or to re-enter an  6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE- Other in	7. If Unit or CA/Agreement, Name and/or No. NMNM 71016X
1. Type of Well Gas Well Oth	
2. Name of Operator BEPCO, L. P.	Poker Lake Unit #191A  9. API Well No.
3a Address	3b. Phone No. (include area code) 30-015-34781
P. O. Box 2760 Midland, TX 79702	3b. Phone No. (include area code) 432-683-2277  FEB - 5 2007  9. API Well No. 30-015-34781  10. Field and Pool, or Exploratory Area Nash Draw (Dela, BS Avalon Sd)
4. Location of Well (Footage, Sec., T., R, M., or Survey Descript	OCD ARTESIA 11. County or Parish, State
NESE, UL I, 1980' FSL & 660' FEL, Sec 7, T24S, R30E Lat N 32.13488 deg, Lon W 103.54523 deg	Mer NMP  Nash Draw (Deta, BS Avaion Su)  11. County or Parish, State  Eddy Co., NM
12. CHECK APPROPRIATE BOX(ES)	TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION
Notice of Intent Acidize  Alter Casing	Deepen Production (Start/Resume) Water Shut-Off Fracture Treat Reclamation Well Integrity
Subsequent Report Casing Repair	New Construction Recomplete
Final Abandonment Notice Change Plans Convert to Injection	☐ Plug and Abandon ☐ Temporarily Abandon ☐ Operations ☐ Plug Back ☐ Water Disposal ☐ Operations
3% S1 + 5 pps D24 + 1/8 pps D130 (wt 12.6, yld 1.99 hrs. Tested csg to 1000 psi - held ok. Drilled 7-7/8" 7522'. Cemented w/ 1020 sx Litecrete + 40/60 D961/10.2, yld 2.37) lead and 375 sx Litecrete + 40/60 D96	an 23 jts 8-5/8", 32#, J-55, LTC csg set at 976'. Cemented with 430 sx 35/65 Poz + 6% D20 + 0) lead and 210 sx Class C + 2% S1 (wt 14.8, yld 1.32) tail. Circ 152 sx to surface. WOC 22.5 nole to 7544'. Ran 156 jts 5-1/2", 15.50#, J-55, LTC and 33 jts 5-1/2", 17#, J-55, LTC set at D124 + 0.05 gpsb D604AM + 0.03 gpsb M45 + 0.04 gpsb D801 + 2 pps D24 + 2% D153 (wt 17/D124 + 0.05 gpsb D604AM + 0.03 gpsb M45 + 0.04 gpsb D801 + 2 pps D24 + 2% D153 (wt + 2% KCL FW. TOC by temperature survey 5260'. Rig released on 1/16/07.
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed)	
Annette Childers	Title Administrative Assistant
Signature Cannette Childe	Date 1-23-2007
THIS SPACE FO	OR FEDERAL OR STATE OFFICE USECCEPTED FOR RECORD
Approved by Conditions of approval, if any, are attached. Approval of this n	
certify that the applicant holds legal or equitable title to those ri	ghts in the subject lease Office
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, mal States any false, fictitious or fraudulent statements or representa	te it a crime for any person knowingly and willfully to make to any HARTHER OF A SECTION OF NEED RED.

(Instructions on page 2)

Accepted for record - NMOCD

# PRECISION PRESSURE DATA, INC.

## TEMPERATURE SURVEY REPORT

Company	BASS ENTERI	PRISES	Lease_	POKER LAKE UNIT	Well #	191A
				EDDY	State	NEW MEXICO
	1/17/07			20:17		CECIL
		Top of Cer	ment	5260		
·		Total Depi	ch	7526		
		Zero @		GL		
		Plug Dowr	n @	1/17/07 @ 14:00		
		Casing Siz	:e	5 1/2		
		Hole Size		7 7/8		
		Sacks of C	Cement	1395		
		Ran By		C. HOMER		-
		Calculated	d By	D. WEST		

### **TEMPERATURE SURVEY REPORT**

