

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-015-31973 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No.
--	---	---

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. ☐ WELL OVER BACK RESV ☐	7. Lease Name or Unit Agreement Name POKER LAKE UNIT						
2. Name of Operator BEPCO, L.P.	8. Well No. 186						
3. Address of Operator P.O. BOX 2760 MIDLAND, TX 79702-2760	9. Pool name or Wildcat NASH DRAW/DEL/BS/AVALON SAND						
4. Well Location Unit Letter K 1750 Feet From The SOUTH Line and 1650 Feet From The WEST Line Section 32 Township 23S Range 30E NMPM EDDY County							
10. Date Spudded 08/18/2006	11. Date T.D. Reached 09/06/2006	12. Date Compl. (Ready to Prod.) 10/01/2006	13. Elevations (DF& RKB, RT, GR, etc.) 3270' GR	14. Elev. Casinghead			
15. Total Depth 7686'	16. Plug Back T.D. 7617'	17. If Multiple Compl. How Many Zones? 	18. Intervals Drilled By X	Rotary Tools 	Cable Tools		
19. Producing Interval(s), of this completion - Top, Bottom, Name 7368' - 7414' DELAWARE/BONE SPRING/AVALON SAND				20. Was Directional Survey Made YES			
21. Type Electric and Other Logs Run GR-CNL; LDT/GR-AIT			22. Was Well Cored NO				
23. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
8-5/8"	32#	517'	12-1/4"	150+100+250+270 SXS	0		
5-1/2"	17#/15.5#	7682'	7-7/8"	900+275 SXS	0		
				TOC@2840' BY TS			
24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	7469'	
26. Perforation record (interval, size, and number) 7368' - 7380' 0.380 12 HOLES 7406' - 7414' 0.380 8 HOLES	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 7368' - 7414' 109,999 GALS PW+ 9238# 14/30 LITE PROP						
Date First Production 10/01/2006	Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING	Well Status (Prod. or Shut-in) PRODUCING					
Date of Test 10/05/2006	Hours Tested 24	Choke Size 14/64"	Prod'n For Test Period	Oil - Bbl 30	Gas - MCF 100	Water - Bbl. 195	Gas - Oil Ratio
Flow Tubing Press. 210	Casing Pressure 110	Calculated 24-Hour Rate	Oil - Bbl. 30	Gas - MCF 100	Water - Bbl. 195	Oil Gravity - API - (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						Test Witnessed By	
30. List Attachments LOGS/INCLINATION REPORT							
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief							
Signature <i>Cindi Goodman</i>		Printed Name CINDI GOODMAN		Title PRODUCTION CLERK		Date 10/09/2006	
E-mail Address cdgoodman@basspet.com							

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt 512'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 3373'	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs 7426' Lime	T. Entrada	T.
T. Abo	T. LAMAR 3596'	T. Wingate	T.
T. Wolfcamp	T. BELL CANYON 3624'	T. Chinle	T.
T. Penn	T. CHERRY CANYON 4496'	T. Permian	T.
T. Cisco (Bough C)	T. L/CHERRY Canyon 5714'	T. Penn "A"	T.

T/Brushy Canyon 5737'
H Brushy Canyon 7158'

T/ Avalon Sand	7552'	OIL OR GAS
B/ Avalon Sand	7562'	SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology