District I 1625 N. French Dr., Hobbs, NPM 88240 1301 W. Grand Avenue, Artesia, NM 88210 zoo Road, Aztes, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM \$7585

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

ities, submit to

Form C-144 June 1, 2004

(10 points)

(O points)

0

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No. 2 Type of action: Registration of a pit or below-grade tank. Closure of a pit or below-grade tank.									
Operator: Ameristate Exploration Telephon (510) 623-5500 and allows: Address: 401 Congress Are, ste 2700, Austin TX 78701 Partity or well aspect East Millingan Unit # 230 APT 8: 30-015-34763 UNL or Congres C See 14 T 195 128 E County: Edd y Latitude N32: 37'52.7" Langing W/04'08'5/3" NAD: 1927 1940 Studies Owner: Policial State Private Indian									
Pit Type: Drilling (I) Production [Disposal [] Westower [] Basongency [] Lined (I) Unified [] Liner type: Synthetic [] Thickness /2 mil Cby [] Pit Volume	Private and teak Volume:bhi Type of finid: Countraction material: Dual-b-walled, with leak detection? You Theat, explain why not.								
Dogth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Loss than 30 first 50 first or more, but less than 100 feet 186 first or more. 150'	(20 points) (10 points) (Opoints)							
Wellhead protection area: (Leas than 200 feet from a private demonstic vester source, or less than 1000 feet from all other unter source.)	Yes No	(20 points)							

200 foot or mose, but less than 1000 feet

your are burying in place	omite officie	☐ If afficite,	name of facility_	NA	·(3) Attack a governi doscr seround surface.	ription of remedial ac	tion taken including
remodiation start date and end date. (4) Groundwater encountened: No X Yes I If yes, show depth below ground surface A. and attach sample results. (5) Attach sell sample results and a fingument of sample lecutions and encountered.								
Additional Comments:	Keter	to t	HACLED	Pit	Closure	Plans		
				. 	<u>_</u>			

							···	

60 fact or myss.

Runking Score (Total Points)

Appreval: Notify OCD 24 hours prior to beginning Samples are to be obtained from

pit closure.

pit area and analysis submitted to NMOCD prior to back-filling



P.O. Box 310 Hobbs, NM 88241-0310

Hobbs. New Mexico 505.392.8584 Cell 505,631,2442 Fax 505.392.3085

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Ameristate Exploration

WELL SITE: East Millman Unit #230

LEGAL DESCRIPTION: Unit C Sec 14 T19s R28e, 1261

FNL 2514 FWL, Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 120' X 120' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1400 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

AMERISTATE EXPLORATION L.L.C. EAST MILLMAN UNIT #230 API#30-015-34763 V-DOOR NORTH EAST

