

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA



## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED  
OMB No 1004-0137  
Expires: March 31, 2007

5 Lease Serial No

NMLC 068430

6 If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No.

NMNM 71016 X

8. Well Name and No.

Poker Lake Unit #291

9. API Well No.

30-015-34781 35546

10 Field and Pool, or Exploratory Area

Nash Draw (Dela, BS Avalon Sd)

11 County or Parish, State

Eddy Co., NM

## SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

JUN 26 2007

2 Name of Operator

BEPCO, L. P.

OCD-ARTESIA

3a Address

P. O. Box 2760 Midland, TX 79702

3b. Phone No (include area code)

432-683-2277

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

NESW, UL K, 1650' FSL & 1980' FWL, Sec 21, T24S, R30E, Mer NMP  
Lat N 32.200500 deg, Lon W 103.500888 deg

## 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <b>Drilling</b>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<b>Operations</b>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

- 13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

H-40 per operator 6/25/07  
Spud well on 5/8/07. Drill 17-1/2" hole to 545'. Ran 13 jts 13-3/8", 48#, J-80, LTC csg set at 293'. Cemented with 230 sx 35/65 Poz + 3% S1 + 5 pps D24 + 1/8 pps D130 (wt 12.7, yld 1.99) lead and 350 sx Class C + 2% S1 (wt 14.8, yld 1.34) tail. Circ 338 sx to surface. WOC 33.5 hrs. Tested csg to 1000 psi - held ok. Drill 12-1/4" hole to 3775'. Ran 89 jts 8-5/8", 32#, J-55, 8rd, LTC csg set at 3773'. Cemented with 1525 sx 50/50 Poz + 10% D20 + 5% D44 + 0.125 pps D130 + 0.2% D46 (wt 11.9, yld 2.46) followed by 907 sx 35/65 Poz + 6% D20 + 5% D44 + 0.02% D46 + 5 pps D24 + 0.125 pps D130 (wt 12.7, yld 1.96) lead and 315 sx Class C + 2% CaCl (wt 14.8, yld 1.35) tail. Circ 1494 sx to surface. WOC 34.5 hrs. Tested csg to 1000 psi - held ok. Drilled 7-7/8" hole to 7766'. Ran 144 jts 5-1/2", 15.50#, J-55, 8rd, LTC and 38 jts 5-1/2", 17#, J-55, 8rd, LTC set at 7765'. Cemented w/ 540 sx Litecrete + 2% D153 + 0.05 gpsb D604AM + 0.03 gpsb M45 + 0.04 gpsb D801 + 2 pps D24 (wt 10.2, yld 2.37) lead and 200 sx Litecrete + 2% D153 + 0.05 gpsb D604AM + 0.03 gpsb M45 + 0.04 gpsb D801 + 2 pps D24 (wt 10.5, yld 2.07) tail. Displace w/ 24 bbls acetic acid + 160 bbls 2% KCL FW. TOC by temperature survey 3689'. Rig released on 6/3/07.

14 I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Annette Childers

Title Administrative Assistant

Signature

Annette Childers

Date

6-14-07

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

Office

ACCEPTED FOR RECORD

Date JUN 25 2007

WESLEY W. INGRAM

PERMISSIONS SECTION

Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

# PRECISION PRESSURE DATA, INC.

## TEMPERATURE SURVEY REPORT

Company BASS ENTERPRISES Lease POKER LAKE Well # 291  
Field \_\_\_\_\_ County EDDY State NEW MEXICO  
Survey Date 6/4/2007 Time 17:06 Company Rep ROGER PRUITT

Top of Cement 3689

Total Depth 7670

Zero @ GL

Plug Down @ 6/4/07 @ 14:15

Casing Size 5 1/2

Hole Size 7 7/8

Sacks of Cement 700

Ran By R. GREGORY

Calculated By C. KENNEDY

# TEMPERATURE SURVEY REPORT

