OCD-ARTESIA

			i a	•
Form 3160-5 (November 1994)	UNITED STATE	=		FORM APPROVED OMB No. 1004-0135
	DEPARTMENT OF THE I		/0007	Expires July 31, 1996
SUNDR	BUREAU OF LAND MANA YINOTICES AND REPO		JUN 20 2007	5. Lease Serial No. LC029339A
abandofied well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name
	lPEIOATE≯Otherdastr	uctions on revers	e'side}	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well Oil Well Gas Well	7 04			8. Well Name and No.
2. Name of Operator				JACKSON A #3
BURNETT OIL CO., INC.				9. API Well No.
3a. Address 801 CHERRY STREET, SIUTE 1500 3b. Phone No. (include area code)				30-015-04132 S2
UNIT #9 FORT WORTH, TEXAS, 76102 (817) 332-5108 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				10. Field and Pool, or Exploratory Area GRAYBURG JACKSON
4. Location of Well (Foolage, Sec., 1., K., M., or Survey Description)				11. County or Parish, State
UNIT J, 1980' FSL, 2000' FEL, SEC 13,T17S,R30E				Eddy County, N.M.
12. CHECK AI	PPROPRIATE BOX(ES) TO	O INDICATE NAT	URE OF NOTICE, I	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	☐ Acidize	Deepen .	Production (Sta	ut/Resume) ACCEMPESSURGER RECORD
Noise of miles	Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
☐ Final Abandonment Notice	Change Plans	Plug and Abandon	_	
	Convert to Injection	☐ Plug Back	Water Disposal	any proposed work and approximate field in spector
We propose to final pl This well bore was drilled running a 4-1/2" liner inside Grayburg oil well in 8/199 (1) Notify BLM and NMC (2) Set CIBP @ top of 4-1 top of 4-1/2" liner is @ (3) Tag TOC. Move up he (4) Set 50' cement plug in (5) Install Dry hole market	inal Abandonment Notices shall I for final inspection.) ug and abandon this w in 9/1937 as an oil well. It die the 7" casing. Well passe 99 by seting a CIBP @ 327 DCD of start to P&A. /2" liner(Approx 2820') and 2826'.) ole and perforate in 7" casi top of 7" and 10' casing. r and restore location as per	ell bore as shown was converted to a ded a NMOCD brader o' in 4-1/2" liner. The didump 50' of cement of approx 800' are BLM requirements	n below or as requirements, including recombers as requirements. Grayburg Jackson Son head test in April 1 he present well bore at on top. (This may find circulate cement in the properties of the present in the pres	uired. AU water injection well in 1/1968 by 998 and was converted to a non-unit is perforated from 2837' to 3016'. Ave to be in bottom of 7" casing since and out of casing ACHED FUR SEE ATTACHED FUR CONDITIONS OF APPROVAL on. CONDITIONS OF APPROVAL of the essence to complete this work.
	ing is true and correct ARK A. JACOBY	Title	ENGINEER	ING MANAGER
Signature Marle a	Jacolin	Date	6/1	3/2007
	THIS SPACE	FOR FEDERAL OR	STATE OFFICE UP	16
Approved by			Title	Date 0 2007
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.				
Title 18 U.S.C. Section 1001, ma fraudulent statements or representa	kes it a crime for any person kno ations as to any matter within its ju	wingly and willfully to risdiction.	make to any department	or agency of the things States and Called Hetitious or

(Instructions on reverse)

SUNDRY NOTICE SPECIAL STIPULATIONS

- 1. Approval is granted to P/A this well with the following modifications to the procedure:
- 2. The CIBP proposed for 2820' should be replaced with perfs and a 34 sack cement squeeze, leaving at least 25 sacks of cement inside of the casing, for the shoe of the 7 " casing, the perfs and the top of the 4.5' liner; to at least 2770 feet. Tag.
- 3. The plug proposed for 800' should be moved to 613' with perfs and a 53 sack cement squeeze, leaving at least 25 sacks of cement inside of the casing, for the surface casing shoe. Tag
- 4. The plug proposed for 60' should be moved to 100' with perfs and circulating cement to the surface through the annulus.

* All plugs, including the surface plug, should leave at least 25 sacks of cement inside the casing and be at least 100 feet, plus an additional 10% for each 1000 feet of depth.

Plugging procedures must conform to 43 CFR 3162.6.d and Onshore Order No. 2.III.G or NMOCD orders if they are more stringent.

All of the work approved here must be completed within 90 days

Engineering can be reached at 505-706-2779 for any variances.

F Wright 6/15/07

STATE OF THE PARTY OF THE PARTY

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, NM 88220

Interim Reclamation Procedures for Permanently Abandoned Federal Wells

- 1. After Subsequent Report of Abandonment, Form 3160-5, is filed and approved by the BLM the surface protection specialist (SPS) will conduct a surface inspection of the abandonment. The SPS will establish the reclamation requirements the operator will need to complete. **DO NOT START RECLAMATION UNTIL THE SPS HAS INSPECTED THE LOCATION.**
- 2. The reclamation requirements will be given to an environmental protection specialist (EPS). The EPS will issue the operator a Notice of Written Order outlining the reclamation requirements. **DO NOT START RECLAMATION UNTIL A NOTICE OF WRITTEN ORDER FOR RECLAMATION HAS BEEN RECEIVED.** The EPS will be responsible for all further abandonment work and inspections.
- 3. Notification: CONTACT THE EPS 3 DAYS PRIOR TO RECLAMATION WORK. This notification gives the EPS an opportunity to discuss by phone or on location the reclamation requirements, any special concerns and the timeframes. It also allows the EPS an opportunity to witness various aspects of the reclamation work to determine if an adequate seedbed has been prepared and all reclamation requirements have been completed. CONTACT THE EPS AT LEAST 3 DAYS PRIOR TO SEEDING. This allows the EPS to witness the seeding operation to make sure the location is seeded properly and with the appropriate seed mixture. DO NOT START RECLAMATION UNTIL THE EPS HAS BEEN NOTIFIED.
- 4. After reclamation work has been completed, submit the I & E copy of the Notice of Written Order to the BLM. It will need to be signed by a company representative and dated. Also submit one original and five copies of the Final Abandonment Notice, Form 3160-5. The report should state that all reclamation work has been completed, and the location is ready for a final abandonment inspection.
- 5. The BLM will continue to monitor the location to ensure the location vegetates successfully, and salts from the reserve pit do not leach to the surface. The location will be monitored until such time as vegetation (20%) is established evenly across the location (including the reserve pit and access road). Once EPS determines that vegetation (20%) is evenly spread across the location, final abandonment will be authorized.

If there are any questions please feel free to contact any of the following:

Jim Amos Supervisory Environmental Protection Specialist (505) 234-5909

Barry Hunt Surface Protection Specialist (505) 234-5965

Todd Suter Surface Protection Specialist (505) 234-5987

Trishia Bad Bear Natural Resource Specialist – Lea County (505) 393-3612 Cody Layton Natural Resource Specialist (505) 234-5959

Paul Evans Environmental Protection Specialist (505) 234-5977

Terry Gregston Environmental Protection Specialist (505) 234-5958

10/18/2006