## Form 3160-5 (April 200 SUNDRY NOTICES AND REPORTS ON WELLS

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

FORM APPROVED
OMB NO. 1004-0137
Expires March 31, 2007

5 Lease Serial No.

NMNM025604
------------

6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side  1 Type of Well    X Oil Well				7 If Unit or CA/Agreement, Name and/or N  NMNM70945X 8 Well Name and No.		
						Empire Abo N 901  9. API Well No
				3a. Address 501 Westlake Park Blvd.; Houston, T	1	3b Phone No ( <i>include area code</i> )  (281) 366-0391
4 Location of Well (Footage, Sec., T. R., M., or Survey L				io. Tield and Fool,	or Exploratory Area	
Sec 10 T18s R27E SWNW 2390 FNL 940 FWL				11. County or Parish, State  Eddy County NM		
12. CHECK APPROPRIATE	BOX(ES) TO INDICA	TE NATURE OF I				
TYPE OF SUBMISSION		TYF	PE OF ACTION	<del></del> -		
Notice of Intent	Acidize	Deepen	Production (S	tart/Resume)	Water Shut-Off	
X Subsequent Report	Alter Casing  Casing Repair	Fracture Treat  New Construction	Reclamation Recomplete		Well Integrity Other	
Final Abandonment Notice	Change Plans  Convert to Injection	X Plug and Abandon Plug Back	Temporarily A  Water Dispose			
determined that the final site is ready for final inspect 7/11/07 MIRU PU. NU BOP. 7/12/07 TIH w/retrieving head on WS. 7/13/07 TIH w/perf sub on WS to 5 Spotted cmt plug f/4201-3960' w/2 pump into holes in 5-1/2" csg 361 spot cmt across holes. 7/14/07 TOH w/pkr. TIH w/perf su TOH to 1300'. 7/15/07 TIH & tagged cmt @ 2958'. TOH. ND BOP. PU 5 joints WS to PU. 7/16/07 Dug out wellhead. Cut of	work string. Release 5757'-tagged cmt on 25 sx Class C neat. 12-3624'-pressured to 12 on WS to 3670'. 10 TOH to 1160'. Spotted cmt	top of CIBP. ( TOH. TIH w/pl up to 2000 psi v  Spotted cmt plug potted cmt plug plug f/160'-su  hors. Installe	circ hole w/9 kr on WS & set w/no rate. Ro ug f/3670-2960 f/1160-920' rface w/20 sx d P&A marker. PPROVED AS TO PLUGGIN VELL BORE. LIABILITY UNITAINED UNTIL SURFACE	.5 ppg mud. c @ 3214'. A seceived appropriate w/75 sx Class Class Class Class Class Class Class Class Class CopTHIS DER BOND	TOH to 4201'. Attempted to Eval f/BLM to Lass C neat. S C neat.	
14 I hereby certify that the foregoing is true and correct		Title	IS COMPLETED			
Name (Printed/Typed)  Leah Brumlow		Permitting Representative				
Seah Brumlow		Date 09/20/2007				
THIS	S SPACE FOR FEDER	AL OR STATE OF	FICE USE			
Approved by S DAVID Reproved.  Conditions of approval, if any, are attached Approved certify that the applicant holds legal or equitable title to	itah Thur the snot warran	it or Office	EUM ENGINEE	,	SEP 2 7 2007	
which would entitle the applicant to conduct operations if  Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section  States any false, fictitious or fraudulent statements or rep	hereon <sup>t</sup> on 1212, makes it a crime for	any person knowingly a	ACCEO	ted for re- VMOCD	of the United	



API No. 30-015-22058

2390' FNL & 940' FWL Sec 10 - T18S - R27E Eddy County, New Mexico

