OCD-ARTESIA

Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

5. Lease Serial No. LC-029342B

6. If Indian, Allottee or Tribe Name

DEC 4/2007

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				UEC 4\2007		
SUBMIT IN TRIPLICATE – Other instructions on page 2.			7. If Unit of C	7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well	<u> </u>				<u> </u>	
Oil Well Gas V	Injection	8. Well Name LOCO I	and No. Hills B Federa	1 5		
2. Name of Operator CBS Operating Corp.			9. API Well N 30-	9. API Well No. 30-015-20672		
3a. Address P O BOX 2236	ne No. (include area code	•	10. Field and Pool or Exploratory Area			
Midland, TX 79702 432/685-0878				GB-J-SR-Q-GB-SA 11. Country or Parish, State		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 1980' FSL & 1980' FEL UL J Sec. 9 T17S R30E			_	Eddy, NM		
12. CHE	CK THE APPROPRIATE BOX(ES) TO	O INDICATE NATURE	OF NOTICE, REPORT O	OR OTHER DATA		
TYPE OF SUBMISSION		TYP	E OF ACTION	ON		
Notice of Intent	Acidize	Deepen	Production (Start/Res	sume) Water Shut-Off		
	Alter Casing	Fracture Treat	Reclamation	Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete	Other		
	·	Plug and Abandon	Temporarily Abandon	n		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
BLM. Ok to plug. RIH with p 11-2-2007 - Tagged @ 334' packer. 11-3-2007 - Tagged @ 255' cement. WOC. Tagged @ 255' 11-6-2007 - Tagged @ 255'. spot 60 sxs cement w/LCM. S 11-7-2007 - Tagged @ 255'. Tagged @ 200'. Pumped 30 st 11-8-2007 - Tagged @ 176'. CaCl 2%. WOC. Tagged @ 16' 11-9-2007 - Tagged @ 60'. P Pumped 35 sxs cement w/LCM 11-12-07 - Tagged @ 60'. Ci	Marrs. POH with 14 jts tubing. I backer. Call BLM. Pumped 50 sx. Tested casing, found hole @ Perforate @ 250'. Pumped 55'. Pumped 35 sxs cement w/LCM RIH with packer. Spot 25 sxs cer DFN. Mix 30 sxs cement. WOC. Takes cement. SDFN. Mix 30 sxs cement w/LCM. W(55'. Pumped 30'. Set packer. Pump	cement to 600'. SDF 120'. Perforate @ 33 is sxs cement. WOC. I. SDFN. ment w/LCM. WOC. gged @ 220'. Pumpe DC. Tagged @ 165'. M + CaCL 2%. SDFN ed 30 sxs cement, no	FN. 12'. Pumped 60 sxs c Tagged @ 255'. Pur RIH and tagged @ 25 and 30 sxs cement w/I Pumped 30 sxs cement J. circulation. WOC. Ta	sement under mped 40 sxs 5'. RIH and Accepte LCM. WOC. No nt w/LCM + agged @ 60'.	d for record MOCD	
14. I hereby certify that the foregoing is to Name (Printed/Typed)	rue and correct.					
M. A. Širgo, II	I	Title Engine	eer	1101 0.7	2007	
Signature	Jugo D	Date Novemb	ber 14, 2007	7	2007	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE LES BABYAK PETROLEUM ENGINEER						
Approved by		T T		Pr (NOZECOW Z)	***	
		 Title		Date		
Conditions of approval, if any, are attached that the applicant holds legal or equitable ti		nt or certify		***************************************		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,

entitle the applicant to conduct operations thereon.

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.