District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia. NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office.

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes \(\subseteq No \times \)
Type of action: Registration of a pit or below-grade tank \(\subseteq \) Closure of a pit or below-grade tank \(\subseteq \)

122 (94 2005 mg/l bloom discounting and mg/l blo		
Operator. Parallel Petroleum Corporation Telephone: 432-684-3905 e-mail address: ddurham@plll.com Address: 1004 N. Big Spring Street, Suite 400, Midland, Texas 79701		
Facility or well name: Go For Wind 1525-29 Fed Com #1 API #:3000563966 U/L or Qtr/Qtr D Sec 28 T 15S R 25E		
County Chaves Latitude 32° 59' 29.55" N Longitude 104° 27' 19.00" W NAD: 1927 X 1983		
Surface Owner Federal State Private Indian Below-grade tank Surface Owner Federal State Private Indian Below-grade tank		
Type; Drilling ⊠ Production □ Disposal □	Volume, bbl Type of fluid:	
Workover	Construction material:	
Lined \(\sum \) Unlined \(\sum \)	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay		
Pit Volume 25,000 bbl		
	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points) 10
high water elevation of ground water.) 65°	100 feet or more	(0 points)
Wellhead protection area. (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points) 0
Discourse to an Comment of the control distance to the	Less than 200 feet	(20 points)
Distance to surface water (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet 700°	(10 points) 10
in igation canals, ditches, and perennial and ephemeral watercourses.)	1000 fect or more	(0 points)
	Ranking Score (Total Points)	20
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if		
your are burying in place) onsite 🔲 If offsite, name of facility (3) Attach a general description of remedial action taken including		
remediation start date and end date. (4) Groundwater encountered: No 🗌 Yes 📋 If yes, show depth below ground surfaceft. and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments. This well shares a drilling location and pit with the Native Dancer 1525-28 #1, API # 3000563916		
The fluids in the reserve pit will be allowed to dry or taken to disposal or used at another Parallel Petroleum Corp. drilling well in the area. The drill cuttings and plastic		
will be placed in a plastic lined burial trench located next to the reserve pit. The trench will then be covered with plastic and backfilled with a minimum of 3° of soil		
The state of the s		
The reserve pit area will then be backfilled and re-contoured and seeded to BLM specifications.		
		- · · · ·
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □, or an (attached) alternative OCD-approved plan □.		
2, 2, 3, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4,		
Date 2-8-08		
Printed Name/Title Gary Miller, Agent Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations		
Approval.		
Printed Name/Title	Signature Signed By Mile Bes	FEB 1 2 2008

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling. If burial trench is constructed in pit area – Sample analyses are to be submitted to NMOCD PRIOR to lining the trench.

Burial trench excavation bottom must be 50' above the highest seasonal depth ground water may be encountered.