Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
	nergy, Minerals and Natural Resources	May 27, 2004 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	OV. GOVGEDALLEVOLEDANIGION	30-015-35789
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name Weems
PROPOSALS.) 1. Type of Well: Oil Well Gas W	ell 🛛 Other	8. Well Number 1
2. Name of Operator		9. OGRID Number
OGX Resources, LLC	APR 1.5 2008	217955
3. Address of Operator POB 2064 Midland, TX 79702	OCD-ARTESIA	10. Pool name or Wildcat Otis; Morrow (Gas)
4. Well Location	00011111111	Otis, Morrow (Gus)
Unit Letter B: 1073 feet from the North line and 1501 feet from the East line		
Section 34 Township 22S Range 27E NMPM Eddy County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
3106' GL		
Pit or Below-grade Tank Application □ or Closure □		
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
	NGE PLANS COMMENCE DR	
PULL OR ALTER CASING MUL	TIPLE COMPL CASING/CEMEN	T JOB 🛛
OTHER:	□ OTHER:	П
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1st INTERMEDIATE CASING & CEMENT 4-12-08 Run float shoe, 1 jt. 9 5/8" 36# J-55 LTC csg., float collar, 51 jts. 9 5/8" J-55 36# LTC csg. & 14 jts. 9 5/8" J-55 40# LTC csg to a set depth of 2710'. Cemented as follows: Lead- 800 sks Econocem + 5% salt, wt 12.4, yield- 2.12. Tail- 200 sks Swiftcem + 1% CaCl 2. Plug down- did not bump. Circulated 198 sks to surface. NU B-section & test to 1300 psi. NU BOP & test to 5000 psi. WOC 26 hrs. Reduce hole size to 8 3/4" & resume drilling.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .		
SIGNATURE Lingula high	TITLE Consultant	DATE4-15-2008
Type or print name Angela Lightner For State Use Only	E-mail address: angela@rkford.com	Telephone No. 432-682-0440
APPROVED BY:	TITLE	DATE
Conditions of Approval (if any):		