Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD-ARTESIA

C

	OM B No. 1004-0135 Expires: January 31, 2004
5.	Lease Serial No.
	NM NM 113387
6.	If Indian, Allottee or Tribe Name
	N/A
7	If I Init or CA/Agreement Name and/or No

SUNDRY		NM NM 113387 6. If Indian, Allottee or Tribe Name N/A						
Do not use the abandoned we	6.							
SUBMIT IN TRIPLICATE- Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or No. N/A 8. Well Name and No.		
1. Type of Well ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ Other ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐								
2. Name of Operator Corkran Energy, LP						Frontier 9 Federal Com #1 9. API Well No.		
3a. Address	ude area code)							
4. Location of Well (Footage, Sec.,	512-329-6140		10. Field and Pool, or Exploratory Area Huapeche, Morrow					
4. Location of well (rootage, Sec., 1980' FSL & 1980' FEL	1., R., M., Or Survey Description	JUN 10 2008			11. County or Parish, State			
Sec. 9, T- 23S, R- 22E	OCD-ARTESIA			Eddy County, NM				
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA								
TYPE OF SUBMISSION TYPE OF ACTION								
Notice of Intent	Acidize		duction (Start/Resume) Water Shut-Off					
Subsequent Report	Alter Casing Casing Repair	Fracture Treat New Construction		amation mplete		Well Integrity Other Strawn Completion		
	Plug and Abandor							
Final Abandonment Notice Convert to Injection Plug Back Water Disposal								
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Strawn Completion Cont.: 5-15-08 Broke circ. w/ 2bbls 2% KCL @ 1.2 bpm, increase rate to 2 bpm. Spot 2 bbls 15% HCL acid @ 46.5 bbls acid on spot. Release 5 1/2 HD pkr. PUH LD 3 jts. tbg, reest pkr. w/ 25 pts. (btm 8033.08°). Hook up monitor to csg., pump 5 bbls 2% KCL wtr. Broke circ. @ 1.5 bbls, press. up csg. to 523#, test lines to 7353 psi. Formation broke @ 3922 psi, start acid & drop 50 balls 7/8 1.3 perf pack balls, start flush, balled out w/ 45 bbls on formation. Press. hit 6498 psi, surge lines. ISIP-2562, 5 mln 2364#, 19 min 2308#, 15 min 2273#, avg. rate- 4.7 bpm, avg. press 3209 psi, max. press 6498 psi. Pumped total 47.6 bbls 15% HCL acid total 109 bbls. Bled off 2200# for 30 min. Made 10 swab runs. SWI 5-16-08 Made 8 swab runs, install gauge, SWI 5-17-08 Tbg. psi 100#, csg. psi 0#. Made 6 swab runs. SWI, SDFWE 5-19-08 Tbg. psi 100#, csg. psi 0#. Made 3 swab runs. SWI, SDFWE 5-19-08 Tbg. psi 100#, csg. psi 0#. Made 3 swab runs. Load hole w/ 47 bbls 2% KCL @ 2 bpm, 0 press. Unset pkr., GH w. 2000' of 2 7/8 tbgkill string, open ended. Load hole w/ 15 bbls 2% KCL. SWI SDFN 5-21-08 POH w/ 2000' of tbg. GH, set CIBP @ 8045'. Dump 30' of cmt. on CIBP, top of cmt 8015' Load hole w/ 9 bbls 2% KCL. Test plug to 1000# for 15. min. GIH w/ 3 1/8 HSC gun 19 grm .40 hole size, Perforate from 7451' to 7478' 54 holes made. GIH w/ 5 1/2 HD pkr., bottom of pkr 7478.50'								
14. I hereby certify that the fore Name (Printed/Typed)								
Angela Lightner	angela@rkford.com	Title	Consultant	432-682-0440	office			
Signature ()	05/22/2008							
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved by		Title		D	ate			
Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant to	Office			-				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.