<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u>

1301 W Grand Avenue, Artesia, NM 88210
 District III
 1000 Rio Brazos Road, Aztec, NM 87410
 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505



State of New Mexico
Energy Minerals and Natural Resources
Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505



Form C-144 June 16, 2008

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

SEP 1 0 2008

NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: Permit of a pit closed-loop system below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinance:

Liner type: Thicknessmil LLDPE HDPE PVC Other	environment. Nor does approval relieve the operator of its responsibility to comp	ply with any other applicable governmental authority's rules, regulations or ordinances.
SKELLY UNIT # 992 API Number: 30-015-36598 OCD Permit Number: U/L or Qtr/Qtr UL E		OGRID #: 229137
API Number: 30-015- 36-598 U/L or Qtr/Qtr ULE Section 14 Township 17S Range 31E County: EDDY Center of Proposed Design: Latitude N/A Longitude N/A NAD: 1927 1983 Surface Owner: Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC Drying Pad Tanks Haul-off Bins Other		TX 79701
U/L or Qtr/Qtr ULE Section 14 Township 17S Range 31E County: EDDY Center of Proposed Design: Latitude N/A		
Center of Proposed Design: Latitude N/A	API Number: 30-015- 36-598	OCD Permit Number:
Surface Owner: Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC	U/L or Qtr/Qtr ULE Section 14 Township 1	7S Range 31E County: EDDY
Pit: Subsection F or G of 19.15.17.11 NMAC Temporary:	Center of Proposed Design: Latitude N/A	LongitudeN/A NAD:1927 1983
Drying Pad	Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian A	Allotment
Permanent Emergency Cavitation Lined Unlined Liner type: Thickness mil LLDPE HDPE HDPE	Pit: Subsection F or G of 19.15.17.11 NMAC	☐ Closed-loop System: Subsection H of 19.15.17.11 NMAC
Liner type: Thicknessmil LLDPE HDPE FUC Other String-Reinforced Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Dimensions: Length x Width Volume: bbl Dimensions: L x W x D Dimensions: Length x Width Volume: bbl Dimensions: Logorithms of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between or four feet Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls and liner Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC Dimensions: Length x Width Volume: bbl yd3 Dimensions: Length x Width Dimensions	Temporary: Drilling Workover	☐ Drying Pad ☐ Tanks ☒ Haul-off Bins ☐ Other
Liner type: Thicknessmil LLDPE HDPE PVC Other	☐ Permanent ☐ Emergency ☐ Cavitation	☐ Lined ☐ Unlined
Other	Lined Unlined	Liner type: Thicknessmil
Seams: Welded Factory Other Volume: bbl yd³ Volume: bbl Dimensions: L x W x D Dimensions: Length x Width Below-grade tank: Subsection I of 19.15.17.11 NMAC Chain link, six feet in height, two strands of barbed wire at top Type of fluid: Four foot height, four strands of barbed wire evenly spaced between or four feet Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 NMAC Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting Other Visible sidewalls and liner Monthly inspections Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Other 12'x24', 2' lettering, providing Operator's name, site location, and emergency telephone numbers Other Signed in compliance with 19.15.3.103 NMAC Alternative Method: Administrative Approvals and Exceptions:	Liner type: Thicknessmil	Other
Volume:bbl Dimensions: L _ x W _ x D Dimensions: Length _ x Width	Other String-Reinforced	Seams: Welded Factory Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Seams: Welded Factory Other	Volume:bblyd ³
Volume:bbl	Volume:bbl Dimensions: L x W x D	Dimensions: Lengthx Width
Type of fluid:	Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC
Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC 12'x24', 2' lettering, providing Operator's name, site location, and emergency telephone numbers Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC 12'x24', 2' lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.3.103 NMAC Administrative Approvals and Exceptions:	Volume:bbl	☐ Chain link, six feet in height, two strands of barbed wire at top
Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 NMAC Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen	Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between one and
□ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off □ Screen □ Netting □ Other □ Visible sidewalls and liner □ Monthly inspections □ Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC □ Other □ □ 12'x24', 2' lettering, providing Operator's name, site location, and emergency telephone numbers □ Other □ Other □ Other □ Signed in compliance with 19.15.3.103 NMAC □ Alternative Method: Administrative Approvals and Exceptions:	Tank Construction material:	four feet `
□ Visible sidewalls and liner □ Monthly inspections □ Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC □ Other □ 12'x24', 2' lettering, providing Operator's name, site location, and Liner type: Thickness mil □ HDPE □ PVC □ Other □ Signed in compliance with 19.15.3.103 NMAC □ Alternative Method: Administrative Approvals and Exceptions:	Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11 NMAC
□ Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC □ Other	☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
☐ Other ☐ 12'x24', 2' lettering, providing Operator's name, site location, and Liner type: Thickness mil ☐ HDPE ☐ PVC ☐ Other ☐ Signed in compliance with 19.15.3.103 NMAC ☐ Alternative Method: Administrative Approvals and Exceptions:	☐ Visible sidewalls and liner	Monthly inspections
Liner type: Thicknessmil	☐ Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
☐ Other ☐ Signed in compliance with 19.15.3.103 NMAC ☐ Alternative Method: Administrative Approvals and Exceptions:		12'x24', 2' lettering, providing Operator's name, site location, and
Alternative Method: Administrative Approvals and Exceptions:	Liner type: Thicknessmil	emergency telephone numbers
	Other	Signed in compliance with 19.15.3.103 NMAC
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration 19.15.17 NMAC for guidance.	Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please refer to
of approval. Please check a box if one or more of the following is requested, if not leablank: Administrative approval(s): Requests must be submitted to the		Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe

	T
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.	
Ground water 1s less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes No
Within a 100-year floodplain FEMA map	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.19 NMAC	cuments are
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	19.15.17.9
Previously Approved Design (attach copy of design) API Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan	
Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank Closed-loop System	☐ Alternative
Proposed Closure Method: Waste Excavation and Removal On-site Closure Method (only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for control of the San	onsideration)
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	Ţ
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attactors are plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please inde or facilities for the disposal of liquids, drilling fluids and drill cuttings. Disposal Facility Name: CRI OR G M INC. Disposal Facility Permit Number: CRI (R9166) G M INC (711-019-001)	entify the facility
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.	
Name (Print): PHYLLIS A. EDWARDS Title: REGULATORY ANALYST	
Signature: Leglie Classic 7-1-08	
e-mail address: pedwards@conchoresources.com Telephone: 432-685-4340	
OCD Approval: Permit Application (including closure plan (only) OCD Representative Signature: Title: OCD Permit Number:	08
OCD Representative Signature: Approval Date: 8-1-0	08
OCD Representative Signature: Title: Closure Report (required within 60 days of closure completion): Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	
OCD Representative Signature: Title: OCD Permit Number: OCD Per	te, by a check
OCD Representative Signature: Title: Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method If different from approved plan, please explain. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	te, by a check
OCD Representative Signature: Title: OCD Permit Number: OCD Per	1983
OCD Representative Signature: Title: Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method If different from approved plan, please explain. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Contine: Latitude Longitude NAD: 1927 Instructions: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my know	1983
OCD Representative Signature: Title: Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method If different from approved plan, please explain. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Revegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my know belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.	1983

Page va

Closed Loop Operation & Maintenance Procedure

All drilling fluid circulated over shaker(s) with cuttings discharged into roll off container.

Fluid and fines below shaker(s) are circulated with transfer pump through centrifuge(s) or solids separator with cuttings and fines discharged into roll off container.

Fluid is continuously re-circulated through equipment with polymer added to aid separation of cutting fines.

Roll off containers are lined and de-watered with fluids re-circulated into system.

Additional tank is used to capture unused drilling fluid or cement returns from casing jobs.

This equipment will be maintained 24 hrs./day by solids control personnel and or rig crews that stay on location.

