Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 88240 State of New Mexico Energy, Minerals and Natural Resources			Form C-103 May 27, 2004 WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-005-63061 5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		STATE FEE
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87		≨6. State Oil & Gas Lease No. ₹ V-2982
SUNDRY NOTICES (DO NOT USE THIS FORM FOR PROPOSALS TO DIFFERENT RESERVOIR. USE "APPLICATION 1. Type of Well: Oil Well Gas W	7. Lease Name or Unit Agreement Name Quincy AMQ State		
			8. Well Number #11
Name of Operator Hanson Operating Company, Inc.	SEP 26	2008	9. OGRID Number 009974
3. Address of Operator P. O. Box 1515, Roswell, NM 88202-	1515 OCD-A	RIESIA	10. Pool name or Wildcat Acme San Andres Southeast
4. Well Location			
Unit Letter K: 1650 feet from the South line and 1650 feet from the West line			
Section 12	Township 8 South Ran	<u> </u>	NMPM Chaves County
	Elevation (Show whether DR, 1934' GR	RKB, RT, GR, etc.)	
	00' Distance from nearest fresh water	well >2 miles Distance f	rom nearest surface water >10 miles
Pit Liner Thickness: 12 mil Below-Grade Tank: Volumebbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON ☒ REMEDIAL WORK □ ALTERING CASING □ REMEDIAL WORK □ ALTERING CASING □			
TEMPORARILY ABANDON			_
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
Purpose to plug and abandon well as follows: Notify OCD 24 hrs. price to any work done.			
 Set CIBP at 2050' with 35' cement cap. Circulate hole with 10# brine with 12.5# per barrel salt water gel. 			
 3. Perforate 4 squeeze holes at 460'. 4. Pump 100 sacks cement for solid plug from 460' to surface. /* to out of cs6. 5. Clean and remediate location. 			
6. Set Dry Hole Marker.			
* Approval for P	1 only		Approval Granted providing work is complete by 12/30/08
Work over Pit Region Submission of C-144			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.			
SIGNATURE Carol J. Smith TITLE Production Analyst Type or print name Carol J. Smith E-mail address: hanson@dfn.com			DATE <u>09/22/2008</u> Telephone No. 505-622-7330
For State Use Only			
APPROVED BY: Marken TITLE fail Rep DATE 9/30/08. Conditions of Approval (if any):			

WELL NAME Quincy AMQ State #11 FIELD Acme San Andres SE **LOCATION** 1650' FSL & 1650' FWL, Section 12-8S-27E, Chaves County, NM GL 3934' **ZERO KB** COMPLETION DATE SPUD DATE 4/30/1995 5/13/1995 API #30-005-63061 **COMMENTS: CASING PROGRAM** 17 1/2" Hole 13 3/8" at 5' Circulated 13 3/8" 8 5/8" 460 24# 12 1/4" Hole 5 1/2" 15.5# 2221 8 5/8" at 460' with 250 sacks cement circulated **BEFORE** 7 7/8" Hole San Andres Perfs: 2144'-2198' 55 holes 5 1/2" at 2221' with 350 sacks cement PBTD at 2211' Not to Scale TD 2221' 9/22/2008

WELLBORE DIAGRAM

