Submit 3 Copies To Appropriate District	State of New Mexico				Form C-103
Office District I	Energy, Minerals and Natural Resources			WELL ADING	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 District II				WELL API NO. 30-015-32930	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION			5. Indicate Type	of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.				T FEE
District IV	Santa Fe, NM 87505		6. State Oil & 0	Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505			,		
SUNDRY NOTICES AND REPORTS ON WELLS				7. Lease Name	or Unit Agreement
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG-BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104) FOR 30 C 20 C				Name:	·
FROFOSALS.)	ATION FOR PERMIT (FORM C-101) 10 43 66 12 9 30 37			Freedom 36 State	Com
1. Type of Well:	/ 17)			Treedom 50 State	, Com
Oil Well Gas Well  2. Name of Operator	Other	<del>√3 1</del>	7 2003 Tu	8. Well No.	
Mewbourne Oil Company	14744	2	COCIVED 4	#1	
3. Address of Operator		00 00	D - ARTESIA	9. Pool name o	r Wildcat
PO Box 5270 Hobbs, NM 88241		100	· · · · · · · · · · · · · · · · · · ·	Burton Flats Mot	Tow
4. Well Location					
Unit Letter I: 1650 feet from the South   Sout					
Om Letter	1050 <u></u> 1000 Holli ti				The
Section 36	Township		Range 28E	NMPM	Eddy County
10. Elevation (Show whether DR, RKB, RT, GR, etc.)					
3223'  11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF IN		marcate N		SEQUENT RE	
PERFORM REMEDIAL WORK	PLUG AND ABAND	ом П	REMEDIAL WOR		ALTERING CASING
	CHANGE PLANS		COMMENCE DRI	_	PLUG AND
_				_	ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AN CEMENT JOB	1D <b>2</b>	
OTHER:			OTHER:		
12. Describe proposed or complete	d operations. (Clearly	state all perti	inent details, and give	ve pertinent dates,	including estimated date of
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or					
recompilation.					
10/08/03MI & spud 26" hole. TD'd 20" hole @ 311'. Ran 311' - 20" X56 BT&C csg. Cemented with 438 sks BJ Lite "C" with					
additives. Mixed @ 12.5 #/g with 1.98 cf/sk yd. Tailed with 200 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 100 sks cmt to reserve pits. WOC 18 hrs. Drilled out with 17 ½" bit.					
1.54 cl/sk yd. Clic 100 sks chii to feserve pits. WOC 18 hrs. Drined out with 17 ½ bit.					
10/14/03TD'd 12 1/4" hole @ 1303'. Ran 1303' - 13 3/8" J55 ST&C csg. Cemented with 800 sks 35:65 Poz "C" with additives. Mixed					
@ 12.5 #/g with 2.04 cf/sk yd. Tailed with 200 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 109 sks cmt to reserve pits. WOC 17 hrs. Test BOPE to 1000#, OK. Drilled out with 12 ¼" bit.					
109 sks cmt to reserve pr	s. WOC 1/ hrs. Test	BOLF to 100	00#, OK. Drilled or	it with 12 ¼" bit.	
10/21/03 TD'd 12 1/4" hole @ 299	7'. Ran 2997' – 9 %" J	55 & N80 LT	&C csg. Cemented	with 500 gals GW	/ 27 & 180 sks Class "H"
with additives. Mixed @ 14.6 #/g with 1.52 cf/sk yd. Followed with 700 sks 35:65:6 Class "C" with additives. Mixed @					
12.5 #/g with 1.96 cf/sk yd. Tailed with 200 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 196 sks cmt to reserve pits. WOC 18 hrs. Test BOPE to 2000#, OK. Drilled out with 8 3/4" bit.					
196 sks cmt to reserve pr	s. WOC 18 hrs. Test	BOPE to 200	00#, OK. Drilled ou	it with $8\frac{3}{4}$ " bit.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
CICHATURE A MALA		mm r	7.11 Division	70	A TETE: 10/04/00
SIGNATURE J.WV		IIILEI	Hobbs District Mana	agerD	ATE10/24/03
Type or print name NM Young Telephone No. 505-393-5905					
(This space for state/use)					
APPPROVED BY	J. Gum	TITI D	itrict Sign	wisov	DATE OCT 2.9 2003
Conditions of approval, if any:		111FE			_DATE