Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources	May 27, 2004 WELL API NO.
1301 Grand 11.0., 11.0314, 11.11 00210	OIL CONSERVATION DIVISION	30-015-36501 5. Indicate Type of Lease
<u>District III</u> 1000 Rìo Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. Santa Fe, NM 87505	STATE FEE X
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Salita Fe, IVIVI 87303	6. State Oil & Gas Lease No.
87505  SUNDRY NOTICES AND REPORTS ON WELLS  7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROPOSALS TO DIFFERENT RESERVOIR. USE "APPLICATION PROPOSALS.)	O DRILL OR TO DEEPEN OR PLUG BACK TO A TO FOR PERMIT" (FORM C-101) FOR SUCH	Quick Draw 15 B  8. Well Number
1. Type of Well: Oil Well X Gas We		1
2. Name of Operator Mewbourne Oil Company	OCT 03 2008	9. OGRID Number 14744
3. Address of Operator PO Box 5270 Hobbs, NM 88240	OCD-ARTESIA	10. Pool name or Wildcat Cemetery Yeso
4. Well Location		
	teet from theN line and1650	
Section 15	Township 20S Range 25E Elevation (Show whether DR, RKB, RT, GR, etc.	NMPM Eddy County
3406' GL  Pit or Below-grade Tank Application □ or Closure □		
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLU	G AND ABANDON 🗌 REMEDIAL WOR	K ALTERING CASING
TEMPORARILY ABANDON   CHA	NGE PLANS   COMMENCE DR	ILLING OPNS.□ P AND A □
PULL OR ALTER CASING   MUL	TIPLE COMPL   CASING/CEMEN	T JOB X
OTHER: OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
09/16/08MI & spud 11" hole. Ran 831' 8 5/8" 32# J55 LT&C csg. Cemented with 180 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail with 400 sks Class C with 2% CaCl2. Mixed @ 14.6 #/g w/ 1.39 yd. Plug down @ 3:30 pm 09/19/08. Circ 95 sks cement to pit. WOC 18 hrs. At 4:30 pm on 09/20/08, tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.		
09/24/08 TD'ed 7 7/8" hole @ 3350'. Ran 3350' 4 ½" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (35:65:6) with additives. Mixed @ 12.5 /g w/2.04 yd. Tail with 325 sks Class H with additives. Mixed @ 15.1 /g w/1.29 yd. Plug down @ 4:00 pm 09/25/08. Circ 20 sks cement to pit. At 4:00 pm on 09/25/08, tested csg to 1400# for 30 mins, held OK. Set casing slips w/32k.		
09/25/08Released rig at 11:00 pm.	ACCEPTED FOR RECORD	
		OCT 6 2008
I hereby certify that the information above is true and complete to the best of my knowledgerand beight the certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit Magantaturched alternative of the property of the construction of the		
SIGNATURE Jackie La	TITLE_Hobbs Regulatory_	
Type or print name Jackie Lathan  For State Use Only	E-mail address:jlathan@mewbourne.	.com Telephone No. 575-393-5905
APPROVED BY:  Conditions of Approval (if any):	TITLE	DATE