

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-33045

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
VB-0516

7. Lease Name or Unit Agreement  
Name:

Black River 35 State Com

8. Well No.  
#2

9. Pool name or Wildcat  
Morrow

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
Mewbourne Oil Company 14744

3. Address of Operator  
PO Box 5270 Hobbs, NM 88241

4. Well Location

Unit Letter A : 660 feet from the North line and 660 feet from the East line

Section 35 Township 23S Range 26E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3232'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

10/24/03...MI & spud 17 1/2" hole. TD 17 1/2" hole @ 528'. Ran 528' 13 3/8 48# H40 ST&C csg. Cemented w/300 sks BJ Lite C with additives. Mixed @ 12.5 #/g with 1.98 cf/sk yd. Tailed with 200 sks Class 'C' with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 75 sks cmt to pits. WOC 18 hrs. Drilled out with 12 1/4" bit.

11/05/03...TD'd 12 1/4" hole. TD 12 1/4" hole @ 3955'. Ran 3955' 9 5/8 40# N80/K55 LT&C csg. Cemented w/1200 sks BJ Lite C with additives. Mixed @ 12.5 #/g with 1.96 cf/sk yd. Tailed with 200 sks Class 'C' with 2% CaCl2. Mixed @ 14.8 #/g with 1.34 cf/sk yd. Circ 75 sks cmt to pits. WOC 18 hrs. Drilled out with 8 3/4" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE NM Young TITLE Hobbs District Manager DATE 11/05/03

Type or print name NM Young Telephone No. 505-393-5905

(This space for State use)

APPROVED BY Jim W. Young TITLE District Supervisor DATE NOV 13 2003

Conditions of approval, if any: