

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
**30-015-01667**

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:  
**Empire Abo Unit 'H'**

8. Well Number  
**27**

9. OGRID Number  
**00778**

10. Pool name or Wildcat  
**Empire Abo**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
**BP America Production Company**

3. Address of Operator  
**P.O. Box 1089 Eunice NM 88231**

4. Well Location  
Unit Letter **O** : **650** feet from the **S** line and **1951** feet from the **E** line  
Section **32** Township **17S** Range **28E** NMPM County **EDDY**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**3662' GL**

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/8/08: RU. BREAK FLOWLINE AND TEST CSG. CSG TOOK 18 BBL TO LOAD AND HELD 500 PSI FOR 30 MIN. CHECK SURFACE CSG PSI, JUST HAD SMALL BLOW. KILL TBG WITH 45 BBL AND NU BOP, LOCKSET WAS IN COMPRESSION W/ 21 PT, INSTALL BIW HEAD TALLY OUT WITH 70 STANDS TBG.

10/9/08: POH WITH KILL STRING AND LAY DOWN PACKER, RIH WITH 4.5 CIBP AND 183 JTS 2 3/8" J-55 TO A DEPTH OF 5670'. SET CIBP, POH TO 5665' CIRC HOLE WITH FRESH WATER. SPOT 25 SX CLASS C CEMENT, LD 12 JTS, POH WITH SETTING TOOL. RIH OPEN ENDED TO 5294' WITH 171 JTS 2 3/8" TBG, CIRC HOLE WITH 80 BBL 9.5 SALT GEL MUD. LD 53 JT TBG TO 3650' 118 JTS IN HOLE.

Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 10/31/08

Type or print name Barry C. Price

E-mail address: barry.price@bp.com Telephone No. 575-394-1648

For State Use Only

Accepted for record

APPROVED BY NMOCD

Conditions of Approval, if any:

TITLE \_\_\_\_\_ DATE 11/5/08

Approved for plugging of well bore only  
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Form C-103. www.oecd.state.nm.us Date 11/5/08

Form C-103  
Empire Abo Unit H-27  
30-015-01667  
Continued from Page 1

10/10/08: WOC. PUMP 25 SX CEMENT PLUG WITH 12.5 BBL DISPLACE. LD 13 JTS. POH WITH 1 ROW TBG.

10/13/08: RIH TAG @3258'. LD 65 JT TOTAL ON RACK OF 142 OUT 41 IN. TO 1250' SPOT 25 SX CEMENT. LD 14 JT AND POH WITH 8 STANDS. WOC. RIH AND TAG @ 850', POH LD ALL BUT 16 JTS TBG. STOOD 8 STANDS BACK. RIG UP KEY WIRELINE RIH AND SHOOT 4 HOLES @ 60'. RIG WIRELINE DOWN. RIH WITH 17 JTS.

10/14/08: MOVE IN EQUIPMENT AND CIRC 4.5" AND SURFACE. CIRC CEMENT FROM 525' TO SURFACE UP 4.5 CSG. SHUT CSG VALVE AND CIRC CEMENT UP BETWEEN 4.5 AND SURFACE CSG. SHUT SURFACE HOOK UP TO SURFACE VALVE AND KEEP SURFACE LOADED WHILE LAYING DOWN 17 JTS TBG. ND BOP.

10/30/08: DIG OUT AND CUT OFF WELLHEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, DIG OUT AND CUT OFF ALL ANCHORS, BACK FILL AND LEVEL LOCATION.