

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brázos Rd., Aztec, NM 87410
District IV
1220 S. St Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-36688
5. Indicate Type of Lease STATE FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Long Draw 10 N
8. Well Number 1
9. OGRID Number 14744
10. Pool name or Wildcat Cemetery Yeso

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well Other	
2. Name of Operator Mewbourne Oil Company	DEC - 2 2008
3. Address of Operator PO Box 5270 Hobbs, NM 88241	OCD-ARTESIA
4. Well Location Unit Letter <u>N</u> : <u>330</u> feet from the <u>S</u> line and <u>2310</u> feet from the <u>W</u> line Section <u>10</u> Township <u>20S</u> Range <u>25E</u> NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3427' GL	
Pit or Below-grade Tank Application ☐ or Closure ☐	
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____	
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/13/08...MI & spud 11" hole. Ran 810' 8 5/8" 32# J55 LT&C csg. Cemented with 400 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 7:30 pm 11/14/08. Circ 87 sks cement to pit. WOC 18 hrs. At 8:30 pm 11/15/08 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

11/18/08 TD'ed 7 7/8" hole @ 3255'. Ran 3255' 4 1/2" 11.6# J55 LT&C csg. Cemented w/400 sks BJ Lite Class C (35:65:6) with additives. Mixed @ 12.5 /g w/2.04 yd. Tail with 400 sks Class H with additives. Mixed @ 15.1 /g w/1.29 yd. Plug down @ 2:15 am 11/19/08. Circ 68 sks cement to pit. Bumped plug w/1364#. At 2:15 am on 11/19/08, tested csg to 1364# for 30 mins, held OK. Set wellhead slips w/35k.

ACCEPTED FOR RECORD

11/19/08...Released rig at 4:00 pm.

DEC 4 - 2008

Gerry Guye, Deputy Field Inspector

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 12/01/08

Type or print name Jackie Lathan

E-mail address: jlathan@mewbourne.com

Telephone No. 575-393-5905

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):