Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED OMB No 1004-0137 Expires July 31, 2010



SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

.IAN 05 2009 5. Lease Serial No NM-10266

SUBMIT IN TRIPLICATE - Ot	7 If Unit or CA/Agreement, Name and/or No.			
1 Type of Well				
Oil Well X Gas Well Other			8 Well Name and No	
2 Name of Operator			Link BKT Federal Com #2H	
Yates Petroleum Corporation			9. API Well No	
3a Address 3b Phone No. (include area code)			30-015-36374	
105 S. 4th Str., Artesia, NM 88210	71	10 Field and Pool or Exploratory Area		
4 Location of Well (Footage, Sec., T ,R.,M., OR Survey Description)			Cottonwood Creek; Wolfcamp	
Surface - 760'FSL & 240'FEL of Section 18-T16S-R25E (Unit P, SESE)			11. County or Parish, State	
BHL - 730'FSL & 695'FEL of Section 17-T16S-R25E (Unit P, SESE)			Eddy County, New Mexico	
12. CHECK APPROPRIATE BOX(E	PORT, OR OTHE	R DATA		
TYPE OF SUBMISSION . TYPE OF ACTION				
Acidize	Deepen	Production (St	art (Resume)	Water Shut-Off
			arty resume)	- 1
Notice of Intent Alter Casir	Fracture Treat	Reclamation	<u></u>	Well Integrity
X Casing Rep	New Construction	Recomplete	X	Other Production
Subsequent Report Change Pl.	ans Plug and Abandor	Temporanly A	bandon	Casing
Final Abandonment Notice Convert to	Injection Plug Back	Water Disposa	ıì	
13 Describe Proposed of Completed Operation Clearly state all pertinen	t details, including estimated starting date	of any proposed work and appr	roximate duration thereof	lf .
11/6/08 Set a cement plug with 200 sx Cla. 11/7/08 Set a cement plug with 150 sx Cla. 11/8/08 TIH to dress off cement. Tagged of 11/10/08 New strap shows cement from 1st from 1649'-900'. Tagged cement at 11/26/08 TD 7-7/8" hole 9000'. 11/27/08 Set 5-1/2" 15.5#, 17# P-110 LT&C 5.89#/sx D044 + D112 + 0.125#/sx 625 sx PVL + 0.15#/sx D046 + 0.4 S001 (yld 1.85, wt 13). Cement circles	ss "H" with additives from cement at 978' and started plug top at 1650'. Set a cat 815'. Continued to drill casing at 9000'. Cement D130 + 39.5#/sx D132 + 5#/sx D065 + 1.5#/sx D11	1300'-900'. I dressing off. Dreement plug with 35 directionally. KOPed with 580 sx 50/5 2#/sx D42 (yld 2.4	50 sx Class "H" v at 1167'. 50 Poz + 8.65#/s 6, wt 11.9). Tail	with additives ex D020 + ed in with
14 I hereby certify that the foregoing is true and correct			<u> </u>	
Name (<i>Printed/Typed</i>)		Goont Com. D.	marker Tital I I I	
Tina Huerta	Title Re	egulatory Compliar	outy Field Inspects ice Supervisor	*
Signature ()	Date De	ecember 17, 2008	ACCEPTED	FOR RECORD
	PACE FOR FEDERAL OR STA			
Approved by	itle	DIEC	2. 1 2000	
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon				mes
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, i	make it a crime for any person knowir	gly and willfully to make to	any department or age	ncy of the United States
any false, fictitious or fraudulent statements or representations a			/ CARLSBĂI	O FIELD OFFICE