1 :

OPERATOR'S COPY

Form 3160-5 (April 2004)	5. Lease S	FORM APPROVED OM B No. 1004-0137 Experies: March 31, 2007 5. Lease Serial No.			
Do not use a abandoned a	6. If Indian, Allottee or Tribe Name				
SUBMIT IN TH	7. If Unit or CA/Agreement, Name and/or No.				
1. Type of Well ☐ ☐ ☐	Gas Well DD Other			8. Well N	ame and No.
2. Name of Operator COG Opera	ding LLC			9. API V	/ell No.
3a Address 550 W. Texas Ave., Suite 1300	10. Field a	nd Puvil, or Exploratory Area			
4. Location of Well (Footage, Sec.	Loco Hills ; Glorieta Yeso 96718				
	11. County or Parish, State				
ANY Park AND LAST TO	EDDY, NM				
···	PPROPRIATE BOX(ES) TO	O INDICATE NATUR	RE OF NOTICE, R	EPORT, O	R OTHER DATA
TYPE OF SUBMISSION		TY	PE OF ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Star	rt/Resume)	Water Shut-Off Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete		Other Change APD
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abs	andon	Drill Plan
	Convert to Injection	Plug Back	Water Disposal		ork and approximate duration thereof.
Attach the Bond under which the following completion of the investing has been completed. Fit determined that the site is ready	ne work will be performed or provolved operations. If the operation at Abandonroem Notices shall be for final inspection.) a variance for drill plan from	ride the Bood No. on file w n results in a multiple compi e filed only after all requires	vith RLM/BLA. Required lection or recomplection in mouts, including rectame	d subsequent i a new interve tion, have bee	ns of all pertinent markers and zones. eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has
#6: minimum specification Also attached is well name	s for pressure costrol. list that this variance applies	to.		,	
Weelley	spelled	Incor	moty,	o www.grama.co.y.y.y.	and the second s
general de la companya del companya del companya de la companya de		N 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	**************************************	NOT 16 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
14. Thereby certify that the foreg Name (Printed/Typed)	oing is true and correct				
Phyllis A. Edward		Title Reg	gulatory Analyst		
Signature Theyll	in a Ser	a los		26/2008	APPROVED
<u> </u>	THIS SPACE FOR F	EDERAL OR ST	ATE OFFICE U	8E	
Approved by		Tid			APR 1 2008
Conditions of approval, if any, are at	ached. Approval of this notice d	oes not warrant or		 	markedown
errify that the applicant holds legal o which would entitle the applicant to c	onduct operations thereon.	0411		L	WESLEY W. INGRAM
itle IB U.S.C. Section 1001 and Title 4	U.S.C. Section 1212, make it a	crime for any person know	ringly and willfully to r	navem any	in pursuant or agraphy of the Omited

Sundry Notes to Change APD's

Loco Hills Area, T17S, R30E

3/26/08

4. Casing Program

Hole Size	Interval	OD Casing	Weight	Grade	Jt., Condition	Jt.	brst/clps/ten
17 1/2"	0-425'	13 3/8"	48#	H-40	ST&C/New	ST&C	9.22/3.943/15.8
11"or12 1/4"	0-1300'	8 5/8"	24or32#	J-55	ST&C/New	ST&C	3.03/2.029/7.82
7 7/8"	0-TD	5 1/2"	15.5or17#	J-55grL80	LT&C/New	LT&C	1.88/1.731/2.42

5. Cement Program

13 3/8" Surface Casing:

Class C, 475 sx, yield 1.32, back to surface

8 5/8" Intermediate Casing:

11" Hole: Class C, 400 sx lead, yield-2.45 + 200 sx

tail, yield-1:32, back to surface.

12-1/4" Hole: Class C, 600 sx lead, yield-2.45 + 200

sx tail, yield-1.32, back to surface.

5 1/2" Production Casing:

Class C, 700 sx Lead, yield-1.97 + 400 sx Tail, yield-1.37, to 200' minimum tie back to intermediate

casing

6. Minimum Specifications for Pressure Control

The blowout preventer equipment (BOP) shown in Exhibit #9 will consist of a double ram-type (2000 psi WP) preventer. This unit will be hydraulically operated and the ram type preventer will be equipped with blind rams on top of 4 1/2" drill pipe rams on the bottom. The BOP will be nippled up on the 13 3/8" surface casing and tested to 1000 psi by rig pump. The BOP will then be nippled up on the 8 5/8" intermediate casing and tested by a third party to 2000 psi and used continuously until total depth is reached. All BOP's and accessory equipment will be tested to 2000 psi before drilling out of the intermediate casing. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment (Exhibit #10) will include a Kelly cock and floor safety valve, choke lines and a choke manifold (Exhibit #11) will a 2000 psi WP rating.

DISTRICT I 1826 N. French Dr., Hobbs, NM 88240 DISTRICT II 1301 W. Grand Avenue, Artesia, NM 88210

1000 Rio Brazos Rd., Aztec. NM 87410

1220 St. Francis Dr., Santa Fe, NM 87505

DISTRICT III

DISTRICT IV

Dedicated Acres

320

Joint or Infill

Ν

Consolidation Code

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised October 12, 2005

Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

OIL CONSERVATION DIVISION 1220 South St. Francis Dr.

1220 South St. Francis Dr. Santa Fe, New Mexico 87505

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number			Pool Code			Pool Name					
			73920			rlsbad East (N					
Property	Cpde		Property Name						Well Number		
1970	776 BIG ED					DDY UNIT			214		
OGRID N	o.				Operator Nam	Name Elevation			lion		
001801			BEPCO, L.P.					3127'			
					Surface Loca	ation					
UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County		
Ε	6	22 S	28 E		1330	NORTH	860	WEST	EDDY		
			Bottom	Hole Loc	cation If Diffe	rent From Sur	face				
UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County		
ı			l			'					

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

Order No.

