

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

MAR 16 2009

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-36934
5. Indicate Type of Lease STATE FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Quick Draw 10 A
8. Well Number 1
9. OGRID Number 14744
10. Pool name or Wildcat North Seven Rivers Glorieta Yeso

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3394' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB X

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/04/09...MI & spud 11" hole. Ran 815' 8 5/8" 24# K55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.51 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Plug down @ 6:30 pm 03/05/09. Circ 97 sks cmt to pit. At 10:00 pm 03/06/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

03/10/09 TD'ed 7 7/8" hole @ 3160'. Ran 3160' 4 1/2" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class H with additives. Mixed @ 15.1 /g w/1.29 yd. Plug down @ 2:30 am 03/11/09. Circ 81 sks cement to pit. At 2:30 am on 03/11/09, tested csg to 1330# for 30 mins, held OK. Set wellhead slips w/35k.

03/11/09...Released rig at 2:00 pm.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/13/09

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com Telephone No. 575-393-5905  
For State Use Only

APPROVED BY: Jackie Weaver TITLE Geologist DATE 3/16/09  
Conditions of Approval (if any):