RELEASE PKR. LD 1- JT. OF 2-3/8", J-55 TBG. AND 1- PUP JT. PULL AND STANDBACK 10 STDS OF TBG. 3/19/09: POH W/ 208 JTS. OF 2-3/8", J-55 TBG. AND LD 5.5" BAKER LOK-SET PKR. STRAP TBG. GOING IN HOLE. PU A 5.5" CIBP AND RIH ON TBG. SET 5.5" CIBP @ 6,060'. TEST CIBP AND CSG TO 500 PSI, GOOD TEST. CIR 145 BBLS. OF 9.3 PPG, 40 FV SW MUD. SPOTTED 25 SXS OF CMT, EST. 6,060- 5,813'. DISPLACED W/ 22 BBLS. OF BRINE. POH AND LD 85 JTS. OF WS TO 3,618'. PUMP 25 SX BALANCED CMT PLUG FOR GLORIETA PLUG. EST. 3,614'- 3,372'. POOH. WOC. Continued on page 2.

Type or print name Barry C. Price

APPROVED BY TITLE

Conditions of Approval, if any:

Approved for plugging of well hore only.
Liability under bond is retained pending receipt
of C 103 (Subsequent Report of Well, Pluggips ATE
which may be found at OCD Web Page under
Forms, www.cmnrd.state.nm.us/ocd.

4/3/07

Telephone No. 575-394-1648

Form C-103 Empire Abo Unit J-233 30-015-22490 Continued from Page 1

3/20/09: CHECK WELLHEAD PRESSURE- ZERO. POOH AND AND LD CIBP SETTING STINGER. MU SLOTTED SUB AND RIH ON WS. TAG TOC @ 3,325' (GLORIETA PLUG). LD WS TO 1,250'. PUMP A 25 SX BALANCED CMT PLUG. POOH AND LD 19- JTS. OF TBG. STANDBACK 12 STDS. OF TBG. ND BOPE. RIH W/ WS TO 690'. PUMP AN 85 SX SUFACE CMT. PLUG. POOH AND LD WS. TOP OFF 5.5" CSG W/ CMT.

4/1/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, BACKFILL AND LEVEL LOCATION.