wice.

District I

OTHER:

1625 N. French Dr , Hobbs, NM 88240

State of New Mexico Energy, Minerals and Natural Resources

APR	-8	2009
-----	----	------

WELL API NO.

	W
Form C-103	17.
May 27, 2004	_

1301 W Grand Ave. Artesia NM 88210 OIL CONSERVATION DIVISION	ON 30 - 015 - 22528
District III 1301 W. Grand Ave, Artesia, NM 88210 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd Aztas NIM 97410	STATE FEE
District IV Santa Fe, NM 8/505	6. State Oil & Gas Lease No.
1220 S St Francis Dr., Santa Fe, NM	OG-103
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Empire Abo Unit "K"
PROPOSALS)	8. Well Number
1. Type of Well: Oil Well	232
2. Name of Operator	9. OGRID Number
BP America Production Company	000778
3. Address of Operator	10. Pool name or Wildcat
P. O. Box 1089 Eunice, New Mexico 8823	1 Empire Abo
4. Well Location	
Unit Letter 1 , 2200 feet from the Couth line	and AETO Control Control Control
Unit Letter J : feet from the South line a	ind 1570 leet from the East line
Section 6 Township 18S Range	
	28E NMPM County Eddy
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR	28E NMPM County Eddy
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure	28E NMPM County Eddy <i>GR</i> , etc.)
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well	28E NMPM County Eddy GR, etc.) Distance from nearest surface water
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well	28E NMPM County Eddy GR, etc.) Distance from nearest surface water Construction Material
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well Pit Liner Thickness: mil Below-Grade Tank: Volume bbls	28E NMPM County Eddy GR, etc.) Distance from nearest surface water Construction Material
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well Pit Liner Thickness: mil Below-Grade Tank: Volume bbls 12. Check Appropriate Box to Indicate Nature of NOTICE OF INTENTION TO:	28E NMPM County Eddy GR, etc.) Distance from nearest surface water Construction Material Notice, Report or Other Data
Section 6 Township 18S Range 11. Elevation (Show whether DR, RKB, RT, 3653.1' GR Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well Pit Liner Thickness: mil Below-Grade Tank: Volume bbls 12. Check Appropriate Box to Indicate Nature of NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMED	28E NMPM County Eddy GR, etc.) Distance from nearest surface water Construction Material Notice, Report or Other Data SUBSEQUENT REPORT OF:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

OTHER:

П

P&A operations were commenced on March 20, 2009 and completed April 6, 2009 - final WB diagram attached.

- MIRU PU and cementing equipment, pressure tested 5½" csg from surface to pkr @ 6174' to 500 psi, OK. Removed WH, installed BOP & POH w/ packer. Made trip w/ bit & scraper to 6199', OK.
- 2. TIH w/ 5½" CIBP on tbg & set @ 6174' (this revised setting depth approved by Phil Hawkins) & spotted 25 sx Class "C" onto CIBP. Bottom plug set from 5927' - 6174' = 247' on 4/1/09.
- 3. Circulated hole with 9.0 ppg mud laden fluid, pulled tbg to 3640' & spotted 25 sx Class "C" Glorieta plug. POH w/ tbg & WOC. TIH w/ tbg & tagged top of plug @ 3455'. Glorieta plug set from 3455' - 3640' = 185' on 4/2/09.
- 4. POH & LD tbg to 1260'. Circulated cement to surface inside 5½" csg using a total of 130 sx Class "C". Queen - Surface Casing Shoe - Yates - Top plugs set from 0' - 1260' on 4/2/09. POH & LD tbg. Removed BOP, topped-off csg w/ cement and RDMO equipment on 4/2/09.
- 5. Cut-off well heads and guy wire anchors to 3' below GL and installed regulation Dry Hole Marker. P&A completed as of 4/6/09

hereby certify that the information above is true an grade tank has been/will be constructed or closed according t				
SIGNATURE M. S. Wartsmall	TITLE <u>Well</u>	s Operations Superintendent	DATE _	04 / 07 / 09
Type or print name M. D. Westmoreland	E-mail address:	dan.westmoreland@bp.com	Telephone No.	432 / 688-5245
For State Use Only		Approved for plugging of well hore only	g receipt	19/20

Conditions of Approval (if any):

of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.

() + C ()

Empire Abo Unit K-232 Empire Abo Field

API No. 30-015-22528

2300' FSL & 1570' FEL Sec 6- T18S - R28E Eddy County, New Mexico

FINAL P&A Status

April 6, 2009

