

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

MAR 20 2009

Form C-103
May 27, 2004

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-04554
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator BEACH EXPLORATION, INC.		6. State Oil & Gas Lease No.
3. Address of Operator 800 NORTH MARIENFELD, SUITE 200, MIDLAND, TX 79701		7. Lease Name or Unit Agreement Name ELLIOTT
4. Well Location Unit Letter M; 330 feet from the SOUTH line and 330 feet from the WEST line Section 31 Township 18S Range 30E NMPM EDDY County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 1903
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>		10. Pool name N/A
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____		
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER RE-PLUG FOR EASTLAND QUEEN UNIT WATER FLOOD ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09/16/08 Removed dry hole marker - no surface plug present
09/17/08 RU rat hole machine. Drilled 20" hole to 40', ran 14" conductor pipe and cmt'd w/2 5 yds of ready mix
09/18/08 Welded wellhead on 14" conductor pipe.
10/10/08 Notified Mike Bratcher (NM OCD) would start plugging operations 10/14/08
10/16/08 RU. NU BOP and ran 9 7/8" bit. No surface cmt plug. Rotated down and tagged cutoff 8 5/8" csg at 244'
10/16/08 Got inside 8 5/8" csg w/ 7 7/8" bit No cmt at base of 8 5/8" csg Drld cmt 918' to 1156'
10/20/08 Came out of 8 5/8" csg and couldn't get back in. Milled 8 5/8" csg to 249' and cleaned w/tapered mill
10/22/08 Got back in 8 5/8" csg w/ 6 1/8" bit. Drld cmt from 1156' to 1219'. Cleaned out open hole to 2497' ✓
Notified Mike Bratcher (NM OCD) would be setting plugs 10/23/08
10/23/08 Loaded hole w/9ppg salt gel
Pumped 50sx Class C cmt plug from 2428' and tagged at 2248' (180' open hole plug) ✓
Pumped 50sx Class C cmt plug from 1767' and tagged at 1585' (182' open hole plug) ✓
10/24/08 Pumped 50sx Class C cmt plug from 1283' and tagged at 1147' (136' open hole plug) ✓
Pumped 150sx Class C cmt plug from 417' and tagged at 143' (274' - 8 5/8" shoe and stub plug combined) ✓
Pumped 30sx Class C cmt plug from 60' to surf. ✓
10/27/08 Notified Mike Bratcher (NM OCD) of all cmt plugs
Removed anchors. Cutoff wellhead Set regulation dry hole maker

AWAITING FORM
C103 - LOCATION READY
REPORT

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jack M. Rose TITLE Engineer DATE March 18, 2009

Type or print name Jack M. Rose

E-mail address: bmartin@beachexp.com Telephone No. (432) 683-6226

For State Use Only

APPROVED BY: Richard Inge TITLE COMPLIANCE OFFICER DATE 4/24/09
Conditions of Approval (if any):

30sx Surf Plug 0' - 60'

Tagged 274' plug
150sx plug
143' - 417'

T Salt
@347'

Tagged 136' OH plug
50sx plug
1147' - 1283'

Yates
@1380'

Tagged 182' OH plug
50sx plug
1585' - 1767'

7 Rivers
@1750'

Tagged 180' OH plug
50sx plug
2248' - 2428'

Queen
@2415'

Clean Out to 2497'

40' 14" conductor
cmt'd w2.5 yds

Cutoff csg 249'

10sx plug at 4280'

TD 4280

Elliott #1

GL: 3,431 Status: P&A
KB: TD: 4,280 Perfs:
PBD: API: 30-015-04554
Fr. Wtr: Legal: 330 from S
330 from W NM Lse:
Section: 31-M Field:
Township: 18S Logs:
Range: 30E Archeological:
County: Eddy

Casing	Wt	Type	Set	Cmt	Hole	TOC	Method
8-5/8"			355	50	10" ? 7-7/8" ?	160'	csg pulled

- 6-Aug-50 Spud well
Roach & Shepard Drilling Co. - Elliot #1
- 23-Oct-50 **D&A**
Drid to TD 4280 and plugged - no plugging record
Field Inspection - has a marker
- 30-Oct-50 **Plugging Detail** - Elliot Industries Records (Sundry notice and Dept of Interior)
10sx plug spotted at 4280', mudded back to 1168'
10sx plug spotted at 1168', mudded back to 350'
10sx plug spotted at 350', pulled 160' of 8-5/8" csg
mudded to surface and spotted cmt plug w/marker
- Beach Re-plug for Eastland Queen Waterflood**
- 09/16/08 Removed dry hole marker - no surface plug present
09/17/08 RU rat hole machine. Drilled 20" hole to 40', ran 14" conductor pipe and cmt'd w/2.5 yds of ready mix
09/18/08 Welded wellhead on 14" conductor pipe.
10/10/08 Notified Mike Bratcher (NM OCD) would start plugging operations 10/14/08
10/16/08 RU. NU BOP and ran 9 7/8" bit. No surface cmt plug. Rotated down and tagged cutoff 8 5/8" csg at 244'.
10/16/08 Got inside 8 5/8" csg w/ 7 7/8" bit. No cmt at base of 8 5/8" csg.
Drid cmt 918' to 1156'
10/20/08 Came out of 8 5/8" csg and couldn't get back in. Milled 8 5/8" csg to 249' and cleaned w/tapered mill
10/22/08 Got back in 8 5/8" csg w/ 6 1/8" bit. Drid cmt from 1156' to 1219'.
Cleaned out open hole to 2497'
Notified Mike Bratcher (NM OCD) would be setting plugs 10/23/08
10/23/08 Loaded hole w/9ppg salt gel
Pumped 50sx Class C cmt plug from 2428' and tagged at 2248' (180' OH plug)
Pumped 50sx Class C cmt plug from 1767' and tagged at 1585' (182' OH plug)
10/24/08 Pumped 50sx Class C cmt plug from 1283' and tagged at 1147' (136' OH plug)
Pumped 150sx Class C cmt plug from 417' and tagged at 143'
(274' - 8 5/8" shoe and stub plug combined)
Pumped 30sx Class C cmt plug from 60' to surf.
10/27/08 Notified Mike Bratcher (NM OCD) of all cmt plugs
Removed anchors. Cutoff wellhead. Set regulation dry hole maker