

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

MAY - 7 2009

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.

30-015-05956

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Johnston

8. Well Number

1Y

9. OGRID Number

6137

10. Pool name or Wildcat

San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

DEVON ENERGY PRODUCTION COMPANY, LP

3. Address of Operator

20 North Broadway, Ste 1500, Oklahoma City, OK 73102

405-552-4615

4. Well Location

Unit Letter L: 2340' feet from the SOUTH line and 990' feet from the WEST line

Section 7 Township 18S Range 27E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3283' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 4/21/09: MIRU. TIH to CIBP @ 900'. Circulate hole w/10# mud.
- Cut 5-1/2" casing @ 700'. (TOC @ 800' by temp survey)
- POOH and lay down casing.
- TIH and spot 50 sx cement on CIBP @ 900'. Tagged TOC @ 589'. (8-5/8" shoe @ 872')
- Circulate 30 sx cement from 110' to surface.
- 5/1/09: Remove wellhead, install P&A marker, clean location. Plugged & Abandoned.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 5/5/09

Type or print name Ronnie Slack

E-mail address: Ronnie.Slack@dvn.com

Telephone No. 405-552-4615

For State Use Only

APPROVED BY: [Signature] TITLE \_\_\_\_\_

DATE 5/7/09

Conditions of Approval (if any):

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms. [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed).

**DEVON ENERGY PRODUCTION COMPANY LP**

Well Name: JOHNSTON 1Y		Field: RED LAKE	
Location: 2340' FSL & 990' FWL; SEC 7-T18S-R27E		County: EDDY	State: NM
Elevation: 3283' GR		Spud Date: 4/7/58	Compl Date: 8/19/58
API#: 30-015-05956	Prepared by: Ronnie Slack	Date: 5/5/09	Rev:

**PLUGGED & ABANDONED**  
5/1/09

1. Circulate 30 sx cement from 110' to surface
2. Remove wellhead, set dry hole marker
3. Clean location

10# Mud

TOC @ 800' by temp survey →

1. TIH to 900', displace hole w/10# mud
2. Cut 5-1/2" casing @ 700'
3. POOH & LD casing
4. Spot 50 sx on CIBP @ 900'
5. WOC. Tagged TOC @ 589'

11" Hole  
8-5/8", 24#, @ 872'  
Cmt'd w/590 sx, circulated to surface  
(8.097" id; .3575 ft³/ft)

QUEEN - GRAYBURG - SAN ANDRES  
990' - 998'

CIBP @ 900' (set 11/11/97)

1540' - 1566'

1642' - 1670'

7-7/8" Hole  
5-1/2", 14#, @ 1,810'  
Cemented w/225 sx cement. TOC @ 800' by temp survey  
(5.012" id; .1370 ft³/ft)

1772' PBTD

1810' TD