Submit 3 Copies To Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505		JUN 23 2009	Form C-103 June 19, 2008
<u>District I</u> 1625 N French Dr., Hobbs, NM 88240 District II			WELL API NO. 30-015-36979	,,,200
1301 W. Grand Ave., Artesia, NM 88210 District III			5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV			STATE State Oil & Gas Lease	FEE
1220 S. St. Francis Dr., Santa Fe, NM 87505	,		o. State on the Gas Bease	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		7. Lease Name or Unit Agreement Name ENRON STATE		
PROPOSALS.) 1. Type of Well: Oil Well			8. Well Number #14	
2. Name of Operator			9. OGRID Number 255333	
LIME ROCK RESOURCES A, L.P. 3. Address of Operator			10. Pool name or Wildcat	
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		Red Lake, Glorieta-Yeso NE (96836)		
4. Well Location				
Unit Letter C: 990 feet from the NORTH line and 2035 feet from the WEST line				
Section 32 Township 17-S Range 28-E NMPM Eddy County				
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3700' GL				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR				NG CASING 🗌
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRIL	<u> </u>	A 🗆
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	JOB 🛛	
DOWNHOLE COMMINGLE				
OTHER:			& Surface & Production Ca	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
Spud well on 6/9/09. Drilled 12-1/4" hole to 360'. Landed 8-5/8" 24# J-55 csg @ 348'. Cmted lead w/150 sx (203 cf) C cmt w/2% Cacl2 & 1/4# pol-e-flake. Tailed w/200 sx (270 cf) C cmt w/2% Cacl2. Circ 158 sx cmt to surface. On 6/10/09, PT 8-5/8" csg to 1000 psi for 30 min – OK.				
Drilled 7-7/8" hole to TD4205' on 6/18/09. On 6/18/09, landed 5-1/2" 17# J-55 csg @ 4195'. Cmted w/400 sx (756 cf) 35/65 poz C cmt w/0.125 pol-e-flake, 3# salt, & 3# gilsonite & tailed w/550 sx (732 cf) C cmt w/0.125 pol-e-flake, 0.4% Lap-1, 0.5% CFR-3, & ½# Deair. Circ 136 sx cmt to pit. Plan to pressure test csg during completion operations. Released drilling rig on 6/19/09.				
Spud Date: 6/9/09	Drilling Rig	Release Date:	6/19/09	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Mike Lippin TITLE Petroleum Engineer - Agent DATE 6/19/09				
Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573				
For State Use Only	$\langle \cdot \rangle$	<u> </u>		1 10 -
	qu & TITLE	Creologis	TDATE	6/2309
Conditions of Approval (if any):	1	1		, ,