Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

334

FOI OMI Exp

SUNDRY NOTICES AND REPORTS ON WELLS

5 Lease Serial No

RM APPROVED	
B No 1004-0137	
res July 31, 2010	

	ot use this form for proposals to drill o	' 1	UCI 14 200			
abandoned well. Use Form 3160-3 (APD) for such proposals		such proposals.	NMOCD ARTI		6 Il Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2.			greement, Name and/or No			
1 Type of Well						
Oil Well	Gas Well X Other	P&A		8. Well Name and	8. Well Name and No	
2 Name of Operator				Roden GD F	ederal #2	
Yates Petroleum Corpor				9 API Well No		
3a Address 3b Phone No (include area code)		30-015-2585	· · · · · · · · · · · · · · · · · · ·			
105 S. 4th Str., Artesia, NM 88210 575-748-1471 4 Location of Well (Footage, Sec ,T.,R ,M., OR Survey Description)			l or Exploratory Area			
4 Location of Well (Footage, Sec	c , r.,k ,m., Ok Survey Description)			Canyon; Wo		
1980'FSL & 1980'FWL of Section 25-T19S-R24E (Unit K, NESW)			· ·	Eddy County, New Mexico		
	PPROPRIATE BOXES) TO IN		TIRE OF NOTICE			
· · · · · · · · · · · · · · · · · · ·		NDICATE IVAI			THERDATA	
TYPE OF SUBMISSION	ON		TYPE OF ACTIO)N		
	Acidize	Deepen	Produc	tion (Start/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture T	reat Reclam	ation	Well Integrity	
	Casing Repair	New Cons	truction Recom	plete	Other	
Subsequent Report				•		
[]	Change Plans	X Plug and A	bandon	rarily Abandon		
Final Abandonment N	Votice Convert to Injection	Plug Back	Water I	Disposal		
9/25/09 Pumped 130 9/28/09 Pumped 50 b 9/29/09 Circulated hol 4 hrs. Tagger 9/30/09 Tagged ceme 6010'-6239'. a 25 sx Class 10/1/09 Load hole with Pumped 50 b down bradenh a plug across WOC 4 hrs.	bbls cut brine down annulus. bls down tubing. Pumped 80 le with fresh water. Pumped d soft cement at 6252'. Pument at 6239'. Perforated at 62 WOC 4 hrs. Tagged cement "C" cement plug from 5233' h fluid. Pressure up on 7" cabls fluid down 7" casing at 50 head. Loaded and pressured squeeze holes at 1262'. PuTagged at 974'. Perforated 40 pressured at 974'. Perforated 41 pressured at 974'.	Unseat pum bbls down and a 45 sx Class apped a 25 sx Class apped a 25 sx Class apped a 26'. Distant at 6126'. Distant 6126'. Pumpersing to 300 ps asing to 300 ps apped a 40 sx 4 squeezed ho	p. TOOH with tubin nulus. NU BOP. s "C" cement plug values "C" cement pumped a 35 sx Class placed hole with need a 25 sx Class "si, held good. Perfoulation out of braci. Unable to circula Class "C" cement ples at 150'. Estab	Liability under Surface restor with 2% CC from lug with 2% CC from 10% of the content of the con	ar bond is retained untilication is completed. 6160'-6427'. WOC from 6093'-6245'. From 1828'-1990'. The holes at 1262'. The holes at 1262'.	
	nent at 14.8 ppg. Circulated P. Cut off wellhead.	cement down	/ and 9-5/8 casi	ng. Circulated 2	b sx cement to	
10/2/09 Installed dry h	nole marker. WELL IS PLUC	GGED AND A	BANDONED.		Section 1998 1998	
14 I hereby certify that the forego Name (Printed/Typed)	oing is true and correct		_			
	Tina Huerta	Title	Regulatory Com	pliance suppors	EUD DEUUDI	
Signature () [()	Date	October 5, 2009	AUULIT		
	THIS SPACE FO	OR FEDERAL OI	R STATE OFFICE USE		CT 1 0 2000	
Approximate				1 1		
Approved by Conditions of approval if any are	e attached Approval of this notice does	not warrant or	Title	Date	Comi	
	egal or equitable title to those rights in the		Office	BUREAU	OF LAND MANAGEMENT	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any peparaters or agency but the Whited States

any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction