

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OCT 05 2009

Form C-103
June 19, 2008 *LM*

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-35193
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name South Red Lake II Unit
8. Well Number #52
9. OGRID Number 241598
10. Pool name or Wildcat Red Lake, Queen, Grayburg, San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,575' GR

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Fairway Resources Operating, LLC

3. Address of Operator
538 Silicon Dr., Suite 101, Southlake, TX 76092

4. Well Location
Unit Letter E : 1,780 feet from the North line and 875 feet from the West line
Section 36 Township 17S Range 27E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☒ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/5/2009 Anticipated T&A date

1. MIRU wireline unit. Set CIBP @ +/- 1475'. RD Wireline unit.
2. MIRU WSU. PU and TIH w/ 2 3/8" tbg.
3. Circ hole w/ pkr fluid containing 1 gal/1000 corrosion inhibitor and oxygen scavenger.
4. Pressure test csg to 500 psig for 30 minutes.
5. TOH LD tbg. NU WH. T/A well.

LAST PRODUCTION REPORT
6/1/07

Temporary Abandoned Status Approved
Until 6/1/2012

Spud Date:

11/19/2006

Rig Release Date:

12/5/2006

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Star Hasse* TITLE Engineering Tech DATE 9/29/09

Type or print name Star Hasse E-mail address: shasse@fairwayresources.com PHONE: 817-416-1946 x223

For State Use Only

APPROVED BY: *Richard Nae* TITLE Compliance Officer DATE 10/14/09

Conditions of Approval (if any):