

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103 *PM*
 June 19, 2008

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-015-36976 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. |
| 7. Lease Name or Unit Agreement Name STALEY STATE |
| 8. Well Number #11 |
| 9. OGRID Number 255333 |
| 10. Pool name or Wildcat: (96836) Red Lake, Glorieta-Yeso NE |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3586' GL |

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location
 Unit Letter L : 1650 feet from the SOUTH line and 330 feet from the WEST line
 Section 30 Township 17-S Range 28-E NMPM Eddy County

RECEIVED
 OCT 30 2009
 MOCD ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

| | | | |
|--|---|---|--|
| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | P AND A <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | MULTIPLE COMPL <input type="checkbox"/> | CASING/CEMENT JOB <input type="checkbox"/> | |
| DOWNHOLE COMMINGLE <input type="checkbox"/> | | | |
| OTHER: <input type="checkbox"/> | | OTHER: COMPLETION <input checked="" type="checkbox"/> | |

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 10/15/09, PT 5-1/2" csg to 5000 psi for 30 min-OK. Perfed lower Yeso @ 4196', 97', 98', 4230', 32', 33', 34', 35', 36', 60', 61', 65', 66', 67', 68', 69', 70', 71', 72', 79', 80', 85', 86', 87', 88', 95', 96', 4307', 08', 09', 10', 11', 13', 14', 19', 20', 56', 57', 60', 62', 85', 86', 87', 88', 93', 95', 96', 97', 98', 4433', 35', 36', 43', 44', 45', 50', 54', 55', 64', 65', 66', 68', 69', 4504', 05', 12', 13', 14', 16', 17', 18', 19', 20', 21', 22', 23', 31', 32', 33', 65', 66', 67' w/1-0.42" spf. Total 82 holes. Treated w/5000 gal 15% NEFE acid & 165 perf balls. On 10/18/09, fraced lower Yeso w/140,987# 16/30 prem. white & 25,604# 16/30 super LC sand in 18# X-linked gel.

Set 5-1/2" CBP @ 4150'. PT csg to 5000 psi for 30 min-OK. Perfed middle Yeso @ 3858', 59', 60', 61', 75', 76', 91', 92', 93', 94', 3921', 22', 23', 32', 33', 34', 39', 40', 42', 43', 47', 49', 51', 52', 53', 55', 57', 59', 60', 61', 63', 65', 66', 67', 68', 71', 72', 73', 74', 76', 77', 81', 83', 87', 88', 89', 96', 99', 4017', 18', 19', 20', 23', 25', 27', 40', 41', 42', 43', 46', 47', 48', 49', 50', 51', 52', 53', 54', 56', 57', 58', 77', 78', 79', 83', 84' w/1-0.42" spf. Total 76 holes. Treated perfs w/6175 gal 15% NEFE acid & 150 perf balls. Fraced w/65,950# prem. White 16/30 & 41,899# super LC 16/30 sand in 18# X-linked gel.

Set 5-1/2" CBP @ 3820'. PT csg to 5000 psi for 30 min-OK. Perfed upper Yeso @ 3561', 62', 63', 64', 65', 66', 70', 71', 85', 86', 88', 89', 90', 93', 98', 99', 3606', 08', 09', 13', 14', 15', 48', 49', 50', 51', 52', 53', 54', 55', 56', 57', 58', 59', 60', 61', 86', 87', 88', 89', 90', 3707', 08', 15', 16', 17', 18', 25', 26', 27', 28', 29', 48', 49', 58', 59' w/1-0.42" spf. Total 56 holes. Treated perfs w/5549 gal 15% NEFE acid & 100 perf balls. Fraced w/79,623# prem. white 16/30 & 27,197# super LC 16/30 sand in 18# X-linked gel.

On 10/20/09, MIRUSU. Drilled CBPs @ 3820' & 4150' & CO to 4711'. On 10/21/09, landed 2-7/8" 6.5# J-55 tbg @ 4573. Ran pump & rods & initiated pumping frac fluid. Released completion rig on 10/22/09.

Spud Date: 8/26/09 Drilling Rig Release Date: 9/8/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Mike Pippin* TITLE Petroleum Engineer - Agent DATE 10/29/09

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: *[Signature]* TITLE Geologist DATE 11/1/2009
 Conditions of Approval (if any)