Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0135 Expires. July 31, 2010

□ Water Shut-Off

☐ Well Integrity

□ Other

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

5.	Lease Serial No.	
	NMLC055561	

Production (Start/Resume)

Temporarily Abandon

☐ Reclamation

□ Recomplete

abandoned wel	. Use form 3160-3 (APD) for s	RECFIVED	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRII	PLICATE - Other instructions	on reverse side. NOV 1 8 2009	7. If Unit or CA/Agreement, Name and/or No. NMNM109695X
1. Type of Well ☐ Gas Well ☐ Oth	er Contact: STAR	NMOCD ARTESIA	8 Well Name and No. S RED LAKE II UNIT 45
2 Name of Operator FAIRWAY RESOURCES	9 API Well No. 30-015-25156-00-S1		
3a. Address 538 SILICON DRIVE STE 101 SOUTHLAKE, TX 76092	. Ph: 8	none No. (include area code) 817-416-1946 17-416-1949	10. Field and Pool, or Exploratory RED LAKE
4. Location of Well (Footage, Sec., T	11. County or Parish, and State		
Sec 35 T17S R27E NWNE 33	EDDY COUNTY, NM		
12. CHECK APPR	OPRIATE BOX(ES) TO INDI	CATE NATURE OF NOTICE,	L REPORT, OR OTHER DATA
TYPE OF SUBMISSION			

☐ Convert to Injection □ Plug Back □ Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the cite is ready for final inspection.) determined that the site is ready for final inspection.)

Deepen Deepen

☐ Fracture Treat

■ New Construction

☐ Plug and Abandon

□ Notice of Intent

Subsequent Report

☐ Final Abandonment Notice

□ Acidize

Alter Casing

Casing Repair

☐ Change Plans

History:
Spud 09/28/1983.
8-5/8" surface casing at 120'; cement circ to surface.
5-1/2" production casing at 1875'; cement w/ 425 sx. (Calculated TOC @ 36')
CIBP at 1300' w/ 25 sx cement on top; paker and tbg below CIBP. Top of tubing @ 1320'.

Current status - SI oil well.

Cleaned out wellbore to PBTD @800'. Drilled shoe track to 1915' and started circ up drilling mud and metal. Estimate bottom of casing @ 1914'. Attempted to mill over junk with no success. Ran impression block that indicated 4 1/2" round fish; possible DC or bit thread. Abandoned deepening.

14 Thereby certify	that the foregoing is true and correct. Electronic Submission #77261 verified For FAIRWAY RESOURC Committed to AFMSS for processing by CH	ES, sei	nt to the Carlsbad	 E)	
Name (Printed/Typed) JAY PULTE		Title	ENGINEER		
Signature	(Electronic Submission)	Date	11/12/2009		
	THIS SPACE FOR FEDERA	AL OR	STATE OFFICE USE		
Approved By ACCEPTED			CHRISTOPHER WALLS PETROLEUM ENGINEER		Date 11/17/2(
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			⊂ Carlsbad		OU

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #77261 that would not fit on the form

32. Additional remarks, continued

Contacted Wesley Ingram, BLM, on Wednesday, 8/12/09, 3:30 PM, and received verbal approval to set CIBP & 35' of cement @ base of csg and whipstock around junk in hole.

Set CIBP @ 1836' w/ 35' of cement. TOC @ 1801'. Orient whipstock to 195 degrees & set. Mill window & drilled 5' of formation. POH w/ bit. Prepare to drill ahead.

THIS IS A RESUBMISSION OF THE ORIGINAL SUNDRY NOTICE SUBMITTED IN AUGUST 2009. THE ORIGINAL NOTICE APPEARS TO BE HUNG UP.