

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-00202
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Atoka San Andres Unit
8. Well Number 130
9. OGRID Number 6137
10. Pool name or Wildcat San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG TACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
DEVON ENERGY PRODUCTION COMPANY, LP

3. Address of Operator
20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615

4. Well Location
Unit Letter **A** : **330'** feet from the **North** line and **330'** feet from the **East** line
Section **14** Township **18S** Range **26E** NMPM County **Eddy**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3300' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 11/10/09-- MIRU. Tag CIBP @ 1577'. Circulate wellbore w/9.5 ppg mud.
- Spot 25 sx cmt on CIBP from 1337' to 1577'.
- Spot 35 sx cmt @ 1,150'. Tagged TOC @ 812'. (8-5/8" csg shoe @ 1,100').
- 11/12/09-- Circulate 25 sx cement from 240' to surface.
- 11/20/09-- Wellhead cut off and P&A marker set.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Operations Technician DATE 11/23/09

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com Telephone No. 405-552-4615
For State Use Only

APPROVED BY: [Signature] TITLE _____ DATE 11/25/09
Conditions of Approval (if any):

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ATOKA SAN ANDRES UNIT #130		Field: RED LAKE	
Location: 330' FNL & 330' FEL; SEC 14-T18S-R26E		County: EDDY	State: NM
Elevation: 3300' GL		Spud Date: 7/18/57	Compl Date: 8/6/57
API#: 30-015-00202	Prepared by: Ronnie Slack	Date: 11/23/09	Rev:

PLUGGED & ABANDONED
11/20/09

1. Circulate 25 sx cmt from 240' to surface. (11/12/09)
2. Wellhead cut off & dry hole marker set. (11/20/09)

9.5 ppg mud

10" Hole
8-5/8", 24#, @ 1,100'
Cmt'd w/400 sx, circ to surface

Spot 35 sx cmt @ 1150'. Tag TOC @ 812'
(11/12/09)

9.5 ppg mud

Spot 25 sx cmt from 1337' to 1577' (11/11/09)

SAN ANDRES (8/10/57)
1,670' - 1,680'

CIBP @ 1577' (3/15/82)

7-7/8" Hole
5-1/2", 14#, @ 1,742'
Cmt'd w/380 sx, circ to surface
5.012 id, .1370 ft³/ft

1,722' PBTD

1,742' TD