

CFO SPUD NOTICE

SPUD DATE: 1/11/10 APROX. SPUD TIME: NOON
 RECEIVED BY: F. Cornwright RECEIVED DATE: 1/11/10
 OPERATOR: YOROS LEASE NO: 111111
 WELL NAME & NO: Swiper BEP #9H API NO: 30-015-37407
 LEGALS: $\frac{1}{4}, \frac{1}{4}$ SEC: 4 T: 24 S: 29 E:

RIG NAME & NUMBER: BEETRIOT #5 COMPANY REP: Dove Williamson
 PHONE NUMBER: 575-308-9780 CEMENT COMPANY: S&L
 INSPECTION NOTES:

OPERATOR INTENTIONS ON HOLE & CASING DESIGN									
HOLE		CASING						PLACEMENT OF CENTRALIZERS	
	SIZE	DEPTH	SIZE	DEPTH	WEIGHT	GRADE	WITNESS		
SURFACE	17 1/2	600	13 3/8	600	48	H-40	☒	☒	5
INTERMEDIATE	12 1/4	2850	9 1/8	2850	36	G-55	☒	☒	
PRODUCTION	8 3/4	12084	5 1/2	12084	17	H-40	☐	☒	
INITIAL SPUD NOTICE REMARKS <u>C-80</u>									
*Request documentation on cements to be used & cement wait time (Per COA)									

HOLE & CASING DESIGN AS APPROVED ON APD									
HOLE		CASING						MINIMUM CENTRALIZERS REQUIREMENTS	
	SIZE	DEPTH	SIZE	DEPTH	WEIGHT	GRADE	WITNESS		
SURFACE							☐	☒	Starting with shoe joint, 1 per joint on the 1st 3 bottom joints
INTERMEDIATE			SAME				☐	☒	
PRODUCTION							☐	☒	

NOTE: Before installing BOP-check the "Wellhead Pressure Rating" against the required "BOP Test Pressure" for compatibility

ACTIVITY	BOP SIZE	WITNESS				INSPECTOR	DATE	REMARKS
SURF. CMT		☐	☒	☐	☒			
SURF BOP		☐	☒	☐	☒			
INT. CMT		☐	☒	☐	☒			
INT. BOP		☐	☒	☐	☒			

W.C. BOP		Required 500' above Wolfcamp if more than 20 days from last test.
OTHER		

LEAD REMARKS

INSPECTOR REMARKS

☐	WORKING FILE	☐	OFFICIAL FILE	DRILLING LOG BOOK	
☐		☐		☐	SURFACE
☐		☐		☐	INTERMEDIATE
☐		☐		☐	PRODUCTION

Monti Sanders ⁴⁰⁰/_A
 798-4244 C144