

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-36333

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Pinnacle State

8. Well Number
25

9. OGRID Number
246289

10. Pool name or Wildcat
Culebra Bluff - Bone Spring, south

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other ☐

2. Name of Operator
RKI-Exploration & Production, LLC

3. Address of Operator
3817 NW Expressway, Ste 950, Okla. City, Ok. 73112

4. Well Location

Unit Letter M: 330 feet from the South line and 800 feet from the West line
Section 36 Township 22S Range 28E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3066' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Rig up Spud In 2-14-2010

Drill 17.5" Hole to 480'. Ran 12 joints 486.70' of 13-5/8" 54.5# J-55 ST&C Casing landed Surface Casing at 480', Float collar @ 444.55'.

Cemented With: 25 SX LEAD 6 BBLS SLURRY MIX @13.5# 1.34 YIELD THEN 525 SX. TAIL 125 BBLS SLURRY 14.8# 1.34 YIELD DISPLACED W/68 BBLS WATER BUMPED PLUG W/ 200 PSI UP TO 700 PSI BLEAD BACK FLOATS HOLDING GOOD CIRC. 20 BBLS CMT TO SURFACE.

Drilled out shoe 22.5 hours after cement in place.

Spud Date: 2-14-2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Amie Armer TITLE Prod Superintendent DATE 2-15-10

Type or print name _____ E-mail address: _____ PHONE (575) 885-1313
For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 2-18-2010

Conditions of Approval (if any):

Provide a sundry including results of Casing Pressure Test.