Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505  SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)  1. Type of Well: Oil Well Gas Well Other RECEIVED  2. Name of Operator		Form C-103 June 19, 2008  WELL API NO. 30-015-37288  5. Indicate Type of Lease STATE FEE  6. State Oil & Gas Lease No.  7. Lease Name or Unit Agreement Name  GJ West Coop Unit  8. Well Number  204  9. OGRID Number
COG Operating LLC  3. Address of Operator 550 W. Texas Ave., Suite 1300 Midland, TX 79701	PEB 2 3 2010  NMOCD ARTESIA	229137  10. Pool name or Wildcat GJ;7RVS-QN-GB-Glorieta-Yeso 97558
4. Well Location  Unit Letter A: 990 feet from the North line and 330 feet from the East line Section 16 Township 17S Range 29E NMPM County Eddy  11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3557 GR		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   ALTERING CASING   COMMENCE DRILLING OPNS.   P AND A   CASING/CEMENT JOB   CASING/CEM		
OTHER: Completion   13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
12/17/09 Test casing to 3,500 psi for 30 mins. Ok. 12/21/09 Perf Lower Blinebry @ 5100-5300 w/ 1 SPF, 26 holes. Acidize w/2,500 gals acid. Frac w/117,000 gals gel, 145,859# 16/30 BASF sand, 34,945# 16/30 SLC sand. Set comp plug @ 5060. Perf Middle Blinebry @ 4830-5030 w/1 SPF, 26 holes. Acidize w/2,500 gals acid. Frac w/ 115,000 gals gel, 146,446# 16/30 BASF sand, 37,526# 16/30 SLC sand. Set comp plug @ 4785. Perf Upper Blinebry @ 4550-4750 w/ 1 SPF, 26 holes. Acidize w/2,500 gals acid. Frac w/ 114,000 gals gel, 147,639# 16/30 BASF sand, 31,540# SLC sand. Set comp plug @ 4240. Perf Paddock @ 4010-4210 w/1 SPF, 26 holes. Acidize w/3,000 gals acid. Frac w/105,000 gals gel, 125,360# 16/30 BASF sand, 19,136# 16/30 SLC sand. 12/28/09 Drill out plugs. Clean out to PBTD 5452. 12/29/09 RIH 160w/jts 2-7/8" 6.5# J55 tbg, SN @ 5085. RIH w/ 1-1/2"x2"x24' pump. 12/30/09 Hang on well.		
Spud Date: 11/29/09 R	ig Release Date:	12/05/09
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE Agent for COG DATE 02/17/10		
Type or print name Chasity Jackson E-mail address: cjackson@conchoresources.com PHONE: 432-685-4332  For State Use Only		
APPROVED BY: David Hay TITLE Field Supervisor DATE 2-25-10  Conditions of Approval (if any):		