

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S St. Francis Dr, Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-36333
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Pinnacle State
8. Well Number 25
9. OGRID Number 246289
10. Pool name or Wildcat Culebra Bluff - Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	<b>RECEIVED</b> <b>MAR 16 2010</b> <b>NMOCD ARTESIA</b>
2. Name of Operator RKI-Exploration & Production, LLC	
3. Address of Operator 3817 NW Expressway, Ste 950, Okla. City, Ok. 73112	
4. Well Location Unit Letter <u>M</u> : <u>330</u> feet from the <u>South</u> line and <u>800</u> feet from the <u>West</u> line Section <u>36</u> Township <u>22S</u> Range <u>28E</u> NMPM County <u>Eddy</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3066' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 2-20-10 drill 11" hole to 2770.90. Land 8-5/8" 32# J-55 casing @ 2770', Float Collar @ 2754.86'.

Cement With: 20 BBLS WATER SPACER THEN 850 SX LEAD CMT MIXED @12.6# W/2.07YIELD 313 BBLS SLURRY THEN PUMP 200 SX TAIL MIXED @14.8# 1.33 YIELD 47.3 BBLS SLURRY MIXED & PUMPED 5TO6 BPM DISPLACE W/167 BBLS WATER BUMPED PLUG FLOATS LEAKED A LITTLE SHUT IN W/200 PSI CIRC.60 BBLS CMT TO SURFACE WAITLING ON CEMENT.

CUT OFF 8 5/8 CSG. WELD ON 11"X3000 TEST TO 10000 OK NIPPLE UP TEST MANIFOLD LINES BOP'S TO 3000 PSI TEST HYDRILL TO 1500 TEST OK

Drilled out cement 21.5 hours after in place.

Spud Date:

2-14-2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE PROD. SUPERINTENDENT DATE 3-15-10

Type or print name \_\_\_\_\_ E-mail address: \_\_\_\_\_ PHONE (505) 885-1313

For State Use Only

APPROVED BY: [Signature] TITLE Field Supervisor DATE 3-18-2010

Conditions of Approval (if any):