Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103	
District I	Energy, Minerals and Natural Resources		Revised June 10, 2003	
1625 N. French Dr., Habbs, NM 88240 District II	OIL CONSERVATION DIVISION		30-015- 32819 33 15 9	
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.		5. Indicate Type of Lea	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE STATE 6. State Oil & Gas Lea	FEE
1220 S. St. Francis Dr., Santa Fe, NM			o. State Off St. Clas Eva.	sc 140.
87505 SUNDRY NOTIC	7. Lease Name or Unit	Agreement Name		
(DO NOT USE THIS FORM FOR PROPOSA	Rifleman "5" State Con			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			8. Well Number	
1. Type of Well: Oil Well Gas Well	2Y			
2. Name of Operator	9. OGRID Number			
Devon Energy Production Company, LP			6137	
3. Address of Operator			10. Pool name or Wildcat	
20 North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102 4. Well Location			Happy Valley (Morrow	·
Unit Letter G: 172	5feet from the North	_ line and1750_	feet from theEast	line
Section 5	Township 22S Ran	nge 26E	NMPM Eddy	County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
3294' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☑ REMEDIAL WORK				RING CASING
TEMPORARILY ABANDON	CHANGE PLANS □	COMMENCE DRILLING OPNS. PLUG AND		
_				NDONMENT
PULL OR ALTER CASING [MULTIPLE COMPLETION	CASING TEST AN CEMENT JOB	ID 🗆	
OTHER:		OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date				
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
or recompletion.				
	1001			
1. Set open hole bridge plug @ +/- 1546'. Spot are cement on top of bridge plug. WOC 4 hrs. Tag plug. TOH. 2. Set 13-3/8" cement retainer @ +/- 580'. Pump 100 sys class "C" + 2% CaCl2 coment below retainer. 100 plug - 1000 - 1100 class class "C" + 2% CaCl2 coment below retainer.				
3. Spot 100 ses of class "C" +2% CaCl2 above retainer. Tag plug. TOH:				
4. Spot a surface cement plug inside 13-3/8" casing. woc- 74				
5. Cut off casing 3' below ground level.				
6. Set a dry hole marker.7. Restore location.				
		ъ.		
Note: Cement class "C" at 14.8 ppg with a yield of 1.32 cu. ft/sx. Dumping of any type bridging				
material must be approved by O.C.D.				
		O.C.D.		
I hereby pertify that the information of	nove is true and assembles to the Le	et of my bouled-	and baliaf	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE KINNE SACK TITLE: Bugineering Technician DATE 2/3/04				
Type or print name Ronnie G. Slack E-mail address: Ronnie.Slack@dvn.com Telephone No. 405-235-3611				
(This space for State use)	\mathcal{M}	A-011	1 . 70	EED 4 0001
APPPROVED BY	TITLE	Julo B	DAT DAT	EFEB · 4 2004
Canditions of amount if (1)	—————	· · · · · · · · · · · · · · · · · · ·	T	