erm 3160-5 rebruary 2005)

OCD-ARTESIA

FORM APPROVED OMB No 1004-0137

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Evalues March 31 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

determined that the site is ready for final inspection.)

	Expires March 31, 2007
5	Lease Serial No.
	NMNM-54856
6	If Indian, Allottee or Tribe Name

abandoned well.	Use Form 3160-3 (A	PD for such purpose	97			
SUBM	IT IN TRIPLICATE - Other	r instructions on page 2.		7. If Unit of CA/Agree	ment, Name a	nd/or No
1. Type of Well		JUN 1 0 201	0			
Oil Well Gas	Well Other	AMAGOD ARTI	=614	8 Well Name and No Dickens	29 Federal	1H
2 Name of Operator Devon Energy Production Co., LP		NMOCD ARTI	_SIA]	9 API Well No 30	-015-37385	
3a Address			ode)	10. Field and Pool or Exploratory Arca		ca
20 North Broadway OKC, OK 73102	(405)-552-7802		Dog Canyon; Wolfcamp			
4 Location of Well <i>(Footage, Sec , T</i> SESE SL 170' FSL & 790' FEL BHL 330' F Sec 29-T16S-R28E	,R,M, or Survey Description SL & 330' FWL)		11 Country or Parish, State Eddy County, NM		
12 CHE	CK THE APPROPRIATE BO	OX(ES) TO INDICATE NATUR	E OF NOTIO	CE, REPORT OR OTHI	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
✓ Notice of Intent	Acidize	Deepen	Prod	uction (Start/Resume)	Water	Shut-Off
Notice of Intent	Alter Casing		at Reclamation		Well Integrity	
	Casing Repair	New Construction	Reco	mplete	✓ Other	Revise Cementing
Subsequent Report	Change Plans	Plug and Abandon	Tem	porarily Abandon		Program & TOC
Final Abandonment Notice	Convert to Injection	Plug Back		er Disposal		
13 Describe Proposed or Completed C the proposal is to deepen direction						

Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has

Devon Energy Production Co., LP respectfully requests approval to revise the production casing cernent plan and TOC to the following attached:

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Stephanie A. Ysasaga	Title Sr. Staff Engineering Technician
Signature	Date 06/07/2010
THIS SPACE FOI	R FEDERAL OR STATE OFFICE PROVED
Approved by	Title Date
Conditions of approval, if any, are attached. Approval of this notice does not use that the applicant holds legal or equitable title to those rights in the subject leasentitle the applicant to conduct operations thereon	varrant or certify e which would Office /s/ Dustin Winkler
Title 18 U S C. Section 1001 and Title 43 U S.C. Section 1212, make it a crim fictitious or fraudulent statements or representations as to any matter within it	e for any person knowingly and willfugureate OfatANDaMANAGEMENT of the United States any CARLSBAD FIELD OFFICE
(Instructions on page 2)	

Ysasaga, Stephanie

From:

Cooper, Mark

Sent:

Sunday, June 06, 2010 6:20 AM

To:

dustin_winkler@blm.gov

Cc:

Ysasaga, Stephanie, McGowen, Gregory

Subject:

Dickens 29 Federal 1H

Dustin,

Devon Energy respectfully requests to revise the production casing cement plan for the Dickens 29 Federal 1H as follows:

Stage 1:

Lead: 350 sacks (35:65) Poz (Fly Ash):Class H Cement, 12.5 ppg, 2.05 cf/sk Tail: 1415 sacks (50:50) Poz (Fly Ash):Class H Cement, 14.2 ppg, 1.28 cf/sk

DV tool at 4,500 ft

Stage 2:

Lead 540 sacks (35:65) Poz (Fly Ash):Class C Cement, 12.5 ppg, 2.04 cf/sk Tail: 100 sacks (60:40) Poz (Fly Ash):Class C Cement, 13.8 ppg, 1.37 cf/sk

Planned TOC 1,800 ft (9-5/8" casing is set at 2,313 ft).

Thank you.

Mark Cooper
Drilling Engineer
Western Division Permian Drilling
405-228-8264 (office)
405-613-7184 (cell)
405-513-6557 (home)
mark.cooper@dvn.com

Devon Energy Production Company, LP NM-54865- Dickens 29 Federal #1H

API: 30-015-37385

Eddy County, New Mexico

RE: Cement Change – Conditions of Approval

Centralizers required on horizontal leg, must be type for horizontal service and minimum of one every other joint.

- 1. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - a. First stage to DV tool, cement shall:
 - Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool, cement shall:
 - Cement should tie-back at least 500 feet into previous casing string. Operator shall provide method of verification.

DHW 060610