District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For closed-loop systems that only use above

Form C-144 CLEZ

July 21, 2008

ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.

# Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Type of action: Permit Closure

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a

closed-loop system that only use above ground steel tanks or haul-off bins and			
Please be advised that approval of this request does not relieve the operator of liabi environment. Nor does approval relieve the operator of its responsibility to comply	lity should operations result in pollution of so with any other applicable governmental au	surface water, ground water or the thority's rules, regulations or ordinances.	
Operator: _Edge Petroleum Operating Co. In  Operator: _Edge Petroleum Operating Co. In  Operator:Edge Petroleum Operator:Edge Petrole		RECEIVED	
Address: POB 51937 Midland, TX 79710		JUL 1 2010	
Facility or well name: East Turkey Track 3 Federal #1		] ]	
API Number: _30-015-34435OC	CD Permit Number: 210499	NMOCD ARTESIA	
U/L or Qtr/Qtr F Section 3 Township 19S	Range 30E County: Eddy		
Center of Proposed Design: Latitude _32°41'29.86' N Longitude _103°57'4			
Surface Owner:  Federal  State  Private Tribal Trust or Indian Allotment			
2.  □ Closed-loop System: Subsection H of 19.15.17.11 NMAC  Operation: □ Drilling a new well ☑ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) □ P&A  ☑ Above Ground Steel Tanks or □ Haul-off Bins			
3.  Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers			
☐ Signed in compliance with 19.15.3.103 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Box 5) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC  Previously Approved Design (attach copy of design) API Number:30-025-38877			
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.			
Disposal Facility Name: CRI Halfway Facility	_		
Disposal Facility Name: Disposal Facility Permit Number:			
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that <i>will not</i> be used for future service and operations?  Yes (If yes, please provide the information below) No			
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
6. Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.			
Name (Print): _Angela Lightner Title: _Regulatory Consultant			
Signature: Urice & higher Date: _06/29/2010			
e-mail address:angela@rkford.com	Telephone: 432-682-0440		

OCD Approval: Permit Application (including closure plan) Closure Plan		
OCD Representative Signature:	Approval Date: 07/06/2010	
Title: DIST IL Superusor	OCD Permit Number: 210499	
8.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.  The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:		
9. Closure Report Regarding Waste Removal Closure For Closed-loop Systems	That Utiliza Abaya Cround Stool Tanks or Haul off Ring Only	
Instructions: Please indentify the facility or facilities for where the liquids, drill two facilities were utilized.		
Disposal Facility Name:	Disposal Facility Permit Number:	
Disposal Facility Name:		
Were the closed-loop system operations and associated activities performed on or in areas that <i>will not</i> be used for future service and operations?  Yes (If yes, please demonstrate compliance to the items below)  No		
Required for impacted areas which will not be used for future service and operation  Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	ons:	
10. Operator Closure Certification:		
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.		
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	

## Edge Petroleum Operating Company, Inc.

### Closed Loop Mud System

### Design

Drilling mud will circulate through a closed system consisting of steel pits on the surface, mud pumps, piping on the surface to the rotating head, and return piping from the bell nipple back to the steel pits. Solids will be removed from the mud in the steel pits using the following equipment:

- 1) 2 shale shakers will be installed with 110-250 mesh screens. These shale shakers should remove solids down to 65 micron diameter. All return drilling mud will flow across the shale shakers.
- 2) A 6T4 mud cleaner will be installed to further remove solids to the 25 micron level. Drilling mud will be circulated through the mud cleaner using a 5x6x12 75 hp pump. This pump will generate the optimal pressure for the mud cleaner cones to process the solids.
- 3) A 518 centrifuge will pick up a portion of the effluent from the mud cleaner. The centrifuge will remove solids to the 10 micron level. The centrifuge will remove solids down to the 1 micron level after adding the dewatering unit, as discussed below.
- 4) A dewatering unit will add polymer to the flow stream entering the centrifuge to flocculate the solids. Flocculation increases the effective particle size of the solids, enhancing the performance of the centrifuge to remove solids down to the 1 micron level.
- 5) Roll-off bins (20 cubic yards per bin) and rails will be installed next to the steel pits so that the solids removed from the shale shakers, mud cleaner, and centrifuge fall directly into a bin. Once a bin is full, it is picked up by a truck and hauled to disposal. An empty bin is moved under the solids control equipment along the rail so that the solids control equipment can operate continuously.

#### Operation and Maintenance

Personnel dedicated exclusively to operating and maintaining the solids control equipment will be on site 24 hours per day while drilling. The solids control personnel will monitor the shale shakers, mud cleaner, centrifuge, dewatering unit, and all associated pumps and piping to make sure the equipment is functioning correctly. If equipment problems are identified, the solids control personnel will coordinate repair or replacement of the equipment. The solids control personnel will also monitor the level of solids in the roll-off bins and arrange for trucks to pick up the bins when they are filled.

### Closure Plan

Cuttings and other solids will be hauled off to a permitted landfill according to OCD guidelines. Liquids will be re-used to the extent possible, but if liquids need to be disposed, they will also be hauled to a permitted disposal facility. Liquids to be temporarily stored on site will be placed in 500 bbl "frac" tanks.

For the Lusk 27-3 well, both solid waste and liquid waste will be taken to the Controlled Recovery, Inc. (CRI) "Halfway Facility" between Carlsbad and Hobbs NM-01-0006.