

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED  
OMB No. 1004-0137  
Expires March 31, 2007

RECEIVED  
JUN 29 2010  
NMOCD ARTESIA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.*

**SUBMIT IN TRIPLICATE- Other instructions on reverse side.**

1 Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other P & A		5 Lease Serial No NMNM 114969
2 Name of Operator BTA Oil Producers		6 If Indian, Allottee or Tribe Name ---
3a Address 104 S. Pecos, Midland, TX 79701	3b Phone No (include area code) 432-682-3753	7 If Unit or CA/Agreement, Name and/or No ---
4 Location of Well (Footage, Sec, T, R, M, or Survey Description) UL -K-, Sec. 18, T26S-R27E 1980' FSL & 1980' FWL		8 Well Name and No Owl Draw Unit, 20504 JV-P #1 SWD
		9 API Well No. 30-015-10730
		10 Field and Pool, or Exploratory Area Wildcat
		11 County or Parish, State Eddy Co., NM

**12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Re-Enter P & A well
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	to place cmt plug on
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	9-5/8" csg stub

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection )

BTA respectfully submits the attached procedure for re-entry into the plugged wellbore to place a cement plug on the 9-5/8" casing stub.

[Attachment]

**SEE ATTACHED FOR  
CONDITIONS OF APPROVAL**

**RECLAMATION PROCEDURE  
ATTACHED**

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Pam Inskeep		Title Regulatory Administrator
Signature <i>Pam Inskeep</i>	Date 06/18/2010	

THIS SPACE FOR FEDERAL OR STATE OFFICE USE		<b>APPROVED</b> JUN 24 2010 /s/ Dustin Winkler BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE
Approved by <i>[Signature]</i>	Title Office	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		
Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		

(Instructions on page 2)

BTA Oil Producers  
20504 JV-P Owl Draw Unit No.1  
Re-Enter P&A Well to Place Cement Plug on 9-5/8" casing stub  
Wildcat Field  
Eddy County, New Mexico

<u>Well Data:</u>	TD 13,510'	<u>Elevations:</u>	3333' KB
	BP Surf		3316' GL
			17' Diff

Casing: 13 3/8" 48# CSA 659' w/ 490 Sx (Cut 6' below GL)  
9 5/8" 40 & 43.5# CSA 5,743' w/ 1100 Sx in 2 stgs, DV tool @ 2272' (Cut 6' below GL)

Cement Plugs: 66' (56 sx) plug in 13 3/8" casing at 0 – 66'  
100' (77 sx) plug in 13 3/8" casing at 588 – 688' (half in & out csg shoe)  
110' (30 sx) plug in 9 5/8" casing at 5690 - 5800' (half in & out csg)  
110' (30 sx) plug in 8 3/4" OH at 6990 - 7100'  
110' (30 sx) plug in 8 3/4" OH at 8290 - 8400'  
110' (30 sx) plug in 8 3/4" OH at 6990 - 7100'  
110' (30 sx) plug in 8 3/4" OH at 9990 - 10100'  
110' (30 sx) plug in 8 3/4" OH at 11790 - 11900'  
110' (30 sx) plug in 8 3/4" OH at 13400 - 13510'

Procedure:

- 1) Locate plugged well at 2176278X, 348774 Y Section 28 T17S-R17E.
- 2) Prepare location.
- 3) Dig out to surface plate. Tap surface plate to determine if there is any trapped pressure inside surface casing.
- 4) Weld on extension to 13 3/8" casing to get surface pipe above GL. Weld on Cameron 5000 psi casing head.
- 5) MI and RU workover rig and reverse unit and tanks.
- 6) NU 5000 psi BOP. Test BOP to 5000 psi. NU bell nipple so circulation goes to an open top reverse unit steel tank.
- 7) Pick up 12-1/4" Piranha mill , 1 - 8" drill collar and drill pipe.
- 8) Drill out surface cement plug at 6' to 66'.
- 9) POH and laydown 8" drill collar. PU 6 – 6-1/4" drill collars.
- 10) Run in hole with mill, DC and drill pipe to cement plug at 588'.
- 11) Drill out cement plug at 588 - 688'.

BTA Oil Producers  
NM-114969: Owl Draw Unit, 20504 JV-P #1 SWD  
API: 30-015-10730  
Eddy County, New Mexico

RE: Plugging and Abandonment Requirements – Conditions of Approval

1. OK
2. OK
3. OK
4. OK
5. OK
6. OK
7. OK
8. OK
9. OK
10. OK
11. OK
12. OK
13. OK
14. OK (Stub plug)
15. OK
16. OK
17. Tag a minimum 110' above depth that plug was spotted – Otherwise OK
18. WOC 4 hours and tag 110' above depth that plug was spotted – Otherwise OK  
(Protection plug)
19. WOC 4 hours and tag at 578' or shallower – Otherwise OK (Casing shoe)
20. OK (Surface)
21. OK
22. OK
23. Submit a subsequent report to the BLM.

See attached standard COAs.

DHW 062110

## **BUREAU OF LAND MANAGEMENT**

**Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

### **Permanent Abandonment of Federal Wells Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well.

**Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
[www.blm.gov/nm](http://www.blm.gov/nm)



In Reply Refer To: 1310

### Interim Reclamation Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.

3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Environmental Protection Specialist  
575-234-5909, 575-361-2648 (Cell)

Cody Layton  
Natural Resource Specialist  
575-234-5959

Terry Gregston  
Environmental Protection Specialist  
575-234-5958

Trishia Bad Bear  
Natural Resource Specialist  
575-393-3612

Bobby Ballard  
Environmental Protection Specialist  
575-234-2230

Todd Suter  
Surface Protection Specialist  
575-234-5987

Randy Rust  
Environmental Protection Specialist  
575-234-5943

Doug Hoag  
Civil Engineering Technician  
575-234-5979

Linda Denniston  
Environmental Protection Specialist  
575-234-5974

Jennifer Van Curen  
Environmental Protection Specialist  
575-234-5905

Justin Frye  
Environmental Protection Specialist  
575-234-5922