

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-37485

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Long Draw 9 I

8. Well Number 1

9. OGRID Number  
14744

10. Pool name or Wildcat  
Cemetery Yeso 11795

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator PO Box 5270  
Hobbs, NM 88241

4. Well Location

Unit Letter I : 2310 feet from the South line and 330 feet from the East line  
Section 9 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3466'

RECEIVED

JUL 13 2010

NMOOD ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/27/10... MI & spud 11" hole. Ran 830' 8 5/8" 24# J55 ST&C csg. Cemented with 100 sks Thixad H w/additives. Mixed @ 14.6 #/g w/1.51 yd. Tail with 400 sks Class C w/2% CaCl2. Mixed @ 14.8/g w/1.34 yd. Plug down @ 5:45 am  
06/29/10. Circ 150 sks to pit. WOC 18 hrs. At 11:15 pm 06/29/10 tested BOPE & csg to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

07/03/10 TD'ed 7 7/8" hole @ 3020'. Ran 3020' 4 1/2" 11.6# J55 LT&C csg. Cemented w/400 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5/g w/2.71 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8/g w/1.33 yd. Plug down @ 3:00 am 07/04/10. Circ 107 sks cmt to pit. At 3:00 am 07/04/10, tested csg to 1500# for 30 mins, held OK. Set wellhead slips w/40k.

07/04/10...Released rig at 12:00 pm.

Spud Date: 06/27/10

Rig Release Date: 07/04/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 07/12/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supv. DATE 7-13-10

Conditions of Approval (if any):