

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

pm


OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-23728

5. Indicate Type of Lease
STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
SWD-247-A

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other SWD	7. Lease Name or Unit Agreement Name Dorstate SWD
2. Name of Operator Mesquite SWD, Inc.	8. Well Number 001
3. Address of Operator P.O. Box 1479 Carlsbad, NM 88221	9. OGRID Number 161968
4. Well Location Unit Letter <u>H</u> : <u>1980</u> feet from the <u>N</u> line and <u>660</u> feet from the <u>E</u> line Section <u>27</u> Township <u>25S</u> Range <u>28E</u> NMPM Eddy County	10. Pool name or Wildcat
11. Elevation (Show whether DR, RKB, RT, GR, etc) 2968 GR	



12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Plug-back and recompletion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/21/2010 RU w/BOP. Pulled injection pkr set at 6200'. Set CIBP @ 6200' with 10 sxs cement on top. Tagged at 6130'. Set CIBP at 3680' with 10 sxs cement on top.
6/23/2010 Tagged cement @ 3644'. Perf 1 SPF 0.42" @ 3488-3500, 3294-96', 3231-54, 3126-34, 3104-08, 3066-82, 3041-56, 3041-56, 2928-34, 3041-56, 2928-34, 2914-16, 2898-2900, 2890-92, 2877-80, 2780-82, 2716-18, 2648-62. Total 113 ft. Acid 5000 gal 15% HCL. Tested 4-1/2" csg found leak at 6'. Replaced top jt 4-1/2". Pressure 500 psi held 30 min. Displaced 2-3/8" tbg annulus w/inert fluid. Set Lok-Set disposal pkr at 2620'. Well ready for MIT.

6/21/2010

7/1/2010

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kay Havenor TITLE Agent DATE 7/2/2010

Type or print name Kay Havenor E-mail address: KHavenor@georesources.com PHONE: 575-622-0283

For State Use Only

APPROVED BY: [Signature] TITLE Godoy DATE 7/13/2010
Conditions of Approval (if any):