

# OPERATOR'S COPY

Form 9-331  
(May 1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.  
NM-9402

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

30.015.22832

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cottonwood KI Fed Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 17-16S-25E  
Unit J NMMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

1980' FSL & 1980' FEL of Section 17-16S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3542' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Set Production Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 7400' - Ran 5½" casing as follows: 24 joints of 5½" 17# K-55 LT&C (1013'); 153 joints of 5½" 15.5# K-55 ST&C (6349'); 1 joint 17# K-55 (42') (Total 7404') of casing set at 7400'. 1-Guide Shoe at 7400', 1-Diff-Fill Collar at 7359'. Used 8 centralizers. Cemented w/250 gallons mud flush, 525 sacks Howco-Lite, 4/10% CFR-2, 2/10% Halad-22, 3#/sack KCL, tailed in w/125 sacks Class C, 4/10% CFR-2, 2/10% Halad-22, 3#/sack KCL. PD 9:30 AM 6-20-79. WOC and tested to 1500# OK. Ran Temperature Survey and found top of cement at 4790'.

RECEIVED

AUG 7 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

Ant to Peter  
8-14-79

18. I hereby certify that the foregoing is true and correct

SIGNED

Christina Anderson

TITLE

Geol. Secty

DATE

8-6-79

(This space for Federal or State office use)

APPROVED BY

George H. Stewart

TITLE

ACTING DISTRICT ENGINEER

DATE

AUG 8 - 1979

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side