Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103		
District I	Energy, Minera	ls and Natura	1 Resources			May 27, 2004
1625 N French Dr , Hobbs, NM 88240				WELL API N		
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION			30-015-37803		
District III	1220 South St. Francis Dr.			5. Indicate T		_
1000 Rio Brazos Rd., Aztec, NM 87410	Santa	Fe, NM 875	05	STAT		<u> </u>
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Suitu	. 0, 1 1111 0 / 5		6. State Oil &	& Gas Lease No.	
87505	·					
	CES AND REPORTS			7. Lease Nan	ne or Unit Agreem	ent Name
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DI "ATION FOR PERMIT" (FO	EEPEN OR PLUG ORM C-101 <del>1 FOR</del>	SIME DA			
DIFFERENT RESERVOIR USE "APPLIPROPOSALS)  1. Type of Well: Oil Well	_ <b>r</b>	DECE	IAED	Spiketail 5 S		
1. Type of Well: Oil Well	Gas Well  Other	III C	1 0100	8. Well Numb	per	
		AUG 2	5 2010	004		
2. Name of Operator	,	1	DTESIA	9. OGRID N	umber	
Cimarex Energy Co. of Colorado	) 	LNMOCD	ARTESIA	162683		
3. Address of Operator		1414.		10. Pool nam	ne or Wildcat	
600 N. Marienfeld, Ste. 600; M	dland, TX 79701			Empire; Glo	rieta-Yeso	
4. Well Location						
SHL Unit Letter F: 198	o feet from the	North li	ne and 1650	feet from the	e <u>West</u> lin	e
Section5Township_	17S Range	29E	NMPM	County	Eddy	
THE WAS THE UNITED BY					184 · 1885 · 1,324	
Research Committee of the Committee of t	3642' GR		,			
Pit or Below-grade Tank Application 🔲 🤇	or Closure 🗌			EAST.		<u> </u>
Pit type Depth to Groundwater	Distance from n	earest fresh wate	r well I	Distance from nea	rest surface water	
Pit Liner Thickness:	Below-Grade Tank: Vo	olume	bbls; Cons	truction Material	1	
	Annuanista Day ta	Indianta Nat				
	Appropriate Box to	indicate Nat	<del></del>			<del></del>
NOTICE OF IN					REPORT OF:	
<u> </u>	PLUG AND ABAN		REMEDIAL WORK		☐ ALTERING C	ASING H
	CHANGE PLANS		COMMENCE DRI			낵
			CASING/CEMENT	JOB	$\boxtimes$	
OTHER:	······································		OTHER:			
13. Describe proposed or complete						
starting any proposed work). S	EE RULE 1103. For M	Iultiple Compl	etions: Attach we	llbore diagram	of proposed comp	letion or
recompletion.						
<u>05-27-10</u> Spudded 16" hole.						
05-28-10 Ran 11¾" 42# H-40 S	-					D-46 + 2#
D-42 + 0.125# D-130	(wt 12.9, yld 1.99) ar	A Tail 200 av	Cl			
Circulated 15 bbls to	•					
	surface. WOC 21 ho					
05-31-10 In 11" hole, ran 8%"		urs. Pressure	-tested casing to	o 1400 psi for	30 minutes.	1.34).
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125	urs. Pressure .' Cemented % D-130 (wt	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx	30 minutes. C + 5% D-55 + 109 c Class C + 2# D-4	1.34). % D-20 + 2 + 0.125#
05-31-10 In 11" hole, ran 8%"	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125	urs. Pressure .' Cemented % D-130 (wt	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx	30 minutes. C + 5% D-55 + 109 c Class C + 2# D-4	1.34). % D-20 + 2 + 0.125#
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120	urs. Pressure .' Cemented % D-130 (wt	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx	30 minutes. C + 5% D-55 + 109 c Class C + 2# D-4	1.34). % D-20 + 2 + 0.125#
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-1 D-130 (wt 14.8, yld 1	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 s .es.	urs. Pressure .' Cemented % D-130 (wt	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx	30 minutes. C + 5% D-55 + 109 c Class C + 2# D-4	1.34). % D-20 + 2 + 0.125#
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-1 D-130 (wt 14.8, yld 1 2000 psi for 30 minut	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 : .es. ole (5178').	urs. Pressure .' Cemented .% D-130 (wt sx to surface.	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 s) . Pressure-te	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat	1.34). % D-20 + 2 + 0.125# e casing to
05-31-10 In 11" hole, ran 8%" 3 0.2% D-46 + 1.5% D-2 D-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5½" 17# P-110 L	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 s .es. ole (5178'). FC to 5178.' Cemento	urs. Pressure .' Cemented .% D-130 (wt sx to surface. ed with <b>Lead</b>	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx . Pressure-te	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2	1.34). % D-20 + 2 + 0.125# e casing to 0 + 0.2% D-
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-1 0-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# D	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 s .es. ole (5178'). IC to 5178.' Cemento -42 + 0.125# D-130 (	urs. Pressure .' Cemented .% D-130 (wt sx to surface. ed with <b>Lead</b> wt 12.4, yld 2	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and <b>Tail</b> 25	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx . Pressure-te	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2	1.34). % D-20 + 2 + 0.125# e casing to 0 + 0.2% D-
05-31-10 In 11" hole, ran 8%" 3 0.2% D-46 + 1.5% D-2 D-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# E D-46 + 0.3% D-13 (wt	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). FC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circula	urs. Pressure .' Cemented .% D-130 (wt sx to surface. ed with <b>Lead</b> wt 12.4, yld 2	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and <b>Tail</b> 25	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx . Pressure-te	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2	1.34). % D-20 + 2 + 0.125# e casing to 0 + 0.2% D-
05-31-10 In 11" hole, ran 8%" : 0.2% D-46 + 1.5% D-1 0-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# D	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). FC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circula	urs. Pressure .' Cemented .% D-130 (wt sx to surface. ed with <b>Lead</b> wt 12.4, yld 2	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and <b>Tail</b> 25	o 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 sx . Pressure-te	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2	1.34). % D-20 + 2 + 0.125# e casing to
05-31-10 In 11" hole, ran 8%":  0.2% D-46 + 1.5% D-1  D-130 (wt 14.8, yld 1  2000 psi for 30 minut  06-04-10 Reached TD of 7%" h  06-05-10 Ran 5%" 17# P-110 L'  46 + 1% D-112 + 3# E  D-46 + 0.3% D-13 (wt  06-16-10 Ran CBL and TOC is 0	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). FC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circula	urs. Pressure .' Cemented .% D-130 (wt sx to surface. ed with <b>Lead</b> wt 12.4, yld 2 ated 103 sx to	-tested casing to with <b>Lead</b> 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and <b>Tail</b> 250 o surface.	2 1400 psi for 2 50/50 POZ ( 2 nd <b>Tail</b> 500 s) 3 Pressure-te 2 C + 5% D-44 3 0 sx PVL + 0.2	30 minutes. C + 5% D-55 + 10% C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D	1.34). % D-20 + 2 + 0.125# e casing to 0 + 0.2% D- -167 + 0.2%
05-31-10 In 11" hole, ran 8%" 3 0.2% D-46 + 1.5% D-2 D-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# E D-46 + 0.3% D-13 (wt	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulation	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with Lead wt 12.4, yld 2 ated 103 sx to	tof my knowledge	2 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 s) . Pressure-te 2 C + 5% D-44 0 sx PVL + 0.2	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%
05-31-10 In 11" hole, ran 8%":  0.2% D-46 + 1.5% D-2  D-130 (wt 14.8, yld 1  2000 psi for 30 minut  06-04-10 Reached TD of 7%" h  06-05-10 Ran 5½" 17# P-110 L  46 + 1% D-112 + 3# D  D-46 + 0.3% D-13 (wt  06-16-10 Ran CBL and TOC is 0  I hereby certify that the information grade tank has been/will be constructed on	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulation	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with Lead wt 12.4, yld 2 ated 103 sx to  olete to the besi CD guidelines  ,	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and Tail 250 c surface.	2 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 s) . Pressure-te 2 C + 5% D-44 0 sx PVL + 0.2	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%
05-31-10 In 11" hole, ran 8%":  0.2% D-46 + 1.5% D-1  D-130 (wt 14.8, yld 1  2000 psi for 30 minut  06-04-10 Reached TD of 7%" h  06-05-10 Ran 5%" 17# P-110 L  46 + 1% D-112 + 3# E  D-46 + 0.3% D-13 (wt  06-16-10 Ran CBL and TOC is 0	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulation	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with Lead wt 12.4, yld 2 ated 103 sx to  olete to the besi CD guidelines  ,	tof my knowledge	2 1400 psi for x 50/50 POZ ( nd <b>Tail</b> 500 s) . Pressure-te 2 C + 5% D-44 0 sx PVL + 0.2	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.
05-31-10 In 11" hole, ran 8%" 0.2% D-46 + 1.5% D-10-130 (wt 14.8, yld 12000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5½" 17# P-110 L46 + 1% D-112 + 3# ED-46 + 0.3% D-13 (wt 06-16-10 Ran CBL and TOC is 00 I hereby certify that the information grade tank has been/will be constructed or SIGNATURE	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulate .'	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with <b>Lead</b> wt 12.4, yld 2 ated 103 sx to  plete to the besi D guidelines  Reg	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC .19) and Tail 250 surface.	o 1400 psi for x 50/50 POZ (nd Tail 500 s). Pressure-te  OZ C + 5% D-40 sx PVL + 0.2  e and belief. It or an (attached) a	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.
05-31-10 In 11" hole, ran 8%" 0.2% D-46 + 1.5% D-10 D-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# D D-46 + 0.3% D-13 (wt 06-16-10 Ran CBL and TOC is 0 I hereby certify that the information grade tank has been/will be constructed or SIGNATURE	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulate .'	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with <b>Lead</b> wt 12.4, yld 2 ated 103 sx to  plete to the besi D guidelines  Reg	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC 19) and Tail 250 c surface.	o 1400 psi for x 50/50 POZ (nd Tail 500 s). Pressure-te  OZ C + 5% D-40 sx PVL + 0.2  e and belief. It or an (attached) a	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.
05-31-10 In 11" hole, ran 8%" 0.2% D-46 + 1.5% D-10-130 (wt 14.8, yld 12000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5½" 17# P-110 L46 + 1% D-112 + 3# ED-46 + 0.3% D-13 (wt 06-16-10 Ran CBL and TOC is 00 I hereby certify that the information grade tank has been/will be constructed or SIGNATURE	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulate .'	urs. Pressure .' Cemented .% D-130 (wt sx to surface.  ed with <b>Lead</b> wt 12.4, yld 2 ated 103 sx to  plete to the besi D guidelines  Reg	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC .19) and Tail 250 surface.	o 1400 psi for x 50/50 POZ (nd Tail 500 s). Pressure-te  OZ C + 5% D-40 sx PVL + 0.2  e and belief. It or an (attached) a	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.
05-31-10 In 11" hole, ran 8%"  0.2% D-46 + 1.5% D-1  D-130 (wt 14.8, yld 1  2000 psi for 30 minut  06-04-10 Reached TD of 7%" h  06-05-10 Ran 5%" 17# P-110 L  46 + 1% D-112 + 3# D  D-46 + 0.3% D-13 (wt  06-16-10 Ran CBL and TOC is 0  I hereby certify that the information grade tank has been/will be constructed on SIGNATURE  Type or print name  Natalie Kru  For State Use Only	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulate .'	urs. Pressure .' Cemented .' Cemented .w D-130 (wt .sx to surface.  ed with Lead .wt 12.4, yld 2 .ated 103 sx to	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC19) and Tail 250 surface.	o 1400 psi for x 50/50 POZ (nd Tail 500 s). Pressure-te  OZ C + 5% D-40 sx PVL + 0.2  e and belief. It or an (attached) a DAT Teleph	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx E August 23, 20 one No. 432-620	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.  210 -1936
05-31-10 In 11" hole, ran 8%" 0.2% D-46 + 1.5% D-10 D-130 (wt 14.8, yld 1 2000 psi for 30 minut 06-04-10 Reached TD of 7%" h 06-05-10 Ran 5%" 17# P-110 L 46 + 1% D-112 + 3# D D-46 + 0.3% D-13 (wt 06-16-10 Ran CBL and TOC is 0 I hereby certify that the information grade tank has been/will be constructed or SIGNATURE	24# K-55 STC to 1236 .12 + 2# D-42 + 0.125 .35). Circulated 120 stes. ole (5178'). TC to 5178.' Cemento -42 + 0.125# D-130 ( .13, yld 1.39). Circulate .'	urs. Pressure .' Cemented .' Cemented .w D-130 (wt .sx to surface.  ed with Lead .wt 12.4, yld 2 .ated 103 sx to	tested casing to with Lead 120 s 11.8, yld 2.58) a WOC 19.75 hrs 400 sx 35/65 PC .19) and Tail 250 surface.	o 1400 psi for x 50/50 POZ (nd Tail 500 s). Pressure-te  OZ C + 5% D-40 sx PVL + 0.2  e and belief. It or an (attached) a DAT Teleph	30 minutes. C + 5% D-55 + 109 C Class C + 2# D-4 sted intermediat 4 bwow + 6% D-2 % D-65 + 0.2% D  further certify that an alternative OCD-approx	1.34).  % D-20 + 2 + 0.125# e casing to  0 + 0.2% D167 + 0.2%  y pit or below- oved plan □.  210 -1936