

DISTRICT I  
1625 N. French Dr., Hobbs, NM 88240  
DISTRICT II  
1301 W. Grand Avenue, Artesia, NM 88210  
DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410  
DISTRICT IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-102  
Revised July 16, 2010

Submit one copy to appropriate  
District Office

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number <b>30-015-38136</b>	Pool Code 96210	Pool Name Empire; Glorieta-Yeso
Property Code	Property Name PONDHAWK "32" STATE	Well Number 30
OGRID No. 162683	Operator Name CIMAREX ENERGY CO. OF COLORADO	Elevation 3646'



Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	32	16 S	29 E		990	SOUTH	330	WEST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 40	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p><b>OPERATOR CERTIFICATION</b></p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><u>Zeno Farris</u> 8/31/2010 Signature Date</p> <p>Zeno Farris Printed Name</p> <p>zfarris@cimarex.com Email Address</p> <p><b>SURVEYOR CERTIFICATION</b></p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p> Date Surveyed Signature &amp; Seal of Professional Surveyor</p> <p>Certificate No. Gary L. Jones 7977 BASIN SURVEYS 23132</p>
---	--

Mud, Casing, Cementing, and BOP Attachment  
**Pondhawk 32 State No. 30**  
Cimarex Energy Co. of Colorado  
Unit M, Section 32  
T16S-R29E, Eddy County, NM

In response to questions asked under Section II B of Bulletin NTL-6, the following information is provided for your consideration:

Location: 990 FSL & 330 FWL

Elevation above sea level: 3646' GR

Proposed drilling depth: 6000'

Proposed Mud Circulating System:

Depth	Mud Wt	Visc	Fluid Loss	Type Mud
0' to 450'	8.4 - 8.6	28	NC	FW
0' to 1100'	10.0	30-32	NC	Brine water
0' to 6000'	8.4 - 9.5	30-32	NC	FW, brine

Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

Mud, Casing, Cementing, and BOP Attachment  
**Pondhawk 32 State No. 30**  
 Cimarex Energy Co. of Colorado  
 Unit M, Section 32  
 T16S-R29E, Eddy County, NM

Casing & Cementing Plan:

String	Hole Size	Depth		Casing OD		Weight	Collar	Grade
Surface	16"	0'	to 450'	New	11¾"	42#	STC	H-40
Intermediate	11"	0'	to 1100'	New	8⅝"	24#	STC	J-55
Production	7⅝"	0'	to 6000'	New	5½"	17#	LTC	P-110

Cementing Plan:

Surface	530 sx Class H + 2% CaCl <sub>2</sub> (wt 14.8, yld 1.34) TOC Surface
Intermediate	Lead: 300 sx Class C Lite + 6# Salt + 1/4# CF (wt 12.7, yld 1.99) Tail: 200 sx Class C + 2% CaCl <sub>2</sub> (wt 14.8, yld 1.34) TOC Surface
Production	Stage 1 580 sx 50/50/2 Class C + 1% FL25 + 0.3% FL52 + 5% Salt + 0.5% SMS (wt 13, yld 1.68) Stage 2 Lead: 550 sx Class H Lite + 6# Salt + 1/4# CF (wt 12.7, yld 1.92) Tail: 200 sx Class H + 2% CaCl <sub>2</sub> (wt 13, yld 1.68) TOC 900'

Fresh water zones will be protected by setting 11¾" casing at 450' and cementing to surface. Hydrocarbon zones will be protected by setting 8⅝" casing at 1100' and cementing to surface, and by setting 5½" casing at 6000' and cementing to 900.'

<u>Collapse Factor</u>	<u>Burst Factor</u>	<u>Tension Factor</u>
1.125	1.125	1.6

Pressure control Equipment:

An 11¾" 3000 PSI working pressure B.O.P. consisting of a one set of blind rams and one set of pipe rams and a 3000 psi annular-type preventor. A choke manifold and 120 gallon accumulator with floor and remote operating stations and auxiliary power system. A kelly cock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor. Test BOP equipment and choke manifold to 250 psi low and 3000 psi high and annular BOP to 250 psi low and 1500 psi high by an independent service company.

BOP unit will be hydraulically operated. Below intermediate casing shoe, BOP will be operated at least once a day while drilling and the blind rams will be operated when out of hole during trips. No abnormal pressure or temperature is expected while drilling. From the base of the surface pipe through the running of production casing, the well will be equipped with a 3000 psi BOP system.

BOPS will be tested by an independent service company to 250 psi low and 3000 psi high. Hydril will be tested to 250 psi low and 1500 psi high.